



HIKVISION TVI Camera



Time ColorVu camera



Fish-eye Camera



HIKVISION PTZ Camera



HIKVISION IP Camera

APAQ HIKVISION PRODUCT



HIKVISION NVR



HIKVISION DVR



HIKVISION Switch



SFP Module

HIKVISION Product Price List

Date:1-4-2024

Model	Descriptions	SRP(RM)
HIKVISION TVI Camera		
DS-2CE16D0T-EXIF	2MP CMOS Sensor, 1 pcs EXIR LEDs, 20m IR, Outdoor EXIR Bullet, ICR, 0.02 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 2.8mm/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output	63
DS-2CE76D0T-EXIPF	2MP CMOS Sensor, 12 pcs SMD LEDs, 20m IR, Indoor IR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 2.8mm/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output	51
DS-2CE19D0T-VFIT3F (2MP Vari-focal)	2MP Vari-focal CMOS Sensor, 2.8~12mm VF Lens , 42 pcs IR LEDs, 40m IR, Outdoor IR Vari-focal Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, Support TVI/AHD/CVI/CVBS video signal output	180
DS-2CE5AD0T-VPIT3F(C) (2MP Vari-focal)	2MP Vari-focal CMOS Sensor, 2.8~12mm VF Lens, EXIR, 40m IR, Outdoor IR Vari-focal Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Vandal Proof, 2.8~12mm Lens,Support TVI/AHD/CVI/CVBS video signal output	180
DS-2CE16D0T-ITFS	2MP Audio CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, 30m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic,Audio up Coaxial(Only TVI) , OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens, Support TVI/AHD/CVI/CVBS video signal output,	89
DS-2CE76D0T-ITPFS	2MP Audio @25fps(P)(Default)/30fps(N), 4in1 TVI/AHD/CVI/CVBS video signal output ,2MP CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic,Audio up Coaxial(Only TVI) ,OSD Menu(Up the Coax), 2.8/3.6/6mm Lens	77
DS-2CE16H0T-ITF	5MP @20fps, 4MP@25fps(P)/30fps(N)(Default) , EXIR, 30m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.4/2.8/3.6/6mm Lens, Support TVI/AHD/CVI/CVBS video signal output	105
DS-2CE76H0T-ITPF	5MP @20fps, 4MP@25fps(P)/30fps(N)(Default) , EXIR, 20m IR, Indoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), 2.4/2.8/3.6/6mm Lens,Support TVI/AHD/CVI/CVBS video signal output	93
DS-2CE19H0T-AIT3ZF (5MP Vari-focal)	5MP Vari-focal , 5MP@20fps , 4MP@25fps(P)/30fps(N)(Default) , EXIR, 40m IR, Outdoor EXIR, ICR, 0.01 Lux/F1.2, 12VDC/24VAC, Smart IR, DNR, OSD Menu(Up the Coax), IP67, 2.7~13.5mm Motorized Vari-focal Lens,Support TVI/AHD/CVI/CVBS video signal output, 2.7~13.5mm Motorized Vari-focal Lens	277
DS-2CE5AH0T-AVPIT3ZF (5MP Vari-focal)	5MP Vari-focal 5MP@20fps , 4MP@25fps(P)/30fps(N)(Default) , EXIR, 40m IR, Outdoor EXIR, ICR, 0.01 Lux/F1.2, 12VDC/24VAC, Smart IR, DNR, OSD Menu(Up the Coax), IP67,IK10, Motorized Vari-focal Lens, Support TVI/AHD/CVI/CVBS video signal output, 2.7~13.5mm Motorized Vari-focal Lens	277
DS-2CE16H0T-ITFS	5MP Audio @20fps, 4MP@25fps(P)/30fps(N)(Default) , Out Door EXIR Bullet, 30m IR, 4in1 TVI/AHD/CVI/CVBS video signal output, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic,Audio up Coaxial(Only TVI),OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens	126
DS-2CE76H0T-ITPFS	5MP Audio @20fps, 4MP@25fps(P)/30fps(N)(Default) , EXIR, 20m IR, Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic,Audio up Coaxial(Only TVI),OSD Menu(Up the Coax), 2.8/3.6/6mm Lens,Support TVI/AHD/CVI/CVBS video signal output	113
DS-2CE16U0T-ITF	8.3MP @12.5fps(Default) , 4in1 TVI/AHD/CVI/CVBS video signal output 5MP@20fps,4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N) , EXIR, 30m IR, Outdoor EXIR Bullet , ICR, 0.01 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu(Up the Coax), IP67,2.8/3.6/6mm Lens	165
DS-2CE76U0T-ITPF	8.3MP @12.5fps(Default) , 4in1 TVI/AHD/CVI/CVBS video signal output 5MP@20fps,4MP@25fps(P)/30fps(N),2MP@25fps(P)/30fps(N) , EXIR, 30m IR, Indoor EXIR Turret,ICR, 0.01 Lux/F1.2, 12VDC, Smart IR,DNR, OSD Menu(Up the Coax), 2.8/3.6/6mm Lens	143
ADS-12FG-12N 12012EPB, 12V/1A Φ2.1	12V 1A Power Adpater ,1000mA 12W 5.5x2.1mm Power AC Adapter for DVE XtremMac router,switches,mini TV,TV box,chargers,wireless,MP3/MP4,mobile DVD,telephones,cameras	13
HIKVISION PIR Camera		
DS-2CE11H0T-PIRLO	5MP PIR @20fps, 4MP@25fps(P)/30fps(N)(Default) , Metal, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, PIR Detection,Led Alarm,Alarm out ,Smart IR,DNR,OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens	128
DS-2CE71H0T-PIRLO	5MP PIR @20fps, 4MP@25fps(P)/30fps(N)(Default) ,EXIR, 20m IR, Outdoor EXIR Turret, ICR, 0.01 Lux/F1.2, 12 VDC, PIR Detection,Led Alarm,Alarm out ,Smart IR,DNR,OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens	128
HIKVISION 24 Hours Full Time ColorVu camera		
DS-2CE10DF3T-FS	2MP 20m Light 4in1 WDR ColorVu Bullet Metal, Built-in Mic,Audio up Coaxial(Only TVI) , 2M BSI CMOS Sensor,Outdoor mini Bullet,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,20M,3D DNR,DC 12V,OSD Menu(Up the Coax), 130dB True WDR , IP67, 2.8/3.6mm Lens,24H Color,Support TVI/AHD/CVI/CVBS video signal output	153
DS-2CE70DF3T-PFS	2MP 20m Light 4in1 WDR ColorVu Dome,Built-in Mic,Audio up Coaxial(Only TVI) , 2M BSI CMOS Sensor,Indoor Turret,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,20M,3D DNR,DC 12V,OSD Menu(Up the Coax), 130dB True WDR , 2.8/3.6mm Lens,24H Color,Support TVI/AHD/CVI/CVBS video signal output	140
DS-2CE10KF0T-FS	3K(5MP) 20m Light 4in1 WDR ColorVu Bullet , (5MP 16:9), CMOS Sensor,3K @ 20 fps(Default),Outdoor Bullet,0.001Lux/F1.0,0 Lux with white Light,20m,2D DNR,Built-in Mic,Audio up Coaxial(Only TVI),12 VDC,OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens,24H Color, Support TVI/AHD/CVI/CVBS_video signal output	166

DS-2CE72HFT-F	SMP 20m Light 4in1 WDR ColorVu Dome, SMP BSI CMOS Sensor,5MP@20fps, 4MP@25fps(P)/30fps(N)(Default),Outdoor Turret,0.0005Lux/F1.0, 0 Lux with Friendly Lighting,20m,3D DNR,12 VDC,OSD Menu(Up the Coax), 130dB True WDR, IP67, 3.6/6mm Lens,24H Color , Support TVI/AHD/CVI/CVBS video signal output	154
HIKVISION IP Camera		
DS-2CD1123G0E-I(L)	2MP, 1/2.8" Progressive CMOS, ICR, 1920x1080: 20fps, H.265/H.264+&H.264 , 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included	144
DS-2CD1023G0E-I(L)	2MP, 1/2.8" Progressive CMOS, ICR, 1920x1080:20fps, H.265/H.264+&H.264 , 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included	139
DS-2CD1143G0-I	4MP, 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N) , H.265+/H265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included	242
DS-2CD1043G0-I	4MP, 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N) , H.265+/H265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connec *power supply no included	231
DS-2CD1153G0-I	5MP,1/2.7" Progressive CMOS, ICR, 2560*1920:15fps(P)/(N), 2304x1296:25fps(P)/30fps(N) , H.265+/H265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included	294
DS-2CD1053G0-I	5MP,1/2.7" Progressive CMOS, ICR, 2560*1920:15fps(P)/(N), 2304x1296:25fps(P)/30fps(N) , H.265+/H265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connec *power supply no included	280
DS-2CD1723G0-IZ	2MP Motorized Vari-focal, 1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N) , H.265+/H265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect *power supply no included	394
DS-2CD1A23G0-IZU	2MP Motorized Vari-focal, 1/2.7" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N) , H.265+/H.265/H.264+&H.264, 3D DNR, BLC, IR range: up to 50m, DC12V & PoE, TF card slot, PT function (P:-100°~100°, T: -45°~20°), Support mobile monitoring via Hik-Connect *power supply no included	351
DS-2CD1743G0-IZ	4MP Motorized Vari-focal, 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N) , 2304x1296:25fps(P)/30fps(N),H.265+/H.265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect *power supply no included	438
DS-2CD1A43G0-IZU	4MP Motorized Vari-focal, 1/3" Progressive CMOS, 4MP motorized vari-focal lens, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N) , H.265+/H265/H.264+&H.264, 3D DNR,WDR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect *power supply no included	380
DS-2CD1753G0-IZ	5MP Motorized Vari-focal, 1/2.7" Progressive CMOS, ICR, 2560*1920:15fps(P)/(N) , 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect *power supply no included	496
DS-2CD1653G0-IZ	5MP Motorized Vari-focal, 1/2.7" Progressive CMOS, ICR, 2560*1920:15fps(P)/(N) , 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring via Hik-Connect *power supply no included	496
DS-2CD2143G2-I	4MP IP AcuSense Dome, 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG ; Powered by Darkfighter technology, Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3200x1800), 25fps/30fps (2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;	370
DS-2CD2043G2-I	4MP IP AcuSense Bullet, 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG ; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service	370
DS-2CD2183G2-I	8MP IP AcuSense Dome, 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG ; Powered by Darkfighter technology, Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (3200x1800, 2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;	474
DS-2CD2083G2-I	8MP IP AcuSense Bullet, 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG ; Powered by Darkfighter technology, Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (3200x1800, 2688x1520, 1920x1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;	474
DS-2CD2345G0P-I	Ultra Wide Angle EXIR Turret Camera, 1/2.7" Progressive Scan CMOS; 4MP, H.265+/H.265/H.264+/H.264/MJPEG ; Color: 0.028 lux@(F2.0, AGC ON), 0 lux with IR; 25fps/24fps (2688x1520); VCA functions; dual streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 10m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service	496

DS-2CD2T45G0P-I	Ultra Wide Angle EXIR Bullet Camera, 1/2.7" Progressive Scan CMOS; 4MP,H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.028 lux@(F2.0, AGC ON), 0 lux with IR; 25fps/24fps (2688x1520); VCA functions; dual streams; 3D DNR; BLC/HLC; ICR; EXIR, up to 10m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service	567
DS-2CD1323G2-IUF	1/2.8" Progressive CMOS, ICR, 2MP Built-in Microphone , 1920x1080:25fps(P)/30fps(N), build in TF card slot, H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Motion 2.0 human and vehicle classification, Support mobile monitoring via Hik-Connect; *power supply no included	180
DS-2CD1023G2-IUF	1/2.8" Progressive CMOS, ICR, 2MP Built-in Microphone , 1920x1080:25fps(P)/30fps(N), build in TF card slot,H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Motion 2.0 human and vehicle classification, Support mobile monitoring via Hik-Connect;*power supply no included	180
DS-2CD1343G0-IUF	1/3" Progressive CMOS, ICR, 4MP Built-in microphone , 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N),Built-in Microphone, TF card slot, H.265+/H265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connec *power supply no included	251
DS-2CD1043G0-IUF	1/3" Progressive CMOS, ICR, 4MP Built-in microphone 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE,Support mobile monitoring via Hik-Connec *power supply no included	251
DS-2CV2Q21FD-IW	1/2.8" Progressive CMOS, ICR, 0lux with IR, 2MP 1920x1080: 25fps(P)/30fps(N), 2.8/4mm lens,H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, Hik-Connect cloud service, Built-in microphone and speaker, support two-way audio . Built-in Wi-Fi, 5VDC power supply. Default: SD card is not included.	177
DS-2CD1027G0-L	2MP ColorVu IP Bullet , 1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, up to 30m warm light , F1.0, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included	187
DS-2CD1127G0-L	2MP ColorVu IP Dome , 1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, up to 30m warm light , F1.0, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included	187
DS-2CD1047G0-L	4MP ColorVu IP Bullet , 1/2.7" Progressive CMOS, ICR, 2560x1440:20fps, H.265+/H.265/H.264+&H.264, 3D DNR, BLC, up to 30m warm light , F1.0, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included	289
DS-2CD1147G0-L	4MP ColorVu IP Dome , 1/2.7" Progressive CMOS, ICR, 2560x1440:20fps, H.265+/H.265/H.264+&H.264, 3D DNR, BLC, up to 30m warm light , F1.0, DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included	289
HIKVISION PTZ Camera		
DS-2AE4225TI-D	2MP Turbo 4in1 PTZ , 1/2.8" CMOS, DWDR, ICR,Up to 100m IR distance, Color: 0.05lux/F1.6, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4-92.0mm,Digital zoom: 16x , 1920*1080:30fps, Pan Speed: 0.1° -80°/s, Tilt Speed: 0.1° -80°/s,12V DC IP66 c/w Wall mount bracket,Support TVI/AHD/CVI/CVBS video signal	1013
DS-2DE2C400MW-DE(F1)	4MP PT Dome Network Camera, 1/2.7" Progressive Scan CMOS,Color: 0.01 Lux @(F1.2,AGC ON), B/W: 0 Lux with IR, 2.8 mm, horizontal FOV 111.4°, vertical FOV 59.1°, diagonal FOV 133.6°,4 mm, horizontal FOV 91.5°, vertical FOV 46.1°, diagonal FOV 109.8 White Light Distance: up to 30 m IR Distance: up to 30 m Digital WDR, BLC, HLC, 3D DNR,Built-in Microphone,Built-in Speaker	322
DS-2DE2A404IW-DE3(C0)(S6)	4MP 4X Mini PTZ Network Camera, 1/3" CMOS,H.265+/H.265/H.264+/H.264 codec, 3D DNR, ICR,Color: 0.005lux/F1.6, B/W:0.001lux/F1.6, 4x optical zoom, Angle of View: 100° to 33° (Wide-Tele), Digital Zoom:16X, 2560 × 1440:30fps, Pan range:0°~355°; Tilt range: 0°~90°(Auto Flip), Pan Speed: 0.1° -100°/s, Tilt Speed: 0.1° -100°/s, 20m IR, POE&12VDC	557
DS-2DE3A400BW-DE(F1)(S5)	4MP ColorVu IP PT Camera, H.265+/H.265;120 dB WDR;12VDC & PoE;ColorVu;IP66 ; Built-in speaker and microphone for audible warning and two-way audio;White light flashing when alarm triggers, Accurate human and vehicle target classification and alarm, based on deep learning algorithm,Support face capture. Up to 5 faces captured at the same time	634
DS-2DE4225IW-DE(T5)	2MP 25X IP IR PTZ , 1/2.8" Progressive Scan CMOS,Up to 1920 × 1080 @30fps resolution Min. illumination:,Color: 0.005 Lux @ (F1.6, AGC ON),B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR, 25 × optical zoom, 16 × digital zoom, WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Up to 100 m IR distance, 12 VDC & POE (802.3at), Support H.265+/H.265 video compression, Accurate human and vehicle target classification and alarm based on deep learning algorithm Support face capture. Up to 5 faces captured at the same time, c/w Wall mount bracket	1271
DS-2DE5232IW-AE(S6)	2MP 32X IP IR PTZ , 1/2.8" Progressive Scan CMOS,Up to 1920 × 1080 @30fps resolution Min. illumination: Color: 0.005 Lux @ (F1.2, AGC ON), B/W: 0.001 Lux @(F1.2, AGC ON), 0 Lux with IR,32 × optical zoom, 16 × digital zoom,WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus,Up to 150 m IR distance,24 VAC & Hi-PoE,Support H.265+/H.265 video compression, Accurate human and vehicle target classification and alarm based on deep learning algorithm,Support face capture. Up to 5 faces captured at the same time, c/w Wall mount bracket	1837

DS-2DE4425IW-DE(T5)	4MP 25X IP IR PTZ , 1/2.8" Progressive Scan CMOS Up to 2560 × 1440 @30fps resolution Min. illumination: Color: 0.005Lux @ (F1.6, AGC ON),B/W: 0.001Lux @(F1.6, AGC ON), 0 Lux with IR 25 × optical zoom, 16 × digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus Up to 100 m IR distance 12 VDC & POE (802.3af) Support H.265+/H.265 video compression, Accurate human and vehicle target classification and alarm based on deep learning algorithm Support face capture. Up to 5 faces captured at the same time,c/w Wall mount bracket	1398
DS-1005KI	PTZ keyboard, Power supply and communication by USB port directly; 3D PTZ control and 2 joystick control buttons;Up to 15 programmable buttons are available;Support digital tube to display the input content;Support indicators to show the operation status of keyboard;	621
DS-1602ZJ	Wall Mount Bracket Indoor/Outdoor, Better water proof design, With safety rope, the assembling is safer and more convenient	73
DS-1663ZJ	Ceiling Mounting Bracket Indoor/Outdoor,Design of cable entrance hole, Complementary rubber blanket pad for waterproofness	39
HIKVISION Fish-eye Camera		
DS-2CD2955FWD-IS	5MP Network Fisheye Camera , 1/2.9" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.016 lux@(F2.2, AGC ON), 0 lux with IR; 20fps(2944×1656), 25fps/30fps(2560×1440, 2048×1536, 1920×1080); F2.2, field of view: 180°(H)×180°(V); 120dB WDR; 2 streams; 3D DNR; BLC; ICR; EXIR, up to 10m(optional); DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service,with Audio/Alarm I/O	926
DS-2CD6365G0E-IVS	6MP Network Fisheye Camera , H.265 , 1/1.8" progressive scan CMOS, 3072 x 2048@30fps,DNR,Lens 1.27mm @ F2.8, Angle of view: 180°(wall mount), 360°(ceiling mount),DC12V&PoE (802.3af), 15 meters IR range,Support up to 128Gon-board storage, Support 14 display modes in total (including display modes of different mount types): Fisheye View, 180 Panorama View, 4PTZ, Fisheye + 3PTZ, 360 Panorama View, 360 Panorama + PTZ,360 Panorama + 3PTZ, 360 Panorama + 6PTZ, 360 Panorama + 8PTZ, 2PTZ, Fisheye + 8PTZ, Panorama View, Panorama + 3PTZ, Panorama + 8PTZ	1923
DS-2PT3326IZ-DE3(2.8- 12mm)(2mm)	3 *2MP 128.5° Panoramic camera: 3 × 1/2.8" CMOS sensor, 2mm lens,3-ch 1920×1080 realtime video output,H.265,Horizontal angle of view: 128.5° × 3, Vertical angle of view: 75.7°,10m IR, 1* 2MP 4x PTZ camera: 1/2.8"CMOS sensor, H.265,Optical Zoom:4x, Focus:2.8-12mm Pan range:350°; Tilt range: 0°~90°, Pan Speed: 0.1°~30°/s, Tilt Speed: 0.1°~30°/s,	1398
DS-2SE4C225MWG- E(12F0)	TandemVu PTZ Bullet lens: Accurate human and vehicle target classification, alarm,based on deep learning algorithm 1/3" Progressive Scan CMOS Up to 1920 × 1080@30fps resolution Min. illumination: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with IR 30m with light PTZ lens:1/2.8" progressive scan CMOS Up to 1920 × 1080@30fps resolution Min. illumination: Color: 0.005 Lux @ (F1.5, AGC ON), B/W: 0.001 Lux @(F1.5, AGC ON), 0 Lux with IR 25 × optical zoom, 16 × digital zoom 100m IR WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus 12VDC, PoE+ Support H.265+/H.265 video compression	1749
HIKVISION Thermal IP Camera		
DS-2TD2617-3/QA	Strobe Light & Audio Alarm , Dual-stream, Streaming in H.265/H.264/MJPEG, Up to 20-ch simultaneous live view, Support Micro SD/SDHC/SDXC Card up to 256G, Audio & Alarm I/O, Open- ended API, Power in DC12V or PoE(802.3af), IP67	1274
DS-2TD2617-6/QA	Thermal camera Features: VOx UFPA 160x120 pixels, Pixel pitch 17 μm, NETD< 40mk, 25Hz thermal frame rate, Support contrast adjustment,15 palettes of color adjustable, smart features. Thermographic accuracy (Measurement range): ±8°C (-20~150°C) Visible camera Features: 1/2.7" CMOS sensor, 4MP(2688× 1520), 2.1mm/4mm/8mm fixed lens, up to 15m IR range, WDR, BLC 3D DNR, ROI	1274
DS-2TD2617-10/QA	Thermal Lens (FOV): 3.1 mm (50° × 37.2°) 6.2 mm (25° × 18.7°) 0.7 mm (14.06° × 10.8°)	1393
DS-2TD1217-2/QA	Strobe Light & Audio Alarm , Dual-stream, Streaming in H.265/H.264/MJPEG, Up to 20-ch simultaneous live view, Support Micro SD/SDHC/SDXC Card up to 256G, Audio & Alarm I/O, Open- ended API, Power in DC12V or PoE(802.3af), IP66 Thermal camera Features: VOx UFPA 160x120 pixels, Pixel pitch 17 μm, NETD< 40mk,	1274

DS-2TD1217-3/QA	25Hz thermal frame rate, Support contrast adjustment,15 palettes of color adjustable, smart features, Thermographic accuracy (Measurement range): ±8°C (-20~150°C) Visible camera Features: Support picture in picture preview. 1/2.7" CMOS sensor, 4MP(2688×1520), 2.1mm/4mm/8mm fixed lens, up to 15m IR range, WDR, BLC 3D DNR, ROI	1274
DS-2TD1217-6/QA	Thermal Lens (FOV): 1.8 mm (90° × 66.4°) 3.1 mm (50° × 37.2°) 6.2 mm (25° × 18.7°)	1274
Model		
HIKVISION DVR		
DS-7204HQHI-K1/E	4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input(up to 6-ch IP), H.265/H.265+ compression, 1 SATA interface,CH01:3MP @ 15fps, CH01-04:1920×1080P @15 fps, 4MP Lite@15fps/ch,260 1U case	241
DS-7208HQHI-K1/E	8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 4-ch IP video input(up to 12-ch IP), H.265/H.265+ compression, 1 SATA interface,CH01 & 02: 3MP @ 15fps, CH01-08:1920×1080P @15 fps, 4MP Lite@15fps/ch, 260 1U case	381
iDS-7216HQHI-M2/S	16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 1-ch face detection or 4-ch false alarm filter,16-ch video&1-ch audio input, H.265/H.265+ compression, 2 SATA interfaces, CH01-04: 3MP @ 15fps, CH01-16:1920×1080P @15 fps, 4MP Lite@15fps/ch, 4K UHD output, support CVBS output, 380 1U case	689
DS-7316HQHI-K4	16 Turbo HD/Analog self-adaptive interfaces input, 16-ch video&4-ch audio input, 4 SATA interfaces, 1920×1080P: 12 fps/ch, 1280×720P:25(P)/30(N) fps/ch, alarm I/O: 16/4, 1.5U 19" case,the first 4 channels support 3MP,Support Cloud storage	1574
iDS-7232HQHI-M2/S(E)	4-ch false alarm filter, 32 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 32-ch video&1-ch audio input, 8-ch IP video input(up to 40-ch IP), H.265/H.265+ compression, 2 SATA interfaces,CH01-32:1920×1080P @15 fps, 4MP Lite @15 fps/ch, 4K UHD output, support CVBS output, 380 1U case	1399
iDS-7204HQHI-M1/FA (Turbo HD X) 2nd Gen AcuSense	1-ch facial recognition or 2-ch false alarm filter, 4ch Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,CH01: 3MP @ 15fps,CH01-04:1920×1080P @15 fps, 4MP Lite@15fps/ch, support CVBS output, standalone 1U case	285
iDS-7208HQHI-M1/FA (Turbo HD X) 2nd Gen AcuSense	1-ch facial recognition or 4-ch false alarm filter, 8ch Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,CH01 & 02: 3MP @15fps, CH01-08:1920×1080P @15 fps, 4MP Lite@15fps/ch, support CVBS output, standalone 1U case	425
iDS-7216HQHI-M1/FA (Turbo HD X) 2nd Gen AcuSense	1-ch face recognition or 4-ch false alarm filter, 16ch Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,CH01-04: 3MP @15fps, CH01-16:1920×1080P @15 fps, 4MP Lite@15fps/ch, 4K UHD output, support CVBS output,standalone 1U case	722
DS-7204HUHI-K1/E	4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 4-ch IP video input(up to 8-ch IP), 1 SATA interface, H.265/H.265+ compression, 5MP:12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 260 1U case	348
iDS-7208HUHI-M1/E	8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,4-ch false alarm filter, 8-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 8-ch IP video input(up to 16-ch IP), 1 SATA interface,H.265/H.265+ compression, 8MP: 8fps, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, 260 1U case	580
iDS-7216HUHI-M2/S	16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 16-ch Motion Detection 2.0 or 4-ch false alarm filter, 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 2 SATA interfaces, H.265/H.265+ compression, 8MP: 8fps, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920×1080P: 25(P)/30(N) fps/ch, 4K UHD output, support CVBS output, 380 1U case	1217
iDS-7332HUHI-M4/S	32Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 32-ch video&4-ch audio input,8-ch IP video input(up to 40-ch IP),H.264/H.264+/H.265+/H.265 video compression,4 SATA interfaces, 5MP: 12 fps/ch,4MP: 15 fps/ch,Extended transmission distance over coax cable, 4K UHD output,alarm I/O: 16/4, 1.5U 19" case	3586
iDS-7204HTHI-M1/S©	4-ch false alarm filter, 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch HDTV coaxial video&audio input, 4-ch IP video input(up to 8-ch IP),H.265+/H.265 compression,1 SATA interfaces, 8 MP@15fps, 5 MP@20fps, 3 MP@18fps,4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), Extended transmission distance over coax cable, 4K UHD output,alarm, standalone 1U case	635
iDS-7208HTHI-M2/S©	8-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch HDTV coaxial video&audio input, 8-ch IP video input(up to 16-ch IP),H.265+/H.265 compression,2 SATA interfaces, 8 MP@15fps, 5 MP@20fps, 3 MP@18fps,4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), Extended transmission distance over coax cable, 4K UHD output, 380 1U case	1235
MSA-C1500IC12.0-18P-GB,UK,12V1.5A,Φ2.1(1017	AC/DC Adapter for 2MP/5MP 4-ch 8-ch DVR etc., Input:100-240V~50/60Hz 0.7A max. Output:12.0V---1.5A, Different versions recorder require different adapters, please confirm with your sales person if it is applicable	29
KPL-040F-VI	AC Adapter for 1MP 16-ch, 3MP 4-ch DVR etc., Input:100-240V~50/60Hz 1.7A max. Output:+12.0V---3.33A, Different versions recorder require different adapters, please confirm with your sales person if it is applicable	61

KPL-060F-VI	AC Adapter for 2MP/3MP/5MP 16-ch DVR etc., Input:100-240V~50/60Hz 1.7A max. Output:+12.0V---5.00A,Different versions recorder require different adapters, please confirm with your sales person if it is applicable	73
HIKVISION NVR		
DS-7104NI-Q1/4P/M	4-ch NVR with PoE, 40Mbps Bit Rate Input Max (up to 4-ch IP video), H.265/H.265+/H.264/H.264+, 1 SATA interface, 4 independent PoE network interfaces, mini 1U case	326
DS-7604NI-Q1/4P	4-ch NVR with PoE, 40Mbps Bit Rate Input Max (up to 4-ch IP video) ,H.265/H.265+/H.264/H.264+, 1 SATA interface, 4 independent PoE network interfaces, 1U 315 case	428
DS-7604NI-K1/4P	4-ch NVR with PoE, 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	456
DS-7108NI-Q1/8P/M	8-ch NVR with PoE, 60Mbps Bit Rate Input Max (up to 8-ch IP video) H.265/H.265+/H.264/H.264+,1 SATA interface,8 independent PoE network interfaces, mini 1U case	456
DS-7608NI-Q1/8P	8-ch NVR with PoE, 80Mbps Bit Rate Input Max (up to 8-ch IP video), H.265/H.265+/H.264/H.264+, 1 SATA interface,8 independent PoE network interfaces, standalone 1U 315 case	571
DS-7608NI-K1/8P	8-ch NVR with PoE, 80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces, 8 independent PoE network interfaces, standalone 1U case	623
DS-7608NI-K2/8P	8-ch NVR with PoE, 80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces, 8 independent PoE network interfaces, standalone 1U case	782
DS-7608NI-Q2	8-ch NVR without PoE, 80Mbps Bit Rate Input Max (up to 8-ch IP video), H.265/H.265+/H.264/H.264+,2 SATA interfaces, 380 1U case	386
DS-7616NI-Q2/16P	16-ch NVR 2HDD bays with PoE, 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case	867
DS-7616NI-K2/16P	16-ch NVR 2HDD bays with PoE, 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1	1068
DS-7616NI-Q2	16-ch NVR 2HDD bays without PoE, 160Mbps Bit Rate Input Max (up to 16-ch IP video), H.265/H.265+/H.264/H.264+, 2 SATA interfaces, 380 1U case	434
DS-7716NI-Q4/16P	16-ch NVR 4HDD bays with PoE, 160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	1292
DS-7716NI-Q4	16-ch NVR 4HDD bays without PoE, 160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	860
DS-7732NI-K4	32-ch NVR 4HDD bays without PoE, 256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	1137
DS-9632NI-I8	32-ch NVR 8HDD bays without PoE, 320 Mbps Bit Rate Input Max(up to 32-ch IP video), 8 SATA Interfaces, alarm I/O: 16/4	3873
DS-9664NI-I8	64-ch NVR 8HDD bays without PoE, 320 Mbps Bit Rate Input Max(up to 64-ch IP video), 8 SATA Interfaces, alarm I/O: 16/4	5439
Model		
Surveillance HDD		
Surveillance 1TB HDD	1TB/64MB(6Gb/s)/IntelliPower(RPM)/SATA3,(3.5")	176
Surveillance 2TB HDD	2TB/64MB(6Gb/s)/IntelliPower(RPM)/SATA3,(3.5")	242
Surveillance 3TB HDD	3TB/64MB(6Gb/s)/IntelliPower(RPM)/SATA3,(3.5")	364
Surveillance 4TB HDD	4TB/64MB(6Gb/s)/IntelliPower(RPM)/SATA3,(3.5")	396
Surveillance 6TB HDD	6TB/64MB(6Gb/s)/IntelliPower(RPM)/SATA3,(3.5")	661
Surveillance 8TB HDD	8TB/64MB(6Gb/s)/IntelliPower(RPM)/SATA3,(3.5")	926
Surveillance 10TB HDD	10TB/64MB(6Gb/s)/IntelliPower(RPM)/SATA3,(3.5")	1168
Model	Description	
HIKVISION Switch		
DS-3E0106P-E/M	Hikvision 4-ports PoE Switch , L2, Unmanaged, 4 10/100M RJ45 PoE ports, 2 10/100M RJ45 uplink port, 802.3af/at, PoE power budget 35W, max. 300m long distance transmission, 6KV surge protection	136
DS-3E0310P-E/M	Hikvision 8-ports PoE Switch , 2 RJ45 uplink ports,L2, Unmanaged, 8 10/100M RJ45 PoE ports, 2 Gigabit RJ45 uplink ports, 802.3af/at, PoE power budget 60W, max. 300m long distance transmission, 6KV surge protection	223
DS-3E0318P-E/M(B)	Hikvision 16-ports PoE Switch , L2, Unmanaged, 16 10/100M RJ45 PoE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port, 802.3af/at, PoE power budget 130W, "Extend" Mode: ports 9-16 support up to 250meter, 6KV surgy protection	603
DS-3E0326P-E/M(B)	Hikvision 24-ports PoE Switch , L2, Unmanaged, 24 10/100M RJ45 PoE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port, 802.3af/at, PoE power budget 230W, "Extend" Mode: ports 17-24 support up to 250meter, 6KV surgy protection	737
DS-3E0505P-E/M	Hikvision 4-ports Unmanaged Gigabit PoE Switch , L2, Unmanaged, 4 Gigabit POE ports, 1 Gigabit RJ45 uplink port, 802.3af/at, PoE power budget 35w	151
DS-3E0510P-E/M	Hikvision 8-ports Unmanaged Gigabit PoE Switch , L2,Unmanaged, 8 Gigabit POE ports, 1 Gigabit RJ45 uplink port, 1 Gigabit SFP uplink port, 802.3af/at, PoE power budget 58w	279

DS-3E0518P-E/M	Hikvision 16-ports Unmanaged Gigabit PoE Switch , L2, Unmanaged, 16 Gigabit POE ports, 2 Gigabit SFP uplink port, 802.3af/at, PoE power budget 125w	783
DS-3E0526P-E/M	Hikvision 24-ports Unmanaged Gigabit PoE Switch , L2, Unmanaged, 24 Gigabit POE ports, 2 Gigabit SFP uplink port, 802.3af/at, PoE power budget 225w	1065
SFP Module		
HK-SFP-1.25G-20-1310	TX1310nm/1.25G, RX1550nm/1.25G, LC, single mode and single fiber, 20km, 0~70°C, SFP, A pair use with HK-SFP-1.25G-20-1550	99
HK-SFP-1.25G-20-1550	TX1550nm/1.25G, RX1310nm/1.25G, LC, single mode and single fiber, 20km, 0~70°C, SFP, A pair use with HK-SFP-1.25G-20-1550	113
<p>*Prices are subject to change without prior notice. Please Call for stock available For Products Enquiries, kindly contact (PM) Lee- 012-327 5139 lee@apaq.com.my</p>		