



HIKVISION TVI Camera



Time ColorVu camera



Fish-eye Camera



HIKVISION PTZ Camera



HIKVISION IP Camera

APAQ HIKVISION PRODUCT



HIKVISION NVR



HIKVISION DVR





HIKVISION Switch


















SFP Module






HIKVISION Product Price List



Date:1-8-2024




| Model | Descriptions | Srp(rm) | Warranty | |
|--|--|----------|-------------------------------|--|
| HIKVISION TVI Camera | | | | |
| DS-2CE16D0T-EXIF | 2MP Fixed Mini Bullet 4 in 1 Camera <ul style="list-style-type: none"> • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.02 Lux/F1.2, 20m EXIR • DNR,DWDR, P67 • Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included | RM63.00 | 2 Years (one to one exchange) | |
| DS-2CE76D0T-EXIPF | 2MP Indoor Fixed Turret 4 in 1 Camera <ul style="list-style-type: none"> • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.02 Lux/F1.2, 20m EXIR • DNR,DWDR • Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included | RM50.00 | 2 Years (one to one exchange) | |
| DS-2CE19D0T-VFIT3F(C) (2MP Vari-focal) | 2MP Manual Varifocal Bullet 4 in 1 Camera <ul style="list-style-type: none"> • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.7-13.5mm varifocal lens, 0.01 Lux/F1.2, 40m EXIR • DNR,DWDR, P67 • Switchable TVI/AHD/CVI/CVBS video signal output • Front cover: Metal, Main body: Plastic,Bracket: Metal. 12VDC,Power supply no included | RM180.00 | 2 Years (one to one exchange) | |
| DS-2CE5AD0T-VPIT3F(C) (2MP Vari-focal) | 2MP Vandal Manual Varifocal Dome 4 in 1 Camera <ul style="list-style-type: none"> • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.7-13.5mm varifocal lens, 0.01 Lux/F1.2, 40m EXIR • DNR,DWDR, P67, IK10 • Switchable TVI/AHD/CVI/CVBS video signal output • Enclosure:Plastic,Main body:Metal,Mounting base:Plastic. 12VDC,Power supply no included | RM180.00 | 2 Years (one to one exchange) | |
| DS-2CE16D0T-ITFS | 2MP Audio Fixed Mini Bullet Camera <ul style="list-style-type: none"> • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.02 Lux/F1.2, 30m EXIR • DNR,DWDR, P67, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included | RM88.00 | 2 Years (one to one exchange) | |
| DS-2CE76D0T-ITPFS | 2MP Audio Indoor Fixed Turret Camera <ul style="list-style-type: none"> • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.02 Lux/F1.2, 20m EXIR • DNR,DWDR,OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included | RM77.00 | 2 Years (one to one exchange) | |
| DS-2CE16H0T-ITF | 5MP Fixed Mini Bullet 4 in 1 Camera <ul style="list-style-type: none"> • 5MP CMOS Sensor,ICR,up to 20fps(2560x1944) • 2.8/3.6mm lens, 0.01 Lux/F1.2, 20m EXIR • DNR,DWDR,BLC, P67, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included | RM101 | 2 Years (one to one exchange) | |
| DS-2CE76H0T-ITPF | 5MP Indoor Fixed Turret 4 in 1 Camera <ul style="list-style-type: none"> • 5MP CMOS Sensor,ICR,up to 20fps(2560x1944) • 2.8/3.6mm lens, 0.01 Lux/F1.2, 20m EXIR • DNR,DWDR,BLC, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included | RM80 | 2 Years (one to one exchange) | |
| DS-2CE19H0T-AIT3ZF (5MP Vari-focal) | 5MP Motorized Varifocal Bullet 4 in 1 Camera <ul style="list-style-type: none"> • 5MP CMOS Sensor,ICR,up to 20fps(2560x1944) • 2.7-13.5mm motorized varifocal lens, 0.01 Lux/F1.2, 40m EXIR • DNR,DWDR,BLC,HLC, P67, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Metal, Dual Voltage 12VDC/24VAC,Power supply no included | RM276 | 2 Years (one to one exchange) | |
| DS-2CE5AH0T-AVPIT3ZF (5MP Vari-focal) | 5MP Vandal Motorized Varifocal Dome 4 in 1 Camera <ul style="list-style-type: none"> • 5MP CMOS Sensor,ICR,up to 20fps(2560x1944) • 2.7-13.5mm motorized varifocal lens, 0.01 Lux/F1.2, 40m EXIR • DNR,DWDR,BLC,HLC, P67, OSD Menu, IK10 • Switchable TVI/AHD/CVI/CVBS video signal output • Metal,Dual Voltage 12VDC/24VAC,Power supply no included | RM276.00 | 2 Years (one to one exchange) | |
| DS-2CE16K0T-LFS |  3K Smart Hybrid Light Audio Fixed Mini Bullet Camera <ul style="list-style-type: none"> • 3K CMOS Sensor,ICR,up to 20fps(2960x1665) • 2.8/3.6mm lens, 0.01 Lux/F1.6, 30m EXIR,20m White Light • DNR,DWDR,BLC,HLC, P67, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included | RM114.00 | 2 Years (one to one exchange) | |
| DS-2CE76K0T-LPFS |  3K Smart Hybrid Light Audio Indoor Fixed Turret Camera <ul style="list-style-type: none"> • 3K CMOS Sensor,ICR,up to 20fps(2960x1665) • 2.8/3.6mm lens, 0.01 Lux/F1.6, 20m EXIR,20m White Light • DNR,DWDR,BLC,HLC, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included | RM96.00 | 2 Years (one to one exchange) | |
| DS-2CE16U0T-ITF | 8MP(4K) Fixed Mini Bullet 4 in 1 Camera <ul style="list-style-type: none"> • 8.3MP CMOS Sensor,ICR,up to 12.5fps(3840x2160) • 2.8/3.6mm lens, 0.01 Lux/F1.2, 30m EXIR • DNR,DWDR,BLC,HLC, P67, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included | RM165.00 | 2 Years (one to one exchange) | |

| DS-2CE76U0T-ITPF | 8MP(4K) Indoor Fixed Turret 4 in 1 Camera <ul style="list-style-type: none"> • 8.3MP CMOS Sensor,ICR,up to 12.5fps(3840x2160) • 2.8/3.6mm lens, 0.01 Lux/F1.2, 30m EXIR • DNR,DWDR,BLC,HCL, P67, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included | RM143.00 | 2 Years (one to one exchange) | |
|---|--|----------|-------------------------------|--|
| VIS-AS-12V2A UK ACPower Adpater | 12V 2A UK Power Adpater ,1000mA 12W 5.5x2.1mm Power AC Adapter for CCTV Camera,2MP 4-ch&8ch DVR, Routers, Door access, etc. | RM9.00 | 6 Months | |
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION 24 Hours Full Time ColorVu camera | | | | |
|  DS-2CE10DF3T-FS | 2MP ColorVu Audio Fixed Mini Bullet Camera <ul style="list-style-type: none"> • 2MP 24/7 color imaging Sensor,up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.0005Lux @F1.0, 20m white light distance • DNR,BLC,HLC,130 dB true WDR, P67, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included | RM139.00 | 2 Years (one to one exchange) | |
|  DS-2CE70DF3T-PFS | 2MP ColorVu Indoor Audio Fixed Turret Camera <ul style="list-style-type: none"> • 2MP 24/7 color imaging Sensor,up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.0005Lux @F1.0, 20m white light distance • DNR,BLC,HLC,130 dB true WDR, P67, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included | RM126.00 | 2 Years (one to one exchange) | |
|  DS-2CE10KF0T-FS | 5MP(3K) ColorVu Audio Fixed Mini Bullet Camera <ul style="list-style-type: none"> • 5MP 24/7 color imaging Sensor,up to 20fps(2960x1665) • 2.8/3.6mm lens, 0.001Lux @F1.0, 20m white light distance • DNR,BLC,HLC,DWDR, P67, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included | RM150.00 | 2 Years (one to one exchange) | |
|  DS-2CE70KF0T-PFS | 5MP(3K) ColorVu Indoor Audio Fixed Turret Camera <ul style="list-style-type: none"> • 5MP 24/7 color imaging Sensor,up to 20fps(2960x1665) • 2.8/3.6mm lens, 0.001Lux @F1.0, 20m white light distance • DNR,BLC,HLC,DWDR,OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI),Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included | RM139.00 | 2 Years (one to one exchange) | |
| HIKVISION Web Camera | | | | |
| DS-U02 | 2MP Web Camera <ul style="list-style-type: none"> • 2MP CMOS Sensor,up to 25fps/30fps(1920x1080) • 3.6mm lens, 0.1Lux/F1.2 • Built-in mic, USB 2.0 Type-A interface cable 1.5m • Operating System:Windows 7 above,Android 8.1 above,Linux 4.14above,macOS 10.12 above • Plastic, DC 5V ± 5% (USB),Plug-and-play | RM82.00 | 2 Years (one to one exchange) | |
| DS-UL2 | 2MP Live Web Camera <ul style="list-style-type: none"> • 2MP CMOS Sensor,up to 50fps/60fps(1920x1080) • 3.6mm lens, 0.1Lux/F1.2 • Built-in mic, Auto Focus, Built-in supplement light for bright imaging,USB 2.0 Type-C interface cable 2m,Magnetic bracket • Operating System:Windows 7 above,Android 8.1 above,Linux 4.14above,macOS 10.12 above • Plastic, DC 5V ± 5% (USB),Plug-and-play | RM344.00 | 2 Years | |
| DS-UVC-X12 | 2MP Portable Conference Camera <ul style="list-style-type: none"> • 2MP CMOS Sensor,up to 25fps/30fps(1920x1080) • 2.8mm lens, 0.1Lux/F2.2,120dB true WDR • Built-in 4-mic array microphones,Built-in a full-range, high definition speakers,USB 3.0 Type-C interface cable 2m, • Operating System:Windows 7 above,Android 8.1 above,Linux 4.14above,macOS 10.12 above • Metal&Plastic&fabric, Built-in 2450 mAh lithium battery,DC 5V ± 5% (USB),Plug-and-play | RM717.00 | 2 Years | |
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION IP Camera | | | | |
| DS-2CD1123G0E-I(L) | 2MP Fixed Vandal Dome Network Camera <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@20fps,H.265 • 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m IR range • 3D DNR, BLC,DWDR, IP67, IK10 • Alarm Trigger Motion detection, Privacy mask • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included | RM144.00 | 2 Years (one to one exchange) | |
| DS-2CD1323G0E-I(L) | 2MP Fixed Network Turret Camera <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@20fps,H.265 • 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m IR range • 3D DNR, BLC,DWDR, IP67, IK10 • Alarm Trigger Motion detection, Privacy mask • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included | RM139.00 | 2 Years (one to one exchange) | |
| DS-2CD1023G0E-I(L) | 2MP Fixed Bullet Network Camera <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@20fps,H.265 • 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m IR range • 3D DNR,BLC, DWDR, IP67 • Alarm Trigger Motion detection, Privacy mask • Front Cover: Metal,Back Cover&Bracket: Plastic,PoE/12VDC,power supply no included | RM139.00 | 2 Years (one to one exchange) | |

| | | | | |
|--|---|----------|-------------------------------|--|
| DS-2CD1323G2-LIU |  <p>2MP Smart Hybrid Light Fixed Turret Network Audio Camera</p> <ul style="list-style-type: none"> • 1/2.9" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6,up to 30m white light • 3D DNR, BLC,HLC,DWDR, IP67 • Built-in Microphone, Motion 2.0 human and vehicle classification • Cover&Base:Plastic,Eyeball;Metal,PoE/12VDC,power supply no included | RM166.00 | 2 Years (one to one exchange) | |
| DS-2CD1023G2-LIU |  <p>2MP Smart Hybrid Light Fixed Bullet Network Audio Camera</p> <ul style="list-style-type: none"> • 1/2.9" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6,up to 30m white light • 3D DNR, BLC,HLC,DWDR, IP67 • Built-in Microphone, Motion 2.0 human and vehicle classification • Front Cover:Metal,Back Cover&Bracket:Plastic,PoE/12VDC,power supply no included | RM166.00 | 2 Years (one to one exchange) | |
| DS-2CD1143G0-I | <p>4MP Fixed Dome Network Camera</p> <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ • 2.8/4mm lens, 0.01 Lux @F2.0, EXIR, up to 30m IR range • 3D DNR,BLC, IP67, IK10,120 dB true WDR • Alarm Trigger Motion detection, Privacy mask • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included | RM228.00 | 2 Years (one to one exchange) | |
| DS-2CD1043G0-I | <p>4MP Fixed Bullet Network Camera</p> <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ • 2.8/4mm lens, 0.01 Lux @F2.0, EXIR, up to 30m IR range • 3D DNR,BLC, IP67,120 dB true WDR • Alarm Trigger Motion detection, Privacy mask • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included | RM228.00 | 2 Years (one to one exchange) | |
| DS-2CD1143G2-LIU |  <p>4MP Smart Hybrid Light Fixed Dome Network AudioCamera</p> <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6,up to 30m white light • 3D DNR, BLC,HLC, 120dB ture WDR, IP67,IK08 • Built-in Microphone, Motion 2.0 human and vehicle classification • Base: Metal,Cover: Plastic,PoE/12VDC,power supply no included | RM254.00 | 2 Years (one to one exchange) | |
| DS-2CD1343G2-LIU |  <p>4MP Smart Hybrid Light Fixed Turret Network Audio Camera</p> <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6,up to 30m white light • 3D DNR, BLC,HLC, 120dB ture WDR, IP67 • Built-in Microphone, Motion 2.0 human and vehicle classification • Cover&Base:Plastic,Eyeball;Metal,PoE/12VDC,power supply no included | RM242.00 | 2 Years (one to one exchange) | |
| DS-2CD1043G2-LIU |  <p>4MP Smart Hybrid Light Fixed Bullet Network Audio Camera</p> <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6,up to 30m white light • 3D DNR, BLC,HLC, 120dB ture WDR, IP67 • Built-in Microphone, Motion 2.0 human and vehicle classification • Front Cover: Metal Back Cover & Bracket: Plastic,PoE/12VDC,power supply no included | RM242.00 | 2 Years (one to one exchange) | |
| DS-2CD1163G2-LIU |  <p>6MP Smart Hybrid Light Fixed Dome Network Camera</p> <ul style="list-style-type: none"> • 1/2.4" Progressive Scan CMOS,ICR,Up to 3200 × 1800@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6, up to 30m White Light • 3D DNR,BLC,HLC, IP67, IK08,120 dB true WDR,Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included | RM294.00 | 2 Years (one to one exchange) | |
| DS-2CD1063G2-LIU |  <p>6MP Smart Hybrid Light Fixed Bullet Network Camera</p> <ul style="list-style-type: none"> • 1/2.4" Progressive Scan CMOS,ICR,Up to 3200 × 1800@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6, up to 20m White Light • 3D DNR,BLC,HLC, IP67, 120 dB true WDR,Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included | RM279.00 | 2 Years (one to one exchange) | |
| DS-2CD1183G2-LIU |  <p>8MP Smart Hybrid Light Fixed Dome Network Camera</p> <ul style="list-style-type: none"> • 1/2.7" Progressive Scan CMOS,ICR,Up to 3840 × 2160@20fps,H.265+ • 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m White Light • 3D DNR,BLC, IP67, IK08,120 dB true WDR,Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included | RM336.00 | 2 Years (one to one exchange) | |
| DS-2CD1083G2-LIU |  <p>8 MP Smart Hybrid Light Fixed Bullet Network Camera</p> <ul style="list-style-type: none"> • 1/2.7" Progressive Scan CMOS,ICR,Up to 3840 × 2160@20fps,H.265+ • 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m White Light • 3D DNR,BLC, IP67, 120 dB true WDR,Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included | RM321.00 | 2 Years (one to one exchange) | |
| Varifocal Lens Camera | | | | |
| DS-2CD1723G0-IZ (Motorized Varifocal) |  <p>2MP Motorized Varifocal Dome Network Camera</p> <ul style="list-style-type: none"> • 1/2.7" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 2.8-12mm motorized lens, 0.005 Lux @F1.6,EXIR,up to 30m IR range • 3D DNR,BLC,DWDR, IP67, IK10 • Alarm Trigger Motion detection, Privacy mask • Metal,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included | RM394.00 | 2 Years (one to one exchange) | |
| DS-2CD1A23G0-IZU (Motorized Varifocal) |  <p>2MP Motorized Varifocal PT Bullet Network Camera</p> <ul style="list-style-type: none"> • 1/2.7" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 2.8-12mm motorized lens, 0.007 Lux @F1.6,EXIR,up to 50m IR range • 3D DNR, BLC,HLC, IP66,120dB WDR • Alarm Trigger Motion detection,Built-in Microphone,Pan, tilt and zoom ability that enables the camera to capture larger and interested areas • Front cover:metal, body:metal, bracket:metal,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included | RM351.00 | 2 Years (one to one exchange) | |

| | | | | |
|---|--|----------------|-------------------------------|--|
| DS-2CD1743G0-IZ (Motorized Varifocal) | 4MP Motorized Varifocal Dome Network Came <ul style="list-style-type: none"> • 1/2.7" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ • 2.8-12mm motorized lens, 0.005 Lux @F1.6,EXIR,up to 30m IR range • 3D DNR,BLC, IP67, IK10,120dB WDR • Alarm Trigger Motion detection, Privacy mask • Metal,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included | RM438.00 | 2 Years (one to one exchange) | |
| DS-2CD1A43G0-IZU (Motorized Varifocal) | 4MP Motorized Varifocal PT Bullet Network Camera <ul style="list-style-type: none"> • 1/2.7" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ • 2.8-12mm motorized lens, 0.007 Lux @F1.6,EXIR,up to 50m IR range • 3D DNR, BLC,HLC, IP66,120dB WDR • Alarm Trigger Motion detection,Built-in Microphone,Pan, tilt and zoom ability that enables the camera to capture larger and interested areas • Front cover:metal, body:metal, bracket:metal,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included | RM379.00 | 2 Years (one to one exchange) | |
| DS-2CD2743G2-IZS (Motorized Varifocal) | 4MP AcuSense Motorized Vari-focal Dome Network Camera <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,ICR,Up to 2688x1520@30fps,H.265+ • 2.8-12mm motorized VF lens, 0.005 Lux @F1.6,EXIR, up to 40m IR range • 3 streams,3D DNR,BLC/HLC, 120dB WDR, IP67, IK10 • VCA functions: Line crossing detection, Intrusion detection, Face detection Human/vehicle classification alarm • All-metal, Audio/Alarm I/O, MicroSD Slot(up to 256GB); PoE/12VDC,power supply no included | RM671.00 | 2 Years | |
| DS-2CD2643G2-IZS (Motorized Varifocal) | 4MP AcuSense Motorized Vari-focal Bullet Network Camera <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,ICR,Up to 2688x1520@30fps,H.265+ • 2.8-12mm motorized VF lens, 0.005 Lux @F1.6,EXIR, up to 40m IR range • 3 streams,3D DNR, BLC/HLC, 120dB WDR, IP67, IK10 • VCA functions: Line crossing detection, Intrusion detection, Face detection Human/vehicle classification alarm • All-metal, Audio/Alarm I/O, MicroSD Slot(up to 256GB); PoE/12VDC,power supply no included | RM671.00 | 2 Years | |
| DS-2CD1663G2-LIZU (Motorized Varifocal) | 6MP Smart Dual Light Varifocal Bullet Network Camera <ul style="list-style-type: none"> • 1/2.4" Progressive Scan CMOS,ICR,Up to 3200 × 1800@20fps,H.265+ • 2.8-12mm motorized VF lens, 0.005 Lux @F1.6, up to 50m White Light • 3D DNR,BLC,HLC, IP67,120 dB true WDR,Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover: Plastic, MicroSD Slot(up to 512GB);PoE/12VDC,power supply no included | RM498.00 | 2 Years (one to one exchange) | |
|  DS-2CD1763G2-LIZU (Motorized Varifocal) | 6MP Smart Dual Light Varifocal Dome Network Camera <ul style="list-style-type: none"> • 1/2.4" Progressive Scan CMOS,ICR,Up to 3200 × 1800@20fps,H.265+ • 2.8-12mm motorized VF lens, 0.005 Lux @F1.6, up to 30m White Light • 3D DNR,BLC,HLC, IP67,IK08,120 dB true WDR,Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal, MicroSD Slot(up to 512GB);PoE/12VDC,power supply no included | RM498.00 | 2 Years (one to one exchange) | |
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION IP Camera | | | | |
|  DS-2CD2143G2-I | 4MP AcuSense Fixed Dome Network Camera <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,ICR,Up to 2688x1520@25fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6, EXIR, up to 30m IR range • 3 streams,3D DNR,BLC,HCL, IP67, IK10,120dB true WDR • Human and vehicle targets classification,Line crossing detection,intrusion detection,Face detection • Metal,MicroSD Slot(up to 512GB),PoE/12VDC,power supply no included | RM370.00 | 2 Years | |
|  DS-2CD2043G2-I | 4MP AcuSense Fixed Bullet Network Camera <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,ICR,Up to 2688x1520@25fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6, EXIR, up to 40m IR range • 3 streams,3D DNR,BLC,HCL, IP67, 120dB true WDR • Human and vehicle targets classification,Line crossing detection,intrusion detection,Face detection • Metal,MicroSD Slot(up to 512GB),PoE/12VDC,power supply no included | RM370.00 | 2 Years | |
|  DS-2CD2183G2-I | 8MP(4K) AcuSense Fixed Dome Network Camera <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 3840x2160@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6, EXIR, up to 30m IR range • 3 streams,3D DNR,BLC,HCL, IP67, IK10,120dB true WDR • Human and vehicle targets classification,Line crossing detection,intrusion detection,Face detection • Metal,MicroSD Slot(up to 512GB),PoE/12VDC,power supply no included | RM474.00 | 2 Years | |
|  DS-2CD2083G2-I | 8MP(4K) AcuSense Fixed Bullet Network Camera <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 3840x2160@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6, EXIR, up to 40m IR range • 3 streams,3D DNR,BLC,HCL, IP67, 120dB true WDR • Human and vehicle targets classification,Line crossing detection,intrusion detection,Face detection • Metal,MicroSD Slot(up to 512GB),PoE/12VDC,power supply no included | RM474.00 | 2 Years | |
|  DS-2CD2783G2-IZS | 8MP(4K) AcuSense Motorized Vari-focal Dome Network Camera <ul style="list-style-type: none"> • 1/1.8" Progressive Scan CMOS,20fps(3840×2160),ICR,25fps/30fps (3200x1800),H.265+ • 2.8-12mm motorized VF lens,0.005 Lux @F1.6, EXIR, up to 40m IR range • 3 streams,3D DNR,BLC/HLC, 120dB WDR, IP67, IK10 • VCA functions: Line crossing detection, Intrusion detection, Face detection,Human/vehicle classification alarm • All-metal, Audio/Alarm I/O, MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included | RM859.00 | 2 Years | |

| | | | | |
|---|---|----------------|-------------------------------|--|
|  | 8MP(4K) AcuSense Motorized Vari-focal Bullet Network Camera <ul style="list-style-type: none"> • 1/1.8" Progressive Scan CMOS,20fps(3840x2160),ICR,25fps/30fps (3200x1800),H.265+ • 2.8-12mm motorized VF lens,0.005 Lux @F1.6, EXIR, up to 40m IR range • 3 streams,3D DNR,BLC/HLC,120dB WDR, IP67, IK10 • VCA functions: Line crossing detection, Intrusion detection, Face detection,Human/vehicle classification alarm • All-metal, Audio/Alarm I/O, MicroSD Slot(up to 256GB),PoE/12VDC, power supply no included | RM859.00 | 2 Years | |
| DS-2CD2683G2-IZS | | | | |
|  | 4MP Super Wide Angle Fixed Turret Network Camera <ul style="list-style-type: none"> • 1/2.7" Progressive Scan CMOS,ICR,Up to 2688x1520@25fps,H.265+ • 1.68mm lens, 0.028 Lux @F2.0, EXIR, up to 10m IR range • 3 streams,3D DNR,BLC,HCL,120dB true WDR • 180°super wide field of view, Line Crossing, Intrusion, Unattended Baggage, Object Removal,Face Detection,Scene Change Detection • Metal, MicroSD Slot(up to 256GB),PoE/12VDC, power supply no included | RM496.00 | 2 Years | |
| DS-2CD2345G0P-I (Super Wide Angle) | | | | |
|  | 4MP Super Wide Angle Fixed Bullet Network Camera <ul style="list-style-type: none"> • 1/2.7" Progressive Scan CMOS,ICR,Up to 2688x1520@25fps,H.265+ • 1.68mm lens, 0.028 Lux @F2.0, EXIR, up to 20m IR range • 3 streams,3D DNR,BLC,HCL,120dB true WDR, IP67 • 180°super wide field of view, Line Crossing, Intrusion, Unattended Baggage, Object Removal,Face Detection,Scene Change Detection • Metal, MicroSD Slot(up to 256GB),PoE/12VDC, power supply no included | RM567.00 | 2 Years | |
| DS-2CD2T45G0P-I (Super Wide Angle) | | | | |
|  | 2MP Covert Network Camera <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,1920 × 1080@60fps,H.265 • 2.8/4mm fixed lens, 0.002 Lux @F1.2, EXIR, up to 20m IR range • 3D DNR,BLC,HCL,defog,120dB true WDR,Dimension 31.5 mm × 31.5 mm × 49.6 mm (1.2" × 1.2" × 2") • Intrusion, line crossing detection, region entrance, region exiting detection, unattended baggage detection, object removal detection,Audio exception detection, defocus detection, scene change detection • Audio input,12VDC,Ø 5.5 mm coaxial power plug, power supply no included | RM378.00 | 2 Years | |
| DS-2CD2D25G1/M-D/NF (Pinhole Camera) | | | | |
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION IP Camera | | | | |
|  | 2MP Indoor Audio Fixed PT Network WiFi Camera <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.264 • 2.8/4mm lens, 0.01 Lux @F1.2,EXIR, up to 10m IR range • 3D DNR, BLC,DWDR • Built-in 2way Audio,2.4GHz WiFi, Alarm Trigger Motion detection,Privacy mask • Plastic, MicroSD Slot(up to 128GB),DC 5V,micro USB interface, power cable included | RM184.00 | 2 Years (one to one exchange) | |
| DS-2CV2Q21FD-IW | | | | |
|  | 2MP Outdoor Fixed Bullet Network WiFi Camera <ul style="list-style-type: none"> • 1/2.7" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 2.8/4mm lens, 0.028 Lux @F2.0, up to 30m IR range • 3D DNR, BLC,HLC • Built-in Microphone,2.4GHz WiFi, Alarm Trigger Motion detection • Front Cover: Metal,Back Cover Plastic, MicroSD Slot(up to 128GB),12VDC, power supply no included | RM189.00 | 2 Years (one to one exchange) | |
| DS-2CV1021G0-IDW1 | | | | |
|  | 2MP ColorVu Fixed Bullet Network Camera <ul style="list-style-type: none"> • 2MP 24/7 color imaging Sensor 1/2.8",Up to 1920x1080@25fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,BLC,HLC,DWDR, P67 • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Metal,PoE/12VDC, power supply no included | RM168.00 | 2 Years (one to one exchange) | |
| DS-2CD1027G2-L | | | | |
|  | 2MP ColorVu Fixed Dome Network Camera <ul style="list-style-type: none"> • 2MP 24/7 color imaging Sensor 1/2.8",Up to 1920x1080@25fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,BLC,HLC,DWDR,IK08, P67 • Alarm Trigger Motion detection, Privacy mask • Base: Metal,Cover:Plastic,PoE/12VDC, power supply no included | RM187.00 | 2 Years (one to one exchange) | |
| DS-2CD1127G0-L | | | | |
|  | 4MP ColorVu Fixed Bullet Network Camera <ul style="list-style-type: none"> • 24/7 color imaging Sensor 1/3",Up to 2560x1440@20fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,HLC,BLC, P67,120dB True WDR • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Metal,PoE/12VDC, power supply no included | RM276.00 | 2 Years (one to one exchange) | |
| DS-2CD1047G2-L | | | | |
|  | 4MP ColorVu Fixed Dome Network Camera <ul style="list-style-type: none"> • 24/7 color imaging Sensor 1/3",Up to 2560x1440@20fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,BLC,IK08, P67,120dB True WDR • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover:Plastic,PoE/12VDC, power supply no included | RM282.00 | 2 Years (one to one exchange) | |
| DS-2CD1147G2-L | | | | |
|  | 4MP ColorVu MD 2.0 Fixed Bullet Network Camera <ul style="list-style-type: none"> • 24/7 color imaging Sensor 1/3",Up to 2560x1440@20fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,BLC,IK08, P67,120dB True WDR, Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover:Plastic,PoE/12VDC, power supply no included | RM303.00 | 2 Years (one to one exchange) | |
| DS-2CD1047G2-LUF | | | | |
|  | 4MP ColorVu Fixed Dome Network Audio Camera <ul style="list-style-type: none"> • 24/7 color imaging Sensor 1/3",Up to 2560x1440@20fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,BLC,IK08, P67,120dB True WDR, Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover:Plastic,PoE/12VDC, power supply no included | RM317.00 | 2 Years (one to one exchange) | |
| DS-2CD1147G2-LUF | | | | |
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION PTZ Camera | | | | |

| | | | | |
|--|--|----------------|-----------------|--|
|  DS-2CE70DF3T-PTS | 2" 2MP ColorVu Audio Indoor Analog TVI PT Camera <ul style="list-style-type: none"> • 24/7 Color Imaging,TVI: 1080P@25 fps/30 fps • 2.8/3.6mm lens, 0.0005 Lux/F1.0, up to 20m IR range • 3D DNR,BLC,HLC,130dB True WDR • Built-in Microphone,Alarm Trigger Motion detection, Pan: 0° to 350°,Tilt:0° to 75° • 12VDC,power supply no included | RM156.00 | | |
| DS-2AE4225TI-D | 4" 2MP 25X Powered by DarkFighter IR Analog PTZ <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps • 4.8-120mm lens, 0.005 Lux/F1.6, up to 100m IR range • 3D DNR,BLC,HLC,120dB True WDR, IP66 • 25× optical, 16 × digital Zoom, Preset/Patrol/Pattern/Pan Scan/Tilt Scan/Panorama Scan, privacy masks, Switchable TVI/AHD/CVI/CVBS video signal output • Come with wall mount bracket, 12VDC,Power supply included | RM1,012.00 | | |
| DS-2DE2C400MW-DE(F1) | 2" 4MP IR Mini PT Dome Network Camera <ul style="list-style-type: none"> • 1/3" Progressive Scan CMOS,Up to 2560x1440@25fps,H.265 • 2.8/4mm lens, 0.005 Lux/F1.2, up to 30m IR range • 3D DNR,BLC,HLC,DWDR,IP66 • Built-in 2way Audio,Alarm Trigger Motion detection, Pan: 0° to 340°,Tilt:-5° to 105° • MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included | RM306.00 | | |
| DS-2DE2A404IW- DE3(C0)(S6) | 2" 4MP 4x Zoom DarkFighter IR Mini PT Dome Network Camera(PTZ) <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 2560x1440@25fps,H.265+ • 2.8-12mm lens, 0.005 Lux/F1.5, up to 20m IR range • 3D DNR,BLC,HLC,120dB True WDR, IP66,IK10 • 4× optical, 16 × digital Zoom,built-in microphone,line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception,Face detection • Audio I/O, MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included | RM557.00 | | |
|   DS-2DE3A400BW- DE(F1)(T5) | 3" 4MP ColorVu Network PT Network Camera <ul style="list-style-type: none"> • 1/1.8" Progressive Scan CMOS,Up to 2560x1440@30fps,H.265+ • 4mm lens, 0.0005 Lux/F1.0, up to 30m white light distance • 3D DNR,BLC,HLC,120dB True WDR, IP66 • Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception,Human/vehicle classification alarm,Face capture • Built-in 2way Audio, MicroSD Slot(up to 256GB),PoE/12VDC,power supply included | RM633.00 | | |
|  DS-2DE4225IW-DE(T5) | 4" 2MP 25X Powered by DarkFighter IR Network Speed Dome(PTZ) <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 4.8-120mm lens, 0.005 Lux/F1.6,up to 100m IR range • 3D DNR,BLC,HLC,120dB True WDR, IP66 • 25× optical, 16× digital Zoom,Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception,Human/vehicle classification alarm,Face capture • Come with wall mount bracket,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply included | RM1,271.00 | | |
|  DS-2DE4425IW-DE(T5) | 4" 4MP 25X Powered by DarkFighter IR Network Speed Dome(PTZ) <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 2560x1440@25fps,H.265+ • 4.8-120mm lens, 0.005 Lux/F1.6,up to 100m IR range • 3D DNR,BLC,HLC,120dB True WDR, IP66 • 25× optical, 16× digital Zoom,Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception,Human/vehicle classification alarm,Face capture • Come with wall mount bracket,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply included | RM1,398.00 | | |
|  DS-2DE5432IWG-E | 5" 4MP 32X Powered by DarkFighter IR Network Speed Dome(PTZ) <ul style="list-style-type: none"> • 1/2.8" Progressive Scan CMOS,ICR,Up to 2560x1440@25fps,H.265+ • 4.8-153mm lens, 0.005 Lux/F1.6,up to 150m IR range • 3D DNR,BLC,HLC,120dB True WDR, IP66 • 32× optical, 16× digital Zoom,Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception,Human/vehicle classification alarm,Face detection,Smart Tracking • Come with wall mount bracket,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),Hi-PoE+/24VAC,power supply included | RM2,179.00 | | |
|   DS-2SE4C225MWG- E(12F0) | 4" TandemVu 2MP 25X Colorful & IR Network Speed Dome <ul style="list-style-type: none"> • Captures a large area and great details at the same time • 1Ch bullet camera: 1/2.8" Progressive Scan CMOS, Up to 1920x1080@30fps,0.0005 Lux @F1.0, 2.8mm lens,30m white light • 1Ch PTZ camera: 1/2.8" progressive scan CMOS, Up to 1920x1080@30fps,.005 Lux @F1.6, 4.8 to 120 mm, 25x Optical & 16x Digital Zoom, 100m IR • 3D DNR,BLC,HLC,120dB True WDR, IP66 • Line crossing, intrusion,Region Entrance/Exiting,audio exception detection,Human/vehicle classification alarm,Face capture • Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply included | RM1,399.00 | | |
| DS-1005KI | USB Keyboard <ul style="list-style-type: none"> • Supports various cameras, NVRs, DVRs and also iVMS 4200 • Flexible 4-axis joystick • Support USB HID protocol • 5V DC,Power supply and communication by USB port directly | RM621.00 | | |
| DS-1602ZJ | Wall Mount Bracket <ul style="list-style-type: none"> • Aluminum alloy material with surface spray treatment • General design for indoor/outdoor • Suitable for speed dome pendent mounting | RM72.00 | | |
| DS-1663ZJ | Ceiling Mount Bracket <ul style="list-style-type: none"> • Aluminum alloy material with surface spray treatment • General design for indoor/outdoor • Suitable for speed dome ceiling mount | RM39.00 | | |
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION Fish-eye Camera | | | | |

| | | | | |
|------------------------------------|---|-------------|----------|--|
| DS-2CD2955G0-ISU | <p>5MP Fisheye Fixed Dome Network Camera</p> <ul style="list-style-type: none"> • 1/2.5" Progressive Scan CMOS,ICR,Up to 2560x1920@25fps,H.265+ • 1.05mm lens, 0.01 Lux/F1.2, up to 8m IR range • 3D DNR,120dB True WDR • Support 14 display modes, Line crossing, intrusion,unattended baggage,object removal detection,face detection, scene change detection • Built-in Microphone,Alarm I/O, MicroSD Slot(up to 128GB),PoE/12VDC,power supply no included | RM704.00 | 2 Years | |
| DS-2CD6365G1-IVS | <p>6MP Fisheye Network Camera</p> <ul style="list-style-type: none"> • 1/1.8" Progressive Scan CMOS,ICR,Up to 2560x2560@25fps,H.265+ • 1.16mm lens, 0.01 Lux/F2.25, up to 15m IR range • 3D DNR,BCL,HCL,DWDR,IP67,IK10 • Support 20 display modes, Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception detection. AI function: People Counting,Queue Management,Heat Map,Intersection Analysis • Built-in 2way Audio,Alarm I/O, MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included | RM2,133.00 | 2 Years | |
| DS-2PT3326IZ-DE3(2.8-12mm)(2mm) | <p>Mini PanoVu Network Camera</p> <ul style="list-style-type: none"> • 3Ch Panoramic camera: 1/2.8" CMOS sensor, 2mm lens, 1920x1080p@30ps,10m IR • 1Ch PTZ camera: 1/2.8" CMOS sensor, 2.8-12mm lens,1920x1080p@30ps, 4x optical zoom, 8x digital zoom • 3D DNR,BCL,HCL,DWDR • Support PTZ linkage, Line crossing, intrusion,audio exception detection • Audio I/O,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included | RM 1,331.00 | 2 Years | |
| HIKVISION Thermal IP Camera | | | | |
| DS-2TD2617-3/QA | <p>Thermal & Optical Bi-spectrum Network Bullet Camera</p> <ul style="list-style-type: none"> • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 3.1mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD<40mk,Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 4mm fixed lens,40m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • IP67,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included | RM1,308.00 | 2 Years | |
| DS-2TD2617-6/QA | <p>Thermal & Optical Bi-spectrum Network Bullet Camera</p> <ul style="list-style-type: none"> • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 6.2mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD<40mk,Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 8mm fixed lens,40m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • IP67,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included | RM1,403.00 | 2 Years | |
| DS-2TD2617-10/QA | <p>Thermal & Optical Bi-spectrum Network Bullet Camera</p> <ul style="list-style-type: none"> • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 9.7mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD<40mk,Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 8mm fixed lens,40m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • IP67,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included | RM 1,410.00 | 2 Years | |
| DS-2TD1217-2/QA | <p>Thermal & Optical Bi-spectrum Network Turret Camera</p> <ul style="list-style-type: none"> • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 1.8mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD<40mk,Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 2.1mm fixed lens,15m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • IP66,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included | RM1,308.00 | 2 Years | |
| DS-2TD1217-3/QA | <p>Thermal & Optical Bi-spectrum Network Turret Camera</p> <ul style="list-style-type: none"> • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 3.1mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD<40mk,Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 4mm fixed lens,15m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • IP66,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included | RM1,308.00 | 2 Years | |
| DS-2TD1217-6/QA | <p>Thermal & Optical Bi-spectrum Network Turret Camera</p> <ul style="list-style-type: none"> • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 6.2mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD<40mk,Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 8mm fixed lens,15m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • IP66,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included | RM1,402.00 | 2 Years | |
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION DVR | | | | |

| | | | | |
|-----------------------|--|------------|---------|--|
| DS-7204HQHI-K1/E | <p>4-ch 1080p 1U DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 4-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 1-ch IP video input (up to 5-ch) • Support 4-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, CH01-04:1080P/4MP Lite@15fps/ch • 1 SATA interface, up to 10TB, 1RJ45, 2 USB Ports, 12VDC 1.5A, power supply included | RM240.00 | 2 Years | |
| DS-7208HQHI-K1/E | <p>8-ch 1080p 1U DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 8-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 2-ch IP video input (up to 10-ch) • Support 4-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, CH01-08:1080P/4MP Lite@15fps/ch • 1 SATA interface, up to 10TB, 1RJ45, 2 USB Ports, 12VDC 1.5A, power supply included | RM380.00 | 2 Years | |
| iDS-7216HQHI-M2/S | <p>16-ch 1080p 1U AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 16-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 2-ch IP video input (up to 18-ch) • 1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, CH01-16:1080P/4MP Lite@15fps/ch, 1ch 4K UHD output, CVBS output • 2 SATA interface, up to 10TB/each, 1RJ45, 2 USB Ports, 12VDC, power supply included | RM689.00 | 2 Years | |
| iDS-7232HQHI- M2/S(E) | <p>32-ch 1080p 1U AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 32-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 2-ch IP video input (up to 34-ch) • 1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, CH01-16:1080P/4MP Lite@15fps/ch, 1ch 4K UHD output, CVBS output • 2 SATA interface, up to 10TB/each, 1RJ45, 2 USB Ports, 12VDC, power supply included | RM1,399.00 | 2 Years | |
| iDS-7204HUHI-M1/E | <p>4-ch 5MP 1U AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 4-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 4-ch IP video input (up to 6-ch) • 1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, 5MP@12fps, 8MP@8fps, 1ch 4K UHD output, CVBS output • 1 SATA interface, up to 10TB, 1RJ45, 2 USB Ports, 12VDC, power supply included | RM348.00 | 2 Years | |
| iDS-7208HUHI-M1/E | <p>8-ch 5MP 1U AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 8-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 4-ch IP video input (up to 12-ch) • 1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, 5MP@12fps, 8MP@8fps, 1ch 4K UHD output, CVBS output • 1 SATA interface, up to 10TB, 1RJ45, 2 USB Ports, 12VDC, power supply included | RM580.00 | 2 Years | |
| iDS-7216HUHI-M2/S | <p>16-ch 5MP 1U AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 16-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 8-ch IP video input (up to 24-ch) • 1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, 5MP@12fps, 8MP@8fps, 1ch 4K UHD output, CVBS output • 2 SATA interface, up to 10TB/each, 1RJ45, 2 USB Ports, 12VDC, power supply included | RM1,217.00 | 2 Years | |
| iDS-7332HUHI-M4/S | <p>32-ch 5MP 1U AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 32-ch HDTV coaxial video & audio input, 4-ch RCA audio input, 32-ch IP video input (up to 64-ch) • Support POS triggered recording & POS information overlay, RAID 0, 1, 5, 6, 10 effectively avoids data loss risks • H.265 Pro+ video compression, 5MP@12fps, 8MP@8fps, 1ch 4K UHD output, CVBS output • 4 SATA interface, up to 12TB/each, 1 eSATA, 2 RJ45, 3 USB Ports, Built in power switch | RM3,586.00 | 2 Years | |
| iDS-7204HTHI- M1/S(C) | <p>4-ch 8MP(4K) 1U AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 4-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 4-ch IP video input (up to 8-ch) • 1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, 8MP@15fps, 1ch 4K UHD output, CVBS output • 1 SATA interface, up to 10TB, 1RJ45, 2 USB Ports, Support Wi-Fi dongle, 12VDC, power supply included | RM634.00 | 2 Years | |
| iDS-7208HTHI- M2/S(C) | <p>8-ch 8MP(4K) 1U AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 8-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 8-ch IP video input (up to 16-ch) • 1-ch face detection or 8-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 8-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, 8MP@15fps, 1ch 4K UHD output, CVBS output • 2 SATA interface, up to 10TB/each, 1RJ45, 2 USB Ports, Support Wi-Fi dongle, 12VDC, power supply included | RM1,235.00 | 2 Years | |

| | | | | |
|---------------------------------|---|---------------------|----------------|-----------------|
| iDS-E04HQHI-D | <p>4-ch 1080p 1U eSSD AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 4-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 1-ch IP video input (up to 5-ch) • Support 4-ch line crossing detection and intrusion detection, 2-ch false alarm filter(classify human&vehicle) • H.265 Pro+ video compression, CH01-04:1080P/4MP Lite@15fps/ch • Built-in 1024GB eSSD (960GB available),1RJ45,2 USB Ports, 12VDC 1A, power supply included | RM426.00 | 3 Years | |
| iDS-E08HQHI-B | <p>8-ch 1080p 1U eSSD AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 8-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 2-ch IP video input (up to 10-ch) • Support 4-ch line crossing detection and intrusion detection, 4-ch false alarm filter(classify human&vehicle) • H.265 Pro+ video compression, CH01-08:1080P/4MP Lite@15fps/ch • Built-in 1024GB eSSD (960GB available),1RJ45,2 USB Ports, 12VDC 1A, power supply included | RM565.00 | 3 Years | |
| iDS-E04HUHI-B | <p>4-ch 5MP 1U eSSD AcuSense DVR</p> <ul style="list-style-type: none"> • TVI/ CVI/AHD/CVBS input adaptively, 4-ch HDTV coaxial video & audio input, 1-ch RCA audio input, 1-ch IP video input (up to 5-ch) • Support 4-ch line crossing detection and intrusion detection, 4-ch false alarm filter(classify human&vehicle) • H.265 Pro+ video compression, CH01-04:5MP/4MP @15fps/ch • Built-in 1024GB eSSD (960GB available),1RJ45,2 USB Ports, 12VDC 1A, power supply included | RM537.00 | 3 Years | |
| VIS-AS-12V2A UKAC Power Adpater | 12V 2A UK Power Adpater ,1000mA 12W 5.5x2.1mm Power AC Adapter for CCTV Camera,2MP 4-ch&8ch DVR, Routers, Door access, etc. | RM9.00 | 6 Months | |
| KPL-040F-VI | AC Adapter for DVR(4Pin) , Input:100-240V~50/60Hz 1.7A max. Output:+12.0V---3.33A , Different versions recorder require different adapters, please confirm with your sales person if it is applicable | RM61.00 | 6 Months | |
| KPL-060F-VI | AC Adapter(4Pin) for 2MP/3MP/5MP 16-ch DVR etc. Input:100-240V~50/60Hz 1.7A max. Output:+12.0V---5.00A ,Different versions recorder require different adapters, please confirm with your sales person if it is applicable | RM72.00 | 6 Months | |
| | Model | Descriptions | Srp(€m) | Warranty |
| HIKVISION NVR | | | | |
| DS-7104NI-Q1/4P/M | <p>4-ch Mini 1U 4PoE NVR, advise for 2MP IPC</p> <ul style="list-style-type: none"> • 4-ch Up to 4MP resolution • Incoming/Outgoing bandwidth:40Mbps/60Mbps, H.265+ • Decoding capability: 4-ch 1080P@30fps or 2-ch 4MP@30fps • 1 SATA interface,up to 6TB, 1RJ45,2 USB Ports, 48VDC 1A, power supply included | RM326.00 | 2 Years | |
| DS-7604NI-Q1/4P | <p>4-ch 1U 4PoE 4K NVR, advise for 2/4MP IPC</p> <ul style="list-style-type: none"> • 4-ch Up to 6MP resolution • Incoming/Outgoing bandwidth:40Mbps/80Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 1 SATA interface,up to 8TB, 1RJ45,2 USB Ports, 48VDC 1.35A, power supply included | RM427.00 | 2 Years | |
| DS-7604NXI-K1/4P | <p>4-ch 1U 4PoE 4K NVR, advise for 2MP/4MP & above IPC</p> <ul style="list-style-type: none"> • 4-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:40Mbps/80Mbps, H.265+ • 1-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 1 SATA interface,up to 8TB, 1RJ45,2 USB Ports, 48VDC 1.35A, power supply included | RM456.00 | 2 Years | |
| DS-7108NI-Q1/8P/M | <p>8-ch Mini 1U 8PoE NVR, advise for 2MP IPC</p> <ul style="list-style-type: none"> • 8-ch Up to 4MP resolution • Incoming/Outgoing bandwidth:60Mbps/60Mbps, H.265+ • Decoding capability: 4-ch 1080P@30fps or 2-ch 4MP@30fps • 1 SATA interface,up to 6TB, 1RJ45,2 USB Ports, 48VDC 1.8A, power supply included | RM456.00 | 2 Years | |
| DS-7608NI-Q1/8P | <p>8-ch 1U 8PoE 4K NVR, advise for 2/4MP IPC</p> <ul style="list-style-type: none"> • 8-ch Up to 6MP resolution • Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 1 SATA interface,up to 8TB, 1RJ45,2 USB Ports, 48VDC 1.88A, power supply included | RM570.00 | 2 Years | |
| DS-7608NXI-K1/8P | <p>8-ch 1U 8PoE 4K NVR, advise for 2MP/4MP & above IPC</p> <ul style="list-style-type: none"> • 8-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ • 1-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 1 SATA interface,up to 10TB, 1RJ45,2 USB Ports, 48VDC 1.88A, power supply included | RM623.00 | 2 Years | |
| DS-7608NXI-K2/8P | <p>8-ch 1U 8PoE 4K NVR, advise for 2MP/4MP & above IPC</p> <ul style="list-style-type: none"> • 8-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ • 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 2 SATA interface,up to 10TB, 1RJ45,3 USB Ports, 48VDC 2.5A, power supply included | RM818.00 | 2 Years | |
| DS-7608NI-Q2 | <p>8-ch 1U 4K NVR without PoE, advise for 2/4MP IPC</p> <ul style="list-style-type: none"> • 8-ch Up to 6MP resolution • Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 2 SATA interface,up to 8TB/each, 1RJ45,2 USB Ports, 12VDC 3.33A, power supply included | RM385.00 | 2 Years | |

| DS-7608NI-M2 | <p>8-ch 1U 4K NVR without PoE, advise for 4/8MP IPC</p> <ul style="list-style-type: none"> • 8-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:128Mbps/256Mbps, H.265+ • Decoding capability: 8-ch 8MP@30fps or 2-ch 32MP@30fps • 2 SATA interface,up to 16TB/each, 2RJ45,2 USB Ports, 12VDC 3.33A, power supply included | RM862.00 | 2 Years | |
|-------------------------|---|------------|----------|--|
| DS-7616NI-Q2/16P | <p>16-ch 1U 16PoE 4K NVR, advise for 2/4MP IPC</p> <ul style="list-style-type: none"> • 16-ch Up to 6MP resolution • Incoming/Outgoing bandwidth:160Mbps/80Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 2 SATA interface,up to 8TB/each, 1RJ45,2 USB Ports, 100-240V,3.4A, power supply included | RM866.00 | 2 Years | |
| DS-7616NXI-K2/16P | <p>16-ch 1U 16PoE 4K NVR, advise for 2MP/4MP & above IPC</p> <ul style="list-style-type: none"> • 16-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:160Mbps/160Mbps, H.265+ • 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • Decoding capability: 4-ch 4MP@30fps or 2-ch 8MP@30fps • 2 SATA interface,up to 10TB/each, 1RJ45,3 USB Ports, 100-240V,3.4A, power supply included | RM1,116.00 | 2 Years | |
| DS-7616NI-Q2 | <p>16-ch 1U 4K NVR without PoE, advise for 2/4MP IPC</p> <ul style="list-style-type: none"> • 16-ch Up to 6MP resolution • Incoming/Outgoing bandwidth:160Mbps/80Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 2 SATA interface,up to 8TB/each, 1RJ45,2 USB Ports, 12VDC, 2.1 A, power supply included | RM434.00 | 2 Years | |
| DS-7716NXI-K4/16P | <p>16-ch 1.5U 16PoE 4K NVR without PoE, advise for 2MP/4MP & above IPC</p> <ul style="list-style-type: none"> • 16-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:160Mbps/160Mbps, H.265+ • 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • Decoding capability: 6-ch 4MP@30fps or 3-ch 8MP@30fps • 4 SATA interface,up to 10TB/each, 1RJ45,3 USB Ports, 100-240V, power supply included | RM1,575.00 | 2 Years | |
| DS-7716NXI-K4 | <p>16-ch 1.5U 16PoE 4K NVR without PoE, advise for 2MP/4MP & above IPC</p> <ul style="list-style-type: none"> • 16-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:160Mbps/160Mbps, H.265+ • 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • Decoding capability: 6-ch 4MP@30fps or 3-ch 8MP@30fps • 4 SATA interface,up to 10TB/each, 1RJ45,3 USB Ports, 100-240V,3.4A, power supply included | RM1,041.00 | 2 Years | |
| DS-7716NI-M4 | <p>16-ch 1.5U 8K NVR without PoE, advise for 4/8MP IPC</p> <ul style="list-style-type: none"> • 16-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:256Mbps/256Mbps, H.265+ • Decoding capability: 10-ch 8MP@30fps or 16-ch 4MP@30fps • 4 SATA interface,1 eSATA interfaceup to 16TB/each, 2RJ45,3 USB Ports,100-240V, power supply included | RM1,618.00 | 2 Years | |
| DS-7732NXI-K4 | <p>32-ch 1.5U 4K NVR without PoE, advise for 2/4MP & above IPC</p> <ul style="list-style-type: none"> • 32-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:256Mbps/160Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 2-ch 8MP@30fps, • 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • 4 SATA interface,up to 10TB/each, 2RJ45,3 USB Ports, 100-240V, power supply included | RM1,187.00 | 2 Years | |
| DS-9632NI-M8 | <p>32-ch 2U 4K NVR without PoE, advise for 2/4MP & above IPC</p> <ul style="list-style-type: none"> • 32-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:320Mbps/400Mbps, H.265+ • Decoding capability: 8-ch 4MP@30fps or 4-ch 8MP@25fps, Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare • 8 SATA interface,up to 16TB/each,1 eSATA, 2RJ45,3 USB Ports, 100-240V, power supply included | RM3,872.00 | 2 Years | |
| DS-9664NI-M8 | <p>64-ch 2U 4K NVR without PoE, advise for 2/4MP & above IPC</p> <ul style="list-style-type: none"> • 64-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:400Mbps/400Mbps, H.265+ • Decoding capability: 8-ch 4MP@30fps or 4-ch 8MP@25fps, Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare • 8 SATA interface,up to 16TB/each,1 eSATA, 2RJ45,4 USB Ports, 100-240V, power supply included | RM5,439.00 | 2 Years | |
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION Switch | | | | |
| DS-3E1106P-EI/M | <p>4 Port 100Mbps Smart Managed PoE Switch</p> <ul style="list-style-type: none"> • 4 x 10/100Mbps PoE ports, and 2 x 10/100Mbps RJ45 ports • PoE power budget 45W, Network topology management, alarm push, network health monitor • Max. 300m long distance transmission, 6KV surge protection | RM135.00 | 2 Years | |
| DS-3E1309P-EI/M | <p>8 Port 100Mbps Smart Managed PoE Switch</p> <ul style="list-style-type: none"> • 8 x 10/100Mbps PoE ports, and and 1 x Gigabit RJ45 port • PoE power budget 60W, Network topology management, alarm push, network health monitor • Max. 300m long distance transmission, 6KV surge protection | RM223.00 | 2 Years | |
| DS-3E1318P-EI/M | <p>16 Port 100Mbps Smart Managed PoE Switch</p> <ul style="list-style-type: none"> • 16 x 10/100 Mbps PoE ports, 1x gigabit RJ45 port, and 1x Gigabit combo • PoE power budget 130WM, Network topology management, alarm push, network health monitor • Max. 300m long distance transmission, 6KV surge protection | RM603.00 | 2 Years | |

| | | | | |
|------------------------------------|---|----------------|-----------------|--|
| DS-3E1326P-EI/M | 24 Port 100Mbps Smart Managed PoE Switch <ul style="list-style-type: none"> • 24 × 10/100 Mbps PoE ports, 1x gigabit RJ45 port, and 1x Gigabit combo • PoE power budget 230W, Network topology management, alarm push, network health monitor • Max. 300m long distance transmission, 6KV surge protection | RM736.00 | 2 Years | |
| DS-3E1506P-EI/M | 4 Port Gigabit Smart Managed PoE Switch <ul style="list-style-type: none"> • L2, Smart Managed, 4 × Gigabit PoE ports, and 2 × Gigabit RJ45 port • PoE power budget 45W, HPP Cloud managed, VLAN, STP/RSTP loop prevention, PoE watchdog, Max. 300 meter PoE transmission • 6KV surge protection | RM150.00 | 2 Years | |
| DS-3E1510P-EI/M | 8 Port Gigabit Smart Managed PoE Switch <ul style="list-style-type: none"> • L2, Smart Managed, 8 × Gigabit PoE ports, and 2 × Gigabit RJ45 port • PoE power budget 60W, HPP Cloud managed, VLAN, STP/RSTP loop prevention, PoE watchdog, Max. 300 meter PoE transmission • 6KV surge protection | RM278.00 | 2 Years | |
| DS-3E0518P-E/M | 16 Port Gigabit Unmanaged PoE Switch <ul style="list-style-type: none"> • L2, Unmanaged, 16 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports • PoE power budget 125W • 6KV surge protection | RM782.00 | 2 Years | |
| DS-3E0526P-E/M | 24 Port Gigabit Unmanaged PoE Switch <ul style="list-style-type: none"> • L2, Unmanaged, 24 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports • PoE power budget 225W • 6KV surge protection | RM1,065.00 | 2 Years | |
| NEW DS-3E1518P-SI | L2 16 Port Gigabit Smart Managed PoE Switch <ul style="list-style-type: none"> • L2, Smart Managed, 16 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports • PoE power budget 250W • Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push & Video Control & Preview, PoE watchdog to auto detect and restart the cameras that do not respond. • Max. 300m long distance transmission, 6KV surge protection | RM1,121.00 | 2 Years | |
| NEW DS-3E1526P-SI | L2 24 Port Gigabit Smart Managed PoE Switch <ul style="list-style-type: none"> • L2, Smart Managed, 24 × Gigabit PoE ports, 2 × Gigabit SFP fiber optical ports • PoE power budget 370W • Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push & Video Control & Preview, PoE watchdog to auto detect and restart the cameras that do not respond. • Max. 300m long distance transmission, 6KV surge protection | RM1,482.00 | 2 Years | |
| HIKVISION Industrial Switch | | | | |
| NEW DS-3T1306P-SI/HS | Industrial 4 Port 100Mbps Smart Harsh PoE Switch <ul style="list-style-type: none"> • 4 × 100M PoE ports, 1 × gigabit RJ45 port and 1 × gigabit SFP Fiber Optical Port. • PoE power budget: 60W, Visualized topology management, Network Health Monitor • Max. 300m long distance transmission, 6KV surge protection, Wider temperature (-30 to 65 °C) design. | RM322.00 | 2 Years | |
| NEW DS-3T1310P-SI/HS | Industrial 8 Port 100Mbps Smart Harsh PoE Switch <ul style="list-style-type: none"> • 8x 100M PoE ports, 1x gigabit RJ45 port and 1x gigabit SFP Fiber Optical Port. • PoE power budget: 110W, Visualized topology management, Network Health Monitor • Max. 300m long distance transmission, 6KV surge protection, Wider temperature (-30 to 65 °C) design. | RM537.00 | 2 Years | |
| NEW DS-3T0506P | Industrial 4 Port Gigabit Unmanaged PoE Switch <ul style="list-style-type: none"> • 4 × Gigabit RJ45 port, 2 × Gigabit fiber optical port • PoE power budget: 120W, Max. Port Power 30W • Adopt redundant dual power input design, 6KV surge protection, Wider temperature (-40 to 75 °C) design. | RM1,065.00 | 2 Years | |
| SFP Module | | | | |
| HK-SFP-1.25G-20-1310 | SFP Module, single mode and single fiber <ul style="list-style-type: none"> • TX1310nm/1.25G, RX1550nm/1.25G, LC Connector, single mode and single fiber, 20km Distance • Hot pluggable capability, Operating temperature 0-70°C • To pair use with HK-SFP-1.25G-20-1550 | RM99.00 | 2 Years | |
| HK-SFP-1.25G-20-1550 | SFP Module, single mode and single fiber <ul style="list-style-type: none"> • TX1550nm/1.25G, RX1310nm/1.25G, LC Connector, single mode and single fiber, 20km Distance • Hot pluggable capability, Operating temperature 0-70°C • To pair use with HK-SFP-1.25G-20-1310 | RM112.00 | 2 Years | |
| HK-SFP-1.25G-20-1310-DF | SFP Module, Single mode and duplex fiber <ul style="list-style-type: none"> • TX1310nm/1.25G, RX1310nm/1.25G, LC Connector, Single mode and duplex fiber, 20km Distance • Hot pluggable capability, Operating temperature 0-70°C • To pair use with HK-SFP-1.25G-20-1310-DF | RM95.00 | 2 Years | |
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION Wireless Bridge | | | | |
| DS-3WF0AC-2NT | 2.4Ghz 300Mbps 100m Elevator Wireless CPE(a pair 2pcs) <ul style="list-style-type: none"> • Up to 100 m wireless transmission distance • 300 Mbps 802.11n wireless, Built-in 8 dBi 2 × 2 MIMO Antenna • 12 V/1 A passive PoE or 12 V/1 A DC, Package Content: CPE(a pair), Power Adapter, Pole Mounting Straps | RM195.00 | 2 Years | |
| DS-3WF0FA-2N/O(2Pcs) | 2.4Ghz 300Mbps 1Km 70° Wireless AP Bridge(a pair 2pcs) <ul style="list-style-type: none"> • Up to 1km wireless transmission distance • 300 Mbps 802.11n wireless, Built-in 7 dBi 2 × 2 MIMO Antenna, Visualized topology management • 12 VDC/1 A Passive PoE, Package Content: CPE x2, Power Adapter x2, 10/100 Mbps PoE injector × 2, binding tape × 4 | RM287.00 | 2 Years | |

| DS-3WF02C-5AC/O(2Pcs) | <p>5Ghz 867Mbps 5km Outdoor Wireless CPE(a pair 2pcs)</p> <ul style="list-style-type: none"> Up to 5km wireless transmission distance,Point-to-Point, Point-to-Multipoint 867 Mbps 802.11a/n/ac wireless,Built-in 12 dBi 2 × 2 MIMO Antenna,Visualized topology management 12 VDC/1 A Passive PoE,Package Content: CPE x2,Power Adapter x2,10/100 Mbps PoE injector × 2, binding tape × 4 | RM433.00 | 2 Years | |
|------------------------------|---|----------|----------|--|
| Model | Descriptions | Srp(rm) | Warranty | |
| HIKVISION Door Access | | | | |
| DS-K1T8003EF | <p>Fingerprint Access Control Terminal</p> <ul style="list-style-type: none"> 2.4-inch LCD Display,Built-in EM card reading module, Support Fingerprint 1000 fingerprints, 1000 card and Max. 100,000 event records Communication: TCP/IP, ISUP5.0 Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm | RM207.00 | 2 Years | |
| DS-K1T8003MF | <p>Fingerprint Access Control Terminal</p> <ul style="list-style-type: none"> 2.4-inch LCD Display,Built-in Mifare card reading module, Support Fingerprint 1000 fingerprints, 1000 card and Max. 100,000 event records Communication: TCP/IP, ISUP5.0 Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm | RM207.00 | 2 Years | |
| DS-K1T804AEF | <p>Fingerprint Access Control Terminal</p> <ul style="list-style-type: none"> 2.4-inch LCD Display,Built-in EM card reading module, Support Fingerprint 3,000 fingerprints, 3,000 cards and 100,000 events storage Communication via TCP/TP and Wi-Fi,RS-485, wiegand interface Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM261.00 | 2 Years | |
| DS-K1T804AMF | <p>Fingerprint Access Control Terminal</p> <ul style="list-style-type: none"> 2.4-inch LCD Display,Built-in Mifare card reading module, Support Fingerprint 3,000 fingerprints, 3,000 cards and 100,000 events storage Communication via TCP/TP and Wi-Fi,RS-485, wiegand interface Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM261.00 | 2 Years | |
| DS-K1T321EX | <p>Face Recognition Access Control Terminal</p> <ul style="list-style-type: none"> 2.4-inch LCD screen, 2 MP lens,Multiple authentication methods, including face,card (EM card), and PIN, etc. 500 faces, 3000 cards, and 150,000 events Communication via TCP/TPi,RS-485 interface Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM307.00 | 2 Years | |
| DS-K1T321MX | <p>Face Recognition Access Control Terminal</p> <ul style="list-style-type: none"> 2.4-inch LCD screen, 2 MP lens,Multiple authentication methods, including face,card (Mifare card), and PIN, etc. 500 faces, 3000 cards, and 150,000 events Communication via TCP/TP,RS-485 interface Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM307.00 | 2 Years | |
| DS-K1T321EFX | <p>Face Recognition Access Control Terminal</p> <ul style="list-style-type: none"> 2.4-inch LCD screen, 2 MP lens,Multiple authentication methods, including face, fingerprint, card (EM card), and PIN, etc. 500 faces, 3000 cards, 3000 fingerprints and 150,000 events Communication via TCP/TPi,RS-485 interface Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM364.00 | 2 Years | |
| DS-K1T321MFX | <p>Face Recognition Access Control Terminal</p> <ul style="list-style-type: none"> 2.4-inch LCD screen, 2 MP lens,Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. 500 faces, 3000 cards, 3000 fingerprints and 150,000 events Communication via TCP/TP,RS-485 interface Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM364.00 | 2 Years | |
| DS-K1T321MFWX | <p>Face Recognition Access Control Terminal</p> <ul style="list-style-type: none"> 2.4-inch LCD screen, 2 MP lens,Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. 500 faces, 3000 cards, 3000 fingerprints and 150,000 events Communication via TCP/TP and Wi-Fi,RS-485,wiegand interface Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM393.00 | 2 Years | |
| DS-K1T342MFX | <p>Face Recognition Access Control Terminal</p> <ul style="list-style-type: none"> 4.3-inch LCD touch screen, 2 MP lens,Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. Two-way audio 1500 faces, 3000 cards, 3000 fingerprints Communication via TCP/TP,RS-485 interface,12 VDC/1 A(power adapter included) Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM553.00 | 2 Years | |

| | | | | |
|---|---|----------------|-----------------|--|
| DS-K1T342MFX-E1 | Face Recognition Access Control Terminal (PoE) <ul style="list-style-type: none"> 4.3-inch LCD touch screen, 2 MP lens, Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. Two-way audio 1500 faces, 3000 cards, 3000 fingerprints Communication via TCP/IP, RS-485 interface, Power input: Power interface (power adapter included, 12 VDC/1A) or PoE (37 to 57 VDC/0.6 A) Power output: Power supply for x1 door lock, 12 VDC/1 A Support Access Control and Time Attendance Function. Remotely opens door via Hik-Connect mobile client, Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM572.00 | 2 Years | |
| DS-K1T671MF | Face Recognition Access Control Terminal <ul style="list-style-type: none"> 7-inch LCD touch screen, 2 MP lens, Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. Two-way audio 6000 faces, 6000 cards, 5000 fingerprints Communication via TCP/IP and Wi-Fi, RS-485 interface. IP65 Support Access Control and Time Attendance Function. Remotely opens door via Hik-Connect mobile client, Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out | RM1,388.00 | 2 Years | |
| Model | Description | Srp(rm) | Warranty | |
| HIKVISION Door Access Controller & Read | | | | |
| DS-K2811 | Single-door Access Controller <ul style="list-style-type: none"> Storage with 10,000 cards and 50,000 access control events, Uplink Communication: TCP/IP Accessible Card Reader: 2 Wiegand readers or RS485 reader; Input interface: Door Sensor×1, Door Switch×1, Case Input×1; Output interface: Door Switch Relay×1, Alarm Relay×4. Supports multi-door interlocking function, anti-passback function supports the Backup Battery Connection, Data can be saved when the access controller is powered off | RM419.00 | 2 Years | |
| DS-K2812 | Double-door Access Controller <ul style="list-style-type: none"> Storage with 10,000 cards and 50,000 access control events, Uplink Communication: TCP/IP Accessible Card Reader: 4 Wiegand readers or RS485 reader; Input interface: Door Sensor×2, Door Switch×2, Case Input×2; Output interface: Door Switch Relay×2, Alarm Relay×4. Supports multi-door interlocking function, anti-passback function supports the Backup Battery Connection, Data can be saved when the access controller is powered off | RM480.00 | 2 Years | |
| DS-K2814 | Four-door Access Controller <ul style="list-style-type: none"> Storage with 10,000 cards and 50,000 access control events, Uplink Communication: TCP/IP Accessible Card Reader: 4 Wiegand readers or RS485 reader; Input interface: Door Sensor×4, Door Switch×4, Case Input×3; Output interface: Door Switch Relay×4, Alarm Relay×4. Supports multi-door interlocking function, anti-passback function supports the Backup Battery Connection, Data can be saved when the access controller is powered off | RM542.00 | 2 Years | |
| DS-K1102AM | 1102 Series Card Reader <ul style="list-style-type: none"> Mifare card reader Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm IP 64, Applied for 86 & 120 Gang Box | RM93.00 | 2 Years | |
| DS-K1102AMK | 1102 Series Card Reader <ul style="list-style-type: none"> Mifare card reader, with keypad Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm IP 64, Applied for 86 & 120 Gang Box | RM118.00 | 2 Years | |
| DS-K1102AE | 1102 Series Card Reader <ul style="list-style-type: none"> EM card reader Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm IP 64, Applied for 86 & 120 Gang Box | RM93.00 | 2 Years | |
| DS-K1102AEK | 1102 Series Card Reader <ul style="list-style-type: none"> EM card reader Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm IP 64, Applied for 86 & 120 Gang Box | RM118.00 | 2 Years | |
| Door Access Accessories | | | | |
|  VIS-AC-Glass Door Lock-KB608-TY c/w controller | Double Glass Door Lock, include x1 remote controller <ul style="list-style-type: none"> Multiple authentication methods, including fingerprint, card (Mifare card), and PIN, APP, Max.100 fingerprints capacity, Max.1,000 ID card capacity Applicable glass door thickness: 10-12mm Power supply mode 4 AAA batteries/Micro-USB emergency power supply interface | RM331.00 | 6 Months | |
| VIS-AC-Remote control for door access/barrier/autogate | Remote control for door access/barrier/autogate(50m) <ul style="list-style-type: none"> x1 Receiver, x2 controller, 50m distance Rated Current: 12VDC Frequency: 315 Mhz Load Capacity: Single Circuit s 3.5A | RM74.00 | 6 Months | |
| VIS-AC-Y280-5Bolts(EM Lock) | Surface mounted magnetic lock (280kg/600lbs) 5 bolts <ul style="list-style-type: none"> Lock size: 250x47x25mm Holding force: 280KG Working voltage: 12/24V DC Working current: 400/200mA | RM64.00 | 6 Months | |
| VIS-AC-Y280-BS (EM Lock with buzzer) | Surface mounted magnetic lock (280kg/600lbs) 5 bolts, c/w buzzer for unlock alarm <ul style="list-style-type: none"> Lock size: 250x47x25mm Holding force: 280KG Working voltage: 12/24V DC Working current: 400/200mA | RM77.00 | 6 Months | |
| VIS-AC-Y280LAbracket | Bracket for Holding lock Plate Installation <ul style="list-style-type: none"> Size : 183x45x17mm Suitable for: 280KG/600LBS Lock magnetic loc | RM16.00 | 6 Months | |
| VIS-AC-Y280Ubracket | U Bracket <ul style="list-style-type: none"> Size : 182x45x28mm Suitable for: 280/350KG magnetic lock | RM15.00 | 6 Months | |

| | | | | |
|---|---|----------------|-------------------------------|--|
| VIS-AC-Y280Lbracket | L Bracket Size : 250x47x28mm Suitable for: 280kg magnetic lock | RM13.00 | 6 Months | |
| VIS-AC-Y280ZLbracket | ZL Bracket Size: 250x47mm +180x53mm Suitable for: 280/350KG magnetic lock | RM26.00 | 6 Months | |
| VIS-AC-K1(ExitButton) | Exit Button Plastic panel Exit Button 86*86mm | RM5.00 | 6 Months | |
| VIS-AC-K2B(Touchless Exit Button) | Touchless Exit Button Size: 86Lx86Wx29H(mm) | RM20.00 | 6 Months | |
| VIS-AC-K3G(Emergency release button) | Emergency release button Resetting Function | RM16.00 | 6 Months | |
| VIS-AC-Y806-3A(Power Supply Box 12V 3A) | Backup Power Supply Box 12V 3A can put back up battery inside(Battery not include) | RM46.00 | 6 Months | |
| VIS-AC-Y806-5A(Power Supply Box 12V 5A) | Backup Power Supply Box 12V 5A can put back up battery inside(Battery not include) | RM56.00 | 6 Months | |
| VIS-AC-Y806-7A(Battery backup 12V 7AH) | Battery backup 12V 7AH | RM39.00 | 6 Months | |
| VIS-AC-EMI-S(EMCard) | 125Khz EM Proximity white blank card Read distance: 1 to 10cm Reading times: >100,000 Applications: access control and identification Thickness: 0.84 to 1.2mm Operating frequency: 125kHz | RM2.00 | NA | |
| VIS-AC-MF(Mifare Card) | Mifare 1K Compatible white blank card 13.56 MHz 1K Memory S50 reader and writer RFID Smart Card. Dimension:86x54x0.8(+/-0.04) mm. Working Frequency:13.56MHz. | RM2.00 | NA | |
| Model | Description | Srp(rm) | Wrranty | |
| HIKVISION Wireless Alarm | | | | |
| DS-PWA64-Kit- WB | 433MHz Wireless Control Panel Kits with keyfob • Supports Wi-Fi, TCP/IP,4G communication methods,Support 64Zones • Supports Hik-Connect/Hik-Partner Pro/Web Portal/ IVMS4200/ Convergence Cloud • Kit Included: 1x Wireless Control Panel (DS-PWA64-L-WB) 1x Wireless Keyfob (DS-PKF1-WB) 1x Wireless PIR Detector (DS--PDP15P-WG2-WB) 1x Wireless Magnetic Contact (DS-PDMC-EG2-WB) | RM623.00 | 2 Years (one to one exchange) | |
| DS-PDP15P-EG2- WB | 433MHz AX Pro Wireless PIR Detector • Two-way Tri-X wireless technology Communication,Range: 1200m (open area) • PIR Detection Range: 15m / 85.9° • Fully remote configurable through APP • Installation Height: 1.8 to 2.4m • Battery Type: 1 * CR123A batteries (included by default, easy replaceable) • Battery Life: 5 years in working status(triggered 10 times every day) | RM122 | 2 Years (one to one exchange) | |
| DS-PDPC12P- EG2-WB | 433MHz AX Pro Wireless PIRCAM Detector • Two-way Tri-X wireless technology Communication,Range: 800m (open area) • PIR Detection Range: 12m / 85.9° • Camera resolution:640*480 Lens Coverage: 88°(H), 68°(V) • Fully remote configurable through APP • Installation Height: 1.8 to 2.4m • Battery Type: 1 * CR123A batteries (included by default, easy replaceable) • Battery Life: 6 years in working status(triggered twice every week, 20 QVGA frames captured for every alarm) | RM321.00 | 2 Years (one to one exchange) | |
| DS-PDMC-EG2- WB | AX Pro Wireless Magnetic Contact • Two-way Tri-X wireless technology Communication,Range: 1200m (open area) • 2-ch External Zones for wired sensors • Fully remote configurable through APP • Slim design for an unobtrusive (unnoticeable) installation • Battery Type: 1 * CR123A batteries (included by default, easy replaceable) • Battery Life: 5 years in working status(triggered 10 times every day) | RM91.00 | 2 Years (one to one exchange) | |
| DS-PDMCS-EG2- WB | AX Pro Wireless Magnetic Contact • Two-way Tri-X wireless technology Communication,Range: 1200m (open area) • Fully remote configurable through APP • Battery Type: 1 * CR2450 batteries (included by default, easy replaceable) • Battery Life: 3 years in working status(triggered 10 times every day) | RM68.00 | 2 Years (one to one exchange) | |
| DS-PDMCK-EG2- WB | 433MHz AX Pro Wireless Magnet Shock Detector • Two-way Tri-X wireless technology Communication,Range: 1200m (open area) • 2-ch External Zones for wired sensors • Fully remote configurable through APP • Slim design for an unobtrusive (unnoticeable) installation • Battery Type: 1 * CR123A batteries (included by default, easy replaceable) • Battery Life: 3 years in working status(triggered 10 times every day) | RM114.00 | 2 Years (one to one exchange) | |
| DS-PDBG8-EG2- WB | 433MHz AX Pro Wireless Glass Break Detector • Two-way Tri-X wireless technology Communication,Range: 1200m (open area) • Fully remote configurable through APP • 2-ch External Zones for wired sensors • Battery Type: 2 * CR123A batteries (included by default, easy replaceable) • Battery Life: 5 years in working status(triggered 10 times every day) | RM122.00 | 2 Years (one to one exchange) | |
| DS-PDWL-E-WB | 433MHz AX Pro Wireless Water Leak Detector • Two-way Tri-X wireless technology Communication,Range: 1000m (open area) • Fully remote configurable through APP • Battery Type: 1 * CR2450 batteries (included by default, easy replaceable) • Battery Life: 3 years in working status(triggered 10 times every day) | RM134.00 | 2 Years (one to one exchange) | |

| | | | | |
|-----------------------------------|--|--------------------|-------------------------------|-----------------|
| DS-PDSMK-S- WB | 433MHz Wireless Photoelectric Smoke Detector <ul style="list-style-type: none"> Two-way RF wireless technology Communication,Range: 800m (open area) Fully remote configurable through APP Battery Type: Non Replaceable 1x CR17450 Battery Life: 10 years(standby time) | RM179.00 | 2 Years (one to one exchange) | |
| DS-PR1-WB | 433MHz AX PRO Series Repeater <ul style="list-style-type: none"> Two-way Tri-X and Cam-X wireless technology; Communication,Range: 800m (open area) Fully remote configurable through APP Multiple Enrolling Methods: Power up, Remote ID, QR Code Finding and connecting up to 8 PIRCAM or smoke detectors automatically, smart auto-pairing Power supply 100 VAC to 240 VAC, Up to 35 hrs battery backup after mains lost, no worry about communication | RM287.00 | 2 Years (one to one exchange) | |
| DS-PS1-I-WB(Blue Indicator) | AX Pro Wireless Indoor Sounder with Blue Strobe Light <ul style="list-style-type: none"> Two-way Tri-X wireless technology Communication,Range: 900m (open area) 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm Fully remote configurable through APP Buzzer Decibel: 90 to 110dB,Front & rear panel tamper-proof Battery Type: 3 * CR123A batteries (included by default, easy replaceable) Battery Life: 3 years(triggered once every two weeks and alerting 90s for each triggering) | RM156.00 | 2 Years (one to one exchange) | |
| DS-PS1-I-WB(Red Indicator) | AX Pro Wireless Indoor Sounder with Red Strobe Light <ul style="list-style-type: none"> Two-way Tri-X wireless technology Communication,Range: 900m (open area) 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm Fully remote configurable through APP Buzzer Decibel: 90 to 110dB,Front & rear panel tamper-proof Battery Type: 3 * CR123A batteries (included by default, easy replaceable) Battery Life: 3 years(triggered once every two weeks and alerting 90s for each triggering) | RM156.00 | 2 Years (one to one exchange) | |
| DS-PS1-E-WB(Red Indicator) | AX Pro Wireless Outdoor Sounder with Red Strobe Light <ul style="list-style-type: none"> Two-way Tri-X wireless technology Communication,Range: 900m (open area) 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm Fully remote configurable through APP Buzzer Decibel: 90 to 110dB, IP65 approved for outdoor installation Battery Type: 4 * CR123A batteries (included by default, easy replaceable) Battery Life: 3 years(triggered once every two weeks and alerting 90s for each triggering) | RM274.00 | 2 Years (one to one exchange) | |
| DS-PDEB1-EG2-WB(B)(Single button) | 433MHz AX Pro Wall-mounted Wireless Emergency Button <ul style="list-style-type: none"> Two-way RF wireless technology Communication,Range: 800m (open area) Fully remote configurable through App IP66 daily environment protection Frequency hopping against jamming for reliable transmission Battery Type: 1 * CR2450 batteries (included by default, easy replaceable) Battery Life: 3 years(triggered 10 times every day) | RM64.00 | 2 Years (one to one exchange) | |
| DS-PDEBP1-EG2-WB(Single button) | 433MHz AX Pro Wireless Portable Emergency Button <ul style="list-style-type: none"> Accidental press protection Fully remote configurable through App IP66 daily environment protection Frequency hopping against jamming for reliable transmission Optional lanyard and wristband accessory available Battery Type: 1 * CR2032 batteries (included by default, easy replaceable) Battery Life: 3 years(triggered 10 times every day) | RM64.00 | 2 Years (one to one exchange) | |
| DS-PM1-O1L- WB | 433MHz AX Pro Relay Module <ul style="list-style-type: none"> Two-way Tri-X wireless technology Communication,Range: 800m (open area) Fully remote configurable through App One-way output and one-way tamper input Frequency hopping against jamming for reliable transmission Voltage protection Trigger By Zone Alarm, By Arm/Disarm/Away/Clear Alarm, By Faults, By Manually, By Schedule | RM100.00 | 2 Years (one to one exchange) | |
| DS-PM1-O1H- WB | 433MHz AX Pro Wall Switch <ul style="list-style-type: none"> Two-way Tri-X wireless technology Communication,Range: 800m (open area) Fully remote configurable through App One-way output Frequency hopping against jamming for reliable transmission Voltage and current protection Trigger By Zone Alarm, By Arm/Disarm/Away/Clear Alarm, By Faults, By Manually, By Schedule | RM114.00 | 2 Years (one to one exchange) | |
| | Model | Description | Srp(€) | Warranty |
| HIK VISION Hybrid Alarm | | | | |
| DS-PHA64-Kit- WB | 433MHz AX Hybrid Pro Control Panle Kit <ul style="list-style-type: none"> Hybrid system: 8 on-board zones and 56 wired/wireless zones expandable,4 on-board outputs, and 60 wired/wireless outputs expandable Supports arming/disarming via keypad, keyfob, APP, iVMS-4200, SMS and tag Multiple configuration tools: APP, Web server, iVMS-4200 Kit Included: <ul style="list-style-type: none"> -64 zone controller DS-PHA64-LP *1 -Keypad DS-PK1-LRT-HWB *1 -Magnetic door contact DS-PD1-MC-WS *1 -PIR detector DS-PDP18-EG2 *2 -Keyfob DS-PKF1-WB *1 -Tag DS-PT-M1 *2 | RM667 | 2 Years (one to one exchange) | |

| | | | | |
|-----------------|---|----------|-------------------------------|--|
| DS-PHA64-LP | <p>AX Hybrid PRO Control Panel</p> <ul style="list-style-type: none"> Hybrid system: 8 on-board zones and 56 wired/wireless zones expandable, 4 on-board outputs, and 60 wired/wireless outputs expandable Dual-path communication of alarm events and other signals over LAN, PSTN, Wi-Fi, GPRS or 3G/4G utilizing a main and backup channel with configurable priority 8-ch HD wired PIRCAM for image verification, GIF can have maximum 20 pics, 4-ch on-board IP camera video verification, supports video recording (5s pre-alarm + 2s post-alarm, or 2s pre-alarm + 5s post-alarm) for verification to the alarm receiving email or mobile client Supports arming/disarming via keypad, keyfob, APP, iVMS-4200, SMS and tag Multiple configuration tools: APP, Web server, iVMS-4200 Pushes alarm notification via messages, email and Hik-Connect 1 installer, 1 administrator, and 62 users Supports ISAPI, Cloud P2P, ISUP, CSV-IP and DC-09 protocol Supports 1 Speed-X Bus | RM460.00 | 2 Years (one to one exchange) | |
| DS-PM2-S | <p>3/4G Communication Module</p> <ul style="list-style-type: none"> FDD-LTE B1/B3/B7/B8/B20 Dual-Band UMTS/HSDPA/HSPA+B1/B8 GSM/GPRS/EDGE 900/1800MHz | RM323.00 | 2 Years | |
| DS-PK1-LRT- HWB | <p>Wired LCD Keypad</p> <ul style="list-style-type: none"> 80 × 25 mm LCD screen display Supports arming and disarming by swiping cards Supports remote arming and disarming via keyfob One-push to arm (Arming without password) Supports user friendly operation menu Supports displaying zone name on the LCD screen Supports Fire/Panic/Medical alarm key Supports 2 on-board alarm inputs and 1 on-board alarm output Supports displaying the real-time system status by LED indicator Detachable wiring terminal for easy wiring and installation Temper proof: cover and wall | RM234.00 | 2 Years (one to one exchange) | |
| DS-PM1-I8O2-H | <p>Wired Input Expander</p> <ul style="list-style-type: none"> 8 on-board wired zones Support 3EOL connection (Alarm: 1KΩ; Tamper: 1KΩ; Fault: 2.2KΩ) Support zone alarm, tamper, masking, fault, short detection 1 power output for wired detectors 2 Speed-X bus, supporting wired input expander cascade mode | RM128.00 | 2 Years (one to one exchange) | |
| DS-PM1-O4L-H | <p>Wired Output Expander</p> <ul style="list-style-type: none"> 4 on-board low current relays, supporting 6-30V and up to 5A current 1 power output, maximum 500mA Powered by Speed-X technology, supporting expander cascading with 1 uplink + Speed-X port and 1 downlink Speed-X port | RM163.00 | 2 Years (one to one exchange) | |
| DS-PM1-RT- HWB | <p>Tri-X Wireless Receiver(433MHz)</p> <ul style="list-style-type: none"> Wireless transmission distance up to 1300m Supports 32 wireless detectors, 4 wireless indoor sounders and 8 wireless outdoor sounders | RM180.00 | 2 Years (one to one exchange) | |
| DS-PD1-EB | <p>Panic Button</p> <ul style="list-style-type: none"> Flame retardant ABS shell Capacity: ≤ 250V/300mA Connection mode: NO/NC | RM11.00 | 2 Years | |
| DS-PDP18-EG2 | <p>Wired internal 18m PIR detector</p> <ul style="list-style-type: none"> Up to 18m volumetric detection coverage, the Ellipse is the ideal solution for any small to large indoor rooms and spaces. Digital temperature compensation Automatic sensitivity 3D optics - Improves the detection of moving targets Creep-zone protection - covers the blind spot area directly below it, where an intruder may have otherwise avoided detection Selectable EOL resistors, Anti-insect interference Wide voltage 9 to 16 V wide voltage adaptation with polarity reverse connection protection IFT technology - automatically adjust the upper and lower alarm trip thresholds when exposed to electromagnetic or electrical interference and shift the thresholds before the detector goes into false alarm | RM36.00 | 2 Years (one to one exchange) | |
| DS-PD1-MC-WS | <p>Surface mounted magnetic contact of plastic casing</p> <ul style="list-style-type: none"> ABS shell Connection type: NC Designed for the surface mounting on wood door Active gap: 40 mm | RM11.00 | 2 Years | |
| DS-PS1-B | <p>Wired Outdoor Siren</p> <ul style="list-style-type: none"> Sound and LED flash indication separately Sound Decibel: 105dB at 30cm IP54 protective level Dimension(WxHxD): 140*134*33mm Weight: 185g Power supply: 8 ~ 16 V DC | RM63 | 2 Years (one to one exchange) | |

*Prices are subject to change without prior notice. Please Call for stock available

For Products Enquiries, kindly contact (PM) Lee- 012-327 5139 | lee@apaq.com.my