







HIKVISION TVI Camera



Fish-eye Camera



HIKVISION PTZ Camera



HIKVISION IP Camera

APAQ HIKVISION PRODUCT



HIKVISION NVR



HIKVISION DVR





SFP Module



HIKVISION Product Price List

Date:1-4-2025

	HIKVISION Product Price List		Date:1-4	-2025
Model	Descriptions	Srp(rm)	Warranty	
HIKVISION TVI Camera				
DS-2CE16D0T-EXIF	2MP Fixed Mini Bullet 4 in 1 Camera • 2MP CMOS Sensor,ICR, up to 25fps/30fps(1920x1080) • 2.8/3,6mm lens, 0.02 Lux/F1.2, 20m EXIR • DNR,DWDR, P67 • Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included	RM63.00	2 Years (one to one exchange)	
DS-2CE76D0T-EXIPF	2MP Indoor Fixed Turret 4 in 1 Camera • 2MP CMOS Sensor,ICR.up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.02 Lux/F1.2, 20m EXIR • DNR,DWDR • Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included	RM50.00	2 Years (one to one exchange)	
DS-2CE19D0T-VFIT3F(C) (2MP Vari-focal)	2MP Manual Varifocal Bullet 4 in 1 Camera • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.7-13.5mm varifocal lens, 0.01 Lux/F1.2, 40m EXIR • DNR,DWDR, P67 • Switchable TVI/AHD/CVI/CVBS video signal output • Front cover: Metal, Main body: Plastic,Bracket: Metal. 12VDC,Power supply no included	RM180.00	2 Years (one to one exchange)	
DS-2CE5AD0T-VPIT3F(C) (2MP Vari-focal)	2MP Vandal Manual Varifocal Dome 4 in 1 Camera • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.7-13.5mm varifocal lens, 0.01 Lux/F1.2, 40m EXIR • DNR,DWDR, P67, IK10 • Switchable TVI/AHD/CVI/CVBS video signal output • Enclosure:Plastic,Main body:Metal,Mounting base:Plastic. 12VDC,Power supply no included	RM180.00	2 Years (one to one exchange)	
DS-2CE16D0T-ITFS	2MP Audio Fixed Mini Bullet Camera • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.02 Lux/F1.2, 30m EXIR • DNR,DWDR, P67, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included	RM88.00	2 Years (one to one exchange)	
DS-2CE76D0T-ITPFS	2MP Audio Indoor Fixed Turret Camera • 2MP CMOS Sensor,ICR,up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.02 Lux/F1.2, 20m EXIR • DNR,DWDR,OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included	RM77.00	2 Years (one to one exchange)	
DS-2CE16H0T-ITF	5MP Fixed Mini Bullet 4 in 1 Camera • 5MP CMOS Sensor,ICR,up to 20fps(2560x1944) • 2.8/3.6mm lens, 0.01 Lux/F1.2, 20m EXIR • DNR,DWDR,BLC, P67, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included	RM101	2 Years (one to one exchange)	
DS-2CE76H0T-ITPF	5MP Indoor Fixed Turret 4 in 1 Camera • 5MP CMOS Sensor,ICR.up to 20fps(2560x1944) • 2.8/3.6mm lens, 0.01 Lux/F1.2, 20m EXIR • DNR,DWDR,BLC, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included	RM80	2 Years (one to one exchange)	
DS-2CE19H0T-AIT3ZF (5MP Vari-focal)	SMP Motorized Varifocal Bullet 4 in 1 Camera • SMP CMOS Sensor,ICR.up to 20fps(2560x1944) • 2.7-13.5mm motorized varifocal lens, 0.01 Lux/F1.2, 40m EXIR • DNR,DWDR,BLC,HLC, P67, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Metal, Dual Voltage 12VDC/24VAC,Power supply no included	RM276	2 Years (one to one exchange)	
DS-2CE5AH0T-AVPIT3ZF (5MP Vari-focal)	SMP Vandal Motorized Varifocal Dome 4 in 1 Camera • SMP CMOS Sensor,ICR.up to 20fps(2560x1944) • 2.7-13.5mm motorized varifocal lens, 0.01 Lux/F1.2, 40m EXIR • DNR,DWDR,BLC,HLC, P67, OSD Menu, IK10 • Switchable TVI/AHD/CVI/CVBS video signal output • Metal,Dual Voltage 12VDC/24VAC,Power supply no included	RM276.00	2 Years (one to one exchange)	
DS-2CE16K0T-LFS	3K Smart Hybrid Light Audio Fixed Mini Bullet Camera • 3K CMOS Sensor,ICR,up to 20fps(2960x1665) • 2.8/3.6mm lens, 0.01 Lux/F1.6, 30m EXIR,20m White Light • DNR,DWDR,BLC,HLC, P67, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included	RM114.00	2 Years (one to one exchange)	
DS-2CE76K0T-LPFS	3K Smart Hybrid Light Audio Indoor Fixed Turret Camera • 3K CMOS Sensor,ICR,up to 20fps(2960x1665) • 2.8/3.6mm lens, 0.01 Lux/F1.6, 20m EXIR,20m White Light • DNR,DWDR,BLC,HLC, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included	RM96.00	2 Years (one to one exchange)	
DS-2CE16U0T-ITF	8MP(4K) Fixed Mini Bullet 4 in 1 Camera 8.3MP CMOS Sensor,ICR,up to 12.5fps(3840x2160) • 2.8/3.6mm lens, 0.01 Lux/F1.2, 30m EXIR • DNR,DWDR,BLC,HCL, P67, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included	RM165.00	2 Years (one to one exchange)	



DS-2CE76U0T-ITPF	8MP(4K) Indoor Fixed Turret 4 in 1 Camera • 8.3MP CMOS Sensor,ICR.up to 12.5fps(3840x2160) • 2.8/3.6mm lens, 0.01 Lux/F1.2, 30m EXIR • DNR,DWDR,BLC,HCL, P67, OSD Menu • Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included	RM143.00	2 Years (one to one exchange)	
VIS-AS-12V2A UK ACPower Adpater	12V 2A UK Power Adpater,1000mA 12W 5.5x2.1mm Power AC Adapter for CCTV Camera,2MP 4-ch&8ch DVR, Routers, Door access, etc.	RM9.00	6 Months	
Model	Descriptions	Srp(rm)	Warranty	
HIKVISION 24 Hours Full Time ColorVu came	2MP ColorVu Audio Fixed Mini Bullet Camera			
ColorVi DS-2CE10DF3T-FS	2MP 24/7 color imaging Sensor,up to 25fps/30fps(1920x1080) 2.8/3.6mm lens, 0.0005Lux @F1.0, 20m white light distance DNR,BLC,HLC,130 dB true WDR, P67, OSD Menu Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output Metal, 12VDC,Power supply no included	RM139.00	2 Years (one to one exchange)	
CotorVu DS-2CE70DF3T-PFS	2MP ColorVu Indoor Audio Fixed Turret Camera • 2MP 24/7 color imaging Sensor,up to 25fps/30fps(1920x1080) • 2.8/3.6mm lens, 0.0005Lux @FI.0, 20m white light distance • DNR,BLC,HLC,130 dB true WDR, P67, OSD Menu • Built-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Plastic, 12VDC,Power supply no included	RM126.00	2 Years (one to one exchange)	
ColorVu DS-2CE10KF0T-FS	SMP(3K) ColorVu Audio Fixed Mini Bullet Camera • 5MP 24/7 color imaging Sensor,up to 20fps(2960x1665) • 2.8/3.6mm lens, 0.001Lux @F1.0, 20m white light distance • DNR,BLC,HLC,DWDR, PG, OSD Menu • Bullt-in Mic,Audio up Coaxial(Only TVI), Switchable TVI/AHD/CVI/CVBS video signal output • Metal, 12VDC,Power supply no included	RM150.00	2 Years (one to one exchange)	
ColorVu DS-2CE70KF0T-PFS	SMP(3K) ColorVu Indoor Audio Fixed Turret Camera SMP 24/7 color imaging Sensor,up to 20fps(2960x1665) 2.8/3.6mm lens, 0.001Lux @F1.0, 20m white light distance DNR,BLC,HLC,DWDR,OSD Menu Built-in Mic,Audio up Coaxial(Only TVI),Switchable TVI/AHD/CVI/CVBS video signal output Plastic, 12VDC,Power supply no included	RM139.00	2 Years (one to one exchange)	
HIKVISION Web Camera				
DS-U02	2MP Web Camera • 2MP CMOS Sensor,up to 25fps/30fps(1920x1080) • 3.6mm lens, 0.1Lux/F1.2 • Built-in mic, USB 2.0 Type-A interface cable 1.5m • Operating System:Windows 7 above,Android 8.1 above,Linux 4.14above,macOS 10.12 above • Plastic, DC 5V ± 5% (USB),Plug-and-play	RM82.00	2 Years (one to one exchange)	
DS-UL2	2MP Live Web Camera • 2MP CMOS Sensor.up to 50fps/60fps(1920x1080) • 3.6mm lens, 0.1Lux/F1.2 • Built-in mic, Auto Focus, Built-in supplement light for bright imaging, USB 2.0 Type-C interface cable 2m, Magnetic bracket • Operating System:Windows 7 above, Android 8.1 above, Linux 4.14above, macOS 10.12 above • Plastic, DC 5V ± 5% (USB), Plug-and-play	RM344.00	2 Years	
DS-UVC-X12	2MP Portable Conference Camera 2MP CMOS Sensor.up to 25fps/30fps(1920x1080) 2.8mm lens, 0.1Lux/F2.2,120dB true WDR Built-in 4-mic array microphones,Built-in a full-range, high definition speakers,USB 3.0 Type-C interface cable 2m, Operating System:Windows 7 above,Android 8.1 above,Linux 4.14above,macOS 10.12 above Metal&Plastic&fabric, Built-in 2450 mAh lithium battery,DC 5V ± 5% (USB),Plug-and-play	RM717.00	2 Years	
Model	Descriptions	Srp(rm)	Warranty	
HIKVISION IP Camera				
DS-2CD1123G0E-I(L)	2MP Fixed Vandal Dome Network Camera 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@20fps,H.265 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m IR range 3D DNR, BLC,DWDR, IP67, IK10 Alarm Trigger Motion detection, Privacy mask Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included	RM144.00	2 Years (one to one exchange)	
DS-2CD1323G0E-I(L)	2MP Fixed Network Turret Camera 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@20fps,H.265 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m IR range 3D DNR, BLC,DWDR, IP67, IK10 Alarm Trigger Motion detection, Privacy mask Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included	RM139.00	2 Years (one to one exchange)	
DS-2CD1023G0E-I(L)	2MP Fixed Bullet Network Camera 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@20fps,H.265 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m IR range 3D DNR,BLC, DWDR, IP67 Alarm Trigger Motion detection, Privacy mask Front Cover: Metal,Back Cover&Bracket: Plastic,PoE/12VDC,power supply no included	RM139.00	2 Years (one to one exchange)	
	<u> </u>	l .	1	



TECHNOLOGY SDN BHD				
DS-2CD1323G2-LIU	2MP Smart Hybrid Light Fixed Turret Network Audio Camera • 1/2.9" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6,up to 30m white light • 3D DNR, BLC,HLC,DWDR, IP67 • Built-in Microphone, Motion 2.0 human and vehicle classification • Cover&Base:Plastic,Eyeball;Metal,PoE/12VDC,power supply no included	RM166.00	2 Years (one to one exchange)	
DS-2CD1023G2-LIU	2MP Smart Hybrid Light Fixed Bullet Network Audio Camera • 1/2.9" Progressive Sean CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6,up to 30m white light • 3D DNR, BLC,HLC,DWDR, IP67 • Built-in Microphone, Motion 2.0 human and vehicle classification • Front Cover:Metal,Back Cover&Bracket:Plastic,PoE/12VDC,power supply no included	RM166.00	2 Years (one to one exchange)	
DS-2CD1143G0-I	4MP Fixed Dome Network Camera • 1/3" Progressive Scan CMOS, ICR, Up to 2560x1440@20fps,H.265+ • 2.8/4mm lens, 0.01 Lux @F2.0, EXIR, up to 30m IR range • 3D DNR, BLC, IF67, IK10,120 dB true WDR • Alarm Trigger Motion detection, Privacy mask • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included	RM228.00	2 Years (one to one exchange)	
DS-2CD1043G0-I	4MP Fixed Bullet Network Camera • 1/3" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ • 2.8/4mm lens, 0.01 Lux @F2.0, EXIR, up to 30m IR range • 3D DNR,BLC, IP67,120 dB true WDR • Alarm Trigger Motion detection, Privacy mask • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included	RM228.00	2 Years (one to one exchange)	
DS-2CD1143G2-LIU	4MP Smart Hybrid Light Fixed Dome Network AudioCamera • 1/3" Progressive Scan CMOS,ICR.Up to 2560x1440@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6,up to 30m white light • 3D DNR, BLC,HLC,120dB ture WDR, IP67,IK08 • Built-in Microphone, Motion 2.0 human and vehicle classification • Base: Metal,Cover: Plastic,PoE/12VDC,power supply no included	RM254.00	2 Years (one to one exchange)	
DS-2CD1343G2-LIU	4MP Smart Hybrid Light Fixed Turret Network Audio Camera • 1/3" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6,up to 30m white light 3D DNR, BLC,HLC,120dB ture WDR, IP67 • Built-in Microphone, Motion 2.0 human and vehicle classification • Cover&Base:Plastic,Eyeball;Metal,PoE/12VDC,power supply no included	RM242.00	2 Years (one to one exchange)	
DS-2CD1043G2-LIU	4MP Smart Hybrid Light Fixed Bullet Network Audio Camera 1/3" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ 2.8.44mm lens, 0.005 Lux @F1.6.up to 30m white light 3D DNR, BLC,HLC,120dB ture WDR, IP67 Built-in Microphone, Motion 2.0 human and vehicle classification Front Cover: Metal Back Cover & Bracket: Plastic,PoE/12VDC,power supply no included	RM242.00	2 Years (one to one exchange)	
DS-2CD1163G2-LIU	6MP Smart Hybrid Light Fixed Dome Network Camera 1/2.4" Progressive Scan CMOS,ICR,Up to 3200 × 1800@20fps,H.265+ 2.8/4mm lens, 0.005 Lux @F1.6, up to 30m White Light 3D DNR,BLC,HLC, IP67, IK08,120 dB true WDR,Built-in Microphone Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included	RM294.00	2 Years (one to one exchange)	
DS-2CD1063G2-LIU	6MP Smart Hybrid Light Fixed Bullet Network Camera • 1/2.4° Progressive Scan CMOS,ICR,Up to 3200 × 1800@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6, up to 20m White Light • 3D DNR,BLC,HLC, IP67, 120 dB true WDR,Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included	RM279.00	2 Years (one to one exchange)	
DS-2CD1183G2-LIU	8MP Smart Hybrid Light Fixed Dome Network Camera 1/2.7" Progressive Scan CMOS,ICR,Up to 3840 × 2160@20fps,H.265+ 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m White Light 3D DNR,BLC, IP67, IK08,120 dB true WDR,Built-in Microphone Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification Base: Metal,Cover: Plastic, PoE/12VDC,power supply no included	RM336.00	2 Years (one to one exchange)	
DS-2CD1083G2-LIU	8 MP Smart Hybrid Light Fixed Bullet Network Camera • 1/2.7" Progressive Scan CMOS,ICR,Up to 3840 × 2160@20fps,H.265+ • 2.8/4mm lens, 0.01 Lux @F2.0, up to 30m White Light • 3D DNR,BLC, IP67, 120 dB true WDR,Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal,Cover: Plastic, PoE/12VDC.power supply no included	RM321.00	2 Years (one to one exchange)	
Varifocal Lens Camera				
DS-2CD1723G0-IZ (Motorized Varifocal)	2MP Motorized Varifocal Dome Network Camera 1/2.7" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ 2.8-12mm motorized lens, 0.005 Lux @F1.6,EXIR,up to 30m IR range 3D DNR,BLC,DWDR, IP67, IK10 Alarm Trigger Motion detection, Privacy mask Metal,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included	RM394.00	2 Years (one to one exchange)	
DS-2CD1A23G0-IZU (Motorized Varifocal)	2MP Motorized Varifocal PT Bullet Network Camera • 1/2.7" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 2.8-12mm motorized lens, 0.007 Lux @F1.6,EXIR,up to 50m IR range • 3D DNR, BLC,HLC, 1P66,120dB WDR • Alarm Trigger Motion detection,Built-in Microphone,Pan, tilt and zoom ability that enables the camera to capture larger and interested areas • Front cover.metal, body:metal, bracket:metal,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included	RM351.00	2 Years (one to one exchange)	



LECHINOLOGY SDIV BHD				
DS-2CD1743G0-IZ (Motorized Varifocal)	4MP Motorized Varifocal Dome Network Came 1/2.7" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ 2.8-12mm motorized lens, 0.005 Lux @F1.6,EXIR,up to 30m IR range 3D DNR,BLC, IP67, IK10,120dB WDR Alarm Trigger Motion detection, Privacy mask Metal,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included	RM438.00	2 Years (one to one exchange)	
DS-2CD1A43G0-IZU (Motorized Varifocal)	4MP Motorized Varifocal PT Bullet Network Camera 1/2.7" Progressive Scan CMOS,ICR,Up to 2560x1440@20fps,H.265+ 2.8-12mm motorized lens, 0.007 Lux @F1.6,EXIR,up to 50m IR range 3D DNR, BLC,HLC, IP66,120dB WDR Alarm Trigger Motion detection,Built-in Microphone,Pan, tilt and zoom ability that enables the camera to capture larger and interested areas Front cover:metal, body:metal, bracket:metal,MicroSD Slot(up to 256GB),PoE/12VDC.power supply no included	RM379.00	2 Years (one to one exchange)	
DS-2CD2743G2-IZS (Motorized Varifocal)	4MP AcuSense Motorized Vari-focal Dome Network Camera 1/3" Progressive Scan CMOS,ICR,Up to 2688x1520@30fps,H.265+ 2.8-12mm motorized VF Iens, 0.005 Lux @F1.6,EXIR, up to 40m IR range 3 streams,3D DNR,BLC/HLC,120dB WDR, IP67, IK10 VCA functions: Line crossing detection, Intrusion detection, Face detection Human/vehicle classification alarm All-metal, Audio/Alarm I/O,MicroSD Slot(up to 256GB); PoE/12VDC,power supply no included	RM671.00	2 Years	
DS-2CD2643G2-IZS (Motorized Varifocal)	4MP AcuSense Motorized Vari-focal Bullet Network Camera 1/3" Progressive Scan CMOS,ICR,Up to 2688x1520@30fps,H.265+ 2.8-12mm motorized VF Iens, 0.005 Lux @F1.6,EXIR, up to 40m IR range 3 streams,3D DNR, BLC/HLC,120dB WDR, IP67, IK10 VCA functions: Line crossing detection, Intrusion detection, Face detection Human/vehicle classification alarm All-metal, Audio/Alarm I/O,MicroSD Slot(up to 256GB); PoE/12VDC,power supply no included	RM671.00	2 Years	
DS-2CD1663G2-LIZU (Motorized Varifocal)	6MP Smart Dual Light Varifocal Bullet Network Camera 1/2.4" Progressive Scan CMOS,ICR,Up to 3200 × 1800@20fps,H.265+ 2.8~12mm motorized VF lens, 0.005 Lux @F1.6, up to 50m White Light 3D DNR,BLC,HLC, IP67,120 dB true WDR,Built-in Microphone Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification Base: Metal,Cover: Plastic, MicroSD Slot(up to 512GB);PoE/12VDC,power supply no included	RM498.00	2 Years (one to one exchange)	
DS-2CD1763G2-LIZU (Motorized Varifocal)	6MP Smart Dual Light Varifocal Dome Network Camera • 1/2.4" Progressive Scan CMOS,ICR,Up to 3200 × 1800@20fps,H.265+ • 2.8-12mm motorized VF lens, 0.005 Lux @F1.6, up to 30m White Light • 3D DNR,BLC,HLC, IP67,IK08,120 dB true WDR,Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base: Metal, MicroSD Slot(up to 512GB);PoE/12VDC,power supply no included	RM498.00	2 Years (one to one exchange)	
Model	Descriptions	Srp(rm)	Warranty	
MIKVISION IP Camera Acusense DS-2CD2143G2-1	4MP AcuSense Fixed Dome Network Camera 1/3" Progressive Scan CMOS,ICR,Up to 2688x1520@25fps,H.265+ 2.8/4mm lens, 0.005 Lux @FI.6, EXIR, up to 30m IR range 3 streams,3D DNR,BLC,HCL, IP67, IK10,120dB true WDR Human and vehicle targets classification,Line crossing detection,intrusion detection,Face detection Metal,MicroSD Slot(up to 512GB),PoE/12VDC,power supply no included	RM370.00	2 Years	
DS-2CD2043G2-I	4MP AcuSense Fixed Bullet Network Camera 1/3" Progressive Scan CMOS,ICR,Up to 2688x1520@25fps,H.265+ 2.8/4mm lens, 0.005 Lux @F1.6, EXIR, up to 40m IR range 3 streams,3D DNR,BLC,HCL, IP67, 120dB true WDR Human and vehicle targets classification,Line crossing detection,intrusion detection,Face detection Metal,MicroSD Slot(up to 512GB),PoE/12VDC.power supply no included	RM370.00	2 Years	
©cuSense DS-2CD2183G2-1	8MP(4K) AcuSense Fixed Dome Network Camera 1/2.8" Progressive Scan CMOS,ICR,Up to 3840x2160@20fps,H.265+ 2.8/4mm lens, 0.005 Lux @FI.6, EXIR, up to 30m IR range 3 streams,3D DNR,BLC,HPG1, IP67, IK10,120dB true WDR Human and vehicle targets classification,Line crossing detection,intrusion detection,Face detection Metal,MicroSD Slot(up to 512GB),PoE/12VDC.power supply no included	RM474.00	2 Years	
DS-2CD2083G2-I	8MP(4K) AcuSense Fixed Bullet Network Camera • 1/2.8" Progressive Scan CMOS,ICR,Up to 3840x2160@20fps,H.265+ • 2.8/4mm lens, 0.005 Lux @F1.6, EXIR, up to 40m IR range • 3 streams,3D DNR,BLC,HCL, IP67, 120dB true WDR • Human and vehicle targets classification,Line crossing detection,intrusion detection,Face detection • Metal,MicroSD Slot(up to 512GB),PoE/12VDC,power supply no included	RM474.00	2 Years	
RcuSense DS-2CD2783G2-IZS	8MP(4K) AcuSense Motorized Vari-focal Dome Network Camera 1/1.8" Progressive Scan CMOS, 20fps(3840×2160),ICR,25fps/30fps (3200x1800),H.265+ 2.8~12mm motorized VF lens,0.005 Lux @F1.6, EXIR, up to 40m IR range 3 streams,3D DNR,BLC/HLC,120dB WDR, IP67, IK10 VCA functions: Line crossing detection, Intrusion detection, Face detection,Human/vehicle classification alarm	RM859.00	2 Years	



DS-2CD2683G2-IZS	8MP(4K) AcuSense Motorized Vari-focal Bullet Network Camera • 1/1.8" Progressive Scan CMOS, 20fps(3840×2160), ICR, 25fps/30fps (3200x1800), H.265+ • 2.8-12mm motorized VF lens, 0.005 Lux @F1.6, EXIR, up to 40m IR range • 3 streams, 3D DNR, BLC/HLC, 120dB WDR, IP67, IK10 • VCA functions: Line crossing detection, Intrusion detection, Face detection, Human/vehicle classification alarm • All-metal, Audio/Alarm I/O, MicroSD Slot(up to 256GB), PoE/12VDC, power supply no included	RM859.00	2 Years	
DS-2CD2345G0P-I (Super Wide Angle)	4MP Super Wide Angle Fixed Turret Network Camera • 1/2.7" Progressive Scan CMOS,ICR,Up to 2688x1520@25fps,H.265+ • 1.68mm lens, 0.028 Lux @F2.0, EXIR, up to 10m IR range • 3 streams,3D DNR,BLC,HCL,120dB true WDR • 180°super wide field of view, Line Crossing, Intrusion, Unattended Baggage, Object Removal,Face Detection,Scene Change Detection • Metal,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included	RM496.00	2 Years	
DS-2CD2T45G0P-I (Super Wide Angle)	4MP Super Wide Angle Fixed Bullett Network Camera 1/2.7" Progressive Scan CMOS,ICR,Up to 2688x1520@25fps,H.265+ 1.68mm lens, 0.028 Lux @F2.0, EXIR, up to 20m IR range 3 streams,3D DNR,BLC,HCL,120dB true WDR, IP67 180°super wide field of view, Line Crossing, Intrusion, Unattended Baggage, Object Removal,Face Detection,Scene Change Detection Metal,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included	RM567.00	2 Years	
DS-2CD2D25G1/M-D/NF (Pinhole Camera)	2MP Covert Network Camera 1/2.8" Progressive Scan CMOS,ICR,1920 × 1080@60fps,H.265 2.8/4mm fixed lens, 0.002 Lux @F1.2, EXIR, up to 20m IR range 3D DNR,BLC,HCL,defog,120dB true WDR,Dimension 31.5 mm × 31.5 mm × 49.6 mm (1.2" × 1.2" × 2") 1ntrusion, line crossing detection, region entrance, region exiting detection, unattended baggage detection, object removal detection,Audio exception detection, defocus detection, scene change detection Audio input,12VDC,Ø 5.5 mm coaxial power plug,power supply no included	RM378.00	2 Years	
Model HIKVISION IP Camera	Descriptions	Srp(rm)	Warranty	
DS-2CV2Q21FD-IW	2MP Indoor Audio Fixed PT Network WiFi Camera 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.264 2.8/4mm lens, 0.01 Lux @F1.2,EXIR, up to 10m IR range 3D DNR, BLC,DWDR Built-in 2way Audio,2.4GHz WiFi, Alarm Trigger Motion detection,Privacy mask Plastic,MicroSD Slot(up to 128GB),DC 5V,micro USB interface, power cable included	RM184.00	2 Years (one to one exchange)	
DS-2CV1021G0-IDW1	2MP Outdoor Fixed Bullet Network WiFi Camera 1/2.7" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ 2.8/4mm lens, 0.028 Lux @F2.0, up to 30m IR range 3D DNR, BLC,HLC Built-in Microphone,2.4GHz WiFi, Alarm Trigger Motion detection Front Cover: Metal,Back Cover Plastic,MicroSD Slot(up to 128GB),12VDC,power supply no included	RM189.00	2 Years (one to one exchange)	
ColorVu DS-2CD1027G2-L	2MP ColorVu Fixed Bullet Network Camera • 2MP 24/7 color imaging Sensor 1/2.8", Up to 1920x1080@25fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,BLC,HLC,DWDR, P67 • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Metal,PoE/12VDC,power supply no included	RM168.00	2 Years (one to one exchange)	
ColorVu DS-2CD1127G0-L	2MP ColorVu Fixed Dome Network Camera • 2MP 24/7 color imaging Sensor 1/2.8", Up to 1920x1080@25fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR, BIC,HLC,DWDR,IK08, P67 • Alarm Trigger Motion detection, Privacy mask • Base:Metal,Cover:Plastic,PoE/12VDC,power supply no included	RM187.00	2 Years (one to one exchange)	
ColorVu DS-2CD1047G2-L	4MP ColorVu Fixed Bullet Network Camera • 24/7 color imaging Sensor 1/3". Up to 2560x1440@20fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,HLC,BLC, P67,120dB True WDR • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Metal,PoE/12VDC,power supply no included	RM276.00	2 Years (one to one exchange)	
ColorVu DS-2CD1147G2-L	4MP ColorVu Fixed Dome Network Camera • 24/7 color imaging Sensor 1/3", Up to 2560x1440@20fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,BLC,IK08, P67,120dB True WDR • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base:Metal,Cover:Plastic,PoE/12VDC,power supply no included	RM282.00	2 Years (one to one exchange)	
ColorVu DS-2CD1047G2-LUF	4MP ColorVu MD 2.0 Fixed Bullet Network Camera • 24/7 color imaging Sensor 1/3", Up to 2560x1440@20fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,BLC,IK08, P67,120dB True WDR, Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base:Metal,Cover:Plastic,PoE/12VDC,power supply no included	RM303.00	2 Years (one to one exchange)	
Color√u DS-2CD1147G2-LUF	4MP ColorVu Fixed Dome Network Audio Camera • 24/7 color imaging Sensor 1/3", Up to 2560x1440@20fps,H265+ • 2.8/4mm lens, 0.001Lux @F1.0, up to 30m white light distance • 3D DNR,BLC,IK08, P67,120dB True WDR, Built-in Microphone • Alarm Trigger Motion detection, Privacy mask,Motion 2.0 human and vehicle classification • Base:Metal,Cover:Plastic,PoE/12VDC,power supply no included	RM317.00	2 Years (one to one exchange)	
	Date: Teagle Visit assister of 2012 Exporter supply no included			



ColorVu DS-2CE70DF3T-PTS	2" 2MP ColorVu Audio Indoor Analog TVI PT Camera • 24/7 Color Imaging,TVI: 1080P@25 fps/30 fps • 2.8/3.6mm lens, 0.0005 Lux/F1.0, up to 20m IR range • 3D DNR,BLC,HLC,130dB True WDR Built-in Microphone,Alarm Trigger Motion detection, Pan: 0° to 350°,Tilt:0° to 75° • 12VDC,power supply no included	RM156.00		
DS-2AE4225TI-D	4" 2MP 25X Powered by DarkFighter IR Analog PTZ • 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps • 4.8-120mm lens, 0.005 Lux/F1.6, up to 100m IR range • 3D DNR,BLC,HLC,120dB True WDR, IP66 • 25× optical, 16 × digital Zoom, Preset/Patrol/Pattern/Pan Scan/Tilt Scan/Panorama Scan, privacy masks, Switchable TVI/AHD/CVI/CVBS video signal output • Come with wall mount bracket, 12VDC,Power supply included	RM1,012.00		
DS-2DE2C400MW-DE(F1)	2" 4MP IR Mini PT Dome Network Camera 1/3" Progressive Scan CMOS, Up to 2560x1440@25fps,H.265 2.8/4mm lens, 0.005 Lux/F1.2, up to 30m IR range 3D DNR,BLC,HLC,DWDR,IP66 Built-in 2way Audio,Alarm Trigger Motion detection, Pan: 0° to 340°,Tilt:-5° to 105° MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included	RM306.00		
DS-2DE2A404IW- DE3(C0)(S6)	2" 4MP 4x Zoom DarkFighter IR Mini PT Dome Network Camera(PTZ) • 1/2.8" Progressive Scan CMOS,ICR,Up to 2560x1440@25fps,H.265+ • 2.8-12mm lens, 0.005 Lux/F1.5, up to 20m IR range • 3D DNR,BLC,HLC,120dB True WDR, IP66,IK10 • 4× optical, 16 × digital Zoom,built-in microphone,line crossing, intrusion,Region Entrance/Exiting,umattended baggage,object removal detection,audio exception,Face detection • Audio I/O, MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included	RM557.00		
ScuSense ColorVu DS-2DE3A400BW- DE(F1)(T5)	3" 4MP ColorVu Network PT Network Camera • 1/1.8" Progressive Scan CMOS,Up to 2560x1440@30fps,H.265+ • 4mm lens, 0.0005 LuvFi.0, up to 30m white light distance • 3D DNR,BLC,HLC,120dB True WDR, IP66 • Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception,Human/vehicle classification alarm,Face capture • Built-in 2way Audio, MicroSD Slot(up to 256GB),PoE/12VDC,power supply included	RM633.00		
SeuSerise DS-2DE4225IW-DE(T5)	4" 2MP 25X Powered by DarkFighter IR Network Speed Dome(PTZ) • 1/2.8" Progressive Scan CMOS,ICR,Up to 1920x1080@25fps,H.265+ • 4.8-120mm lens, 0.005 Lux/F1.6,up to 100m IR range • 3D DNR,BLC,HLC,120dB True WDR, IP66 • 25× optical, 16× digital Zoom,Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception,Human/vehicle classification alarm,Face capture • Come with wall mount bracket,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply included	RM1,271.00		
ScuSerise DS-2DE4425IW-DE(T5)	4" 4MP 25X Powered by DarkFighter IR Network Speed Dome(PTZ) • 1/2.8" Progressive Scan CMOS,ICR,Up to 2560x1440@25fps,H.265+ • 4.8-120mm lens, 0.005 Lux/F1.6,up to 100m IR range • 3D DNR,BLC,HLC,120dB True WDR, IP66 • 25× optical, 16× digital Zoom,Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception,Human/vehicle classification alarm,Face capture • Come with wall mount bracket,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply included	RM1,398.00		
DS-2DE5432IWG-E	5" 4MP 32X Powered by DarkFighter IR Network Speed Dome(PTZ) • 1/2.8" Progressive Scan CMOS,ICR,Up to 2560x1440@25fps,H.265+ • 4.8-153mm lens, 0.005 Lux/F1.6.up to 150m IR range • 3D DNR, BLC,HLC,120dB True WDR, IP66 • 32× optical, 16× digital Zoom,Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception,Human/vehicle classification alarm,Face detection,Smart Tracking • Come with wall mount bracket,Audio I/O,,Alarm I/O, MicroSD Slot(up to 256GB),Hi-PoE+/24VAC,power supply included	RM2,179.00		
R _{CUSense} ColorVu DS-2SE4C225MWG- E(12F0)	4" TandemVu 2MP 25X Colorful & IR Network Speed Dome • Captures a large area and great details at the same time • 1Ch bullet camera: 1/2.8" Progressive Scan CMOS, Up to 1920x1080@30fps,0.0005 Lux @F1.0, 2.8mm lens,30m white light • 1Ch PTZ camera: 1/2.8" progressive scan CMOS, Up to 1920x1080@30fps,0.005 Lux @F1.6, 4.8 to 120 mm, 25x Optical & 16x Digital Zoom, 100m IR • 3D DNR,BLC,HLC,120dB True WDR, IP66 • Line crossing, intrusion,Region Entrance/Exiting,audio exception detection,Human/vehicle classification alarm,Face capture • Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply included	RM1,399.00		
DS-1005KI	USB Keyboard • Supports various cameras, NVRs, DVRs and also iVMS 4200 • Flexible 4-axis joystick • Support USB HID protocol • 5V DC,Power supply and communication by USB port directly	RM621.00		
DS-1602ZJ	Wall Mount Bracket • Aluminum alloy material with surface spray treatment • General design for indoor/outdoor • Suitable for speed dome pendent mounting	RM72.00		
DS-1663ZJ	Ceiling Mount Bracket • Aluminum alloy material with surface spray treatment • General design for indoor/outdoor • Suitable for speed dome ceiling mount	RM39.00		
Model HIKVISION Fish-eye Camera	Descriptions	Srp(rm)	Warranty	



TECHNOLOGY SDN BHD				
DS-2CD2955G0-ISU	5MP Fisheye Fixed Dome Network Camera • 1/2.5" Progressive Scan CMOS,ICR,Up to 2560x1920@25fps,H.265+ • 1.05mm lens, 0.01 Lux/F1.2, up to 8m IR range • 3D DNR,120dB True WDR • Support 14 display modes, Line crossing, intrusion,unattended baggage,object removal detection, face detection, scene change detection • Built-in Microphone,Alarm I/O, MicroSD Slot(up to 128GB),PoE/12VDC,power supply no included	RM704.00	2 Years	
DS-2CD6365G1-IVS	6MP Fisheye Network Camera 1/1/8" Progressive Scan CMOS,ICR,Up to 2560x2560@25fps,H.265+ 1.16mm lens, 0.01 Lux/F2.25, up to 15m IR range 3D DNR,BCL,HCL,DWDR,IP67,IK10 Support 20 display modes, Line crossing, intrusion,Region Entrance/Exiting,unattended baggage,object removal detection,audio exception detection. AI function: People Counting,Queue Management,Heat Map,Intersection Analysis Built-in 2way Audio,Alarm I/O, MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included	RM2,133.00	2 Years	
DS-2PT3326IZ-DE3(2.8-12mm)(2mm)	Mini PanoVu Network Camera • 3Ch Panoramic camera: 1/2.8" CMOS sensor, 2mm lens, 1920×1080p@30ps,10m IR • 1Ch PTZ camera: 1/2.8" CMOS sensor, 2.8-12mm lens,1920×1080p@30ps, 4× optical zoom, 8× digital zoom • 3D DNR,BCL,HCL,DWDR • Support PTZ linkage, Line crossing, intrusion,audio exception detection • Audio I/O,MicroSD Slot(up to 256GB),PoE/12VDC,power supply no included	RM 1,331.00	2 Years	
HIKVISION Thermal IP Camera	The same of the sa			
DS-2TD2617-3/QA	Thermal & Optical Bi-spectrum Network Bullet Camera • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 3.1mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD< 40mk,Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 4mm fixed lens,40m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • 1P67,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included	RM1,308.00	2 Years	
DS-2TD2617-6/QA	Thermal & Optical Bi-spectrum Network Bullet Camera • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 6.2mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD< 40mk,Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 8mm fixed lens,40m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • 1P67,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included	RM1,403.00	2 Years	
DS-2TD2617-10/QA	Thermal & Optical Bi-spectrum Network Bullet Camera • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 9.7mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD< 40mk,Thermographic accuracy: +/-8°C • Optical Module: 1/2.7° CMOS, 4MP(2688x1520), 8mm fixed lens,40m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • 1P67,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included	RM 1,410.00	2 Years	
DS-2TD1217-2/QA	Thermal & Optical Bi-spectrum Network Turret Camera • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 1.8mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD< 4dmk, Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 2.1mm fixed lens, 15m IR range, 3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • 1P66,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included	RM1,308.00	2 Years	
DS-2TD1217-3/QA	Thermal & Optical Bi-spectrum Network Turret Camera • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 3.1mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD< 4dmk,Thermographic accuracy, +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 4mm fixed lens,15m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • IP66,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included	RM1,308.00	2 Years	
DS-2TD1217-6/QA	Thermal & Optical Bi-spectrum Network Turret Camera • High accuracy temperature exception alarm, -20 °C to 150 °C • Thermal Module: 6.2mm lens, 17micrometre, VOx UFPA Resolution:160x120 pixels, NETD< 40mk, Thermographic accuracy: +/-8°C • Optical Module: 1/2.7" CMOS, 4MP(2688x1520), 8mm fixed lens,15m IR range,3D DNR,BLC,120 dB WDR • Line Crossing, Intrusion, region entrance/exit, Temperature exception alarm,Strobe Light & Audio Alarm(Preset&user-defined voice) • IP66,Audio I/O,Alarm I/O, MicroSD Slot(up to 256GB),PoE+/12VDC,power supply no included	RM1,402.00	2 Years	
Model	Descriptions	Srp(rm)	Warranty	
HIKVISION DVR				
				L



TECHNOLOGY SDN BHD				
DS-7204HQHI-K1/E	4-ch 1080p 1U DVR TVI/ CVI/AHD/CVBS input adaptively, 4-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 1-ch P video input (up to 5-ch) Support 4-ch line crossing detection and intrusion detection H.265 Pro+ video compression, CHO1-04:1080P/4MP Lite@15fps/ch I SATA interface,up to 10TB, 1RJ45,2 USB Ports, 12VDC 1.5A, power supply included	RM240.00	2 Years	
DS-7208HQHI-K1/E	8-ch 1080p 1U DVR TVI/ CVI/AHD/CVBS input adaptively, 8-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 2-ch IP video input (up to 10-ch) Support 4-ch line crossing detection and intrusion detection H.265 Pro+ video compression, CH01-08:1080P/4MP Lite@15fps/ch 1 SATA interface,up to 10TB, 1RJ45,2 USB Ports, 12VDC 1.5A, power supply included	RM380.00	2 Years	
iDS-7216HQHI-M2/S	16-ch 1080p 1U AcuSense DVR TVI/ CVI/AHD/CVBS input adaptively, 16-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 2-ch IP video input (up to 18-ch) 1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection H.265 Pro+ video compression, CH01-16:1080P/4MP Lite@15fps/ch, 1ch 4K UHD output,CVBS output 2 SATA interface,up to 10TB/each, 1RJ45,2 USB Ports, 12VDC, power supply included	RM689.00	2 Years	
EcuSense iDS-7232HQHI- M2/S(E)	32-ch 1080p 1U AcuSense DVR * TVI CVI/AHD/CVBS input adaptively, 32-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 2-ch IP video input (up to 34-ch) * 1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection * H.265 Pro+ video compression, CH01-16:1080P/4MP Lite@15fps/ch, 1ch 4K UHD output, CVBS output * 2 SATA interface.up to 10TB/each, 1RJ45, 2 USB Ports, 12VDC, power supply included	RM1,399.00	2 Years	
Rusense iDs-7204HUHI-M1/E	4-ch 5MP 1U AcuSense DVR *TVI CVI/AHD/CVBS input adaptively, 4-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 4-ch IP video input (up to 6-ch) *1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection *H.265 Pro+ video compression, 5MP@12fps,8MP@8fps, 1ch 4K UHD output,CVBS output *1 SATA interface.up to 10TB, 1RJ45.2 USB Ports, 12VDC, power supply included	RM348.00	2 Years	
Rusense iDS-7208HUHI-M1/E	8-ch 5MP 1U AcuSense DVR *TVI CVI/AHD/CVBS input adaptively, 8-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 4-ch IP video input (up to 12-ch) *1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection *H.265 Pro+ video compression, 5MP@12fps,8MP@8fps, 1ch 4K UHD output,CVBS output *1 SATA interface.up to 10TB, 1RJ45,2 USB Ports, 12VDC, power supply included	RM580.00	2 Years	
iDS-7216HUHI-M2/S	16-ch 5MP 1U AcuSense DVR • TVI/ CVI/AHD/CVBS input adaptively, 16-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 8-ch IP video input (up to 24-ch) • 1-ch face detection or 4-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, 5MP@12fps,8MP@8fps, 1ch 4K UHD output,CVBS output • 2 SATA interface,up to 10TB/each, 1RJ45,2 USB Ports, 12VDC, power supply included	RM1,217.00	2 Years	
RouSense iDS-7332HUHI-M4/S	32-ch 5MP 1U AcuSense DVR *TVI CVI/AHD/CVBS input adaptively, 32-ch HDTVI coaxial video & audio input, 4-ch RCA audio input, 32-ch IP video input (up to 64-ch) *Support POS triggered recording & POS information overlay,RAID 0, 1, 5, 6, 10 effectively avoids data loss risks *H.265 Pro+ video compression, 5MP@12fps,8MP@8fps, 1ch 4K UHD output,CVBS output *4 SATA interface,up to 12TB/each,1 eSATA,2 RJ45,3 USB Ports, Built in power switch	RM3,586.00	2 Years	
iDS-7204HTHI- M1/S(C)	4-ch 8MP(4K) 1U AcuSense DVR - TVI/ CVI/AHD/CVBS input adaptively, 4-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 4-ch IP video input (up to 8-ch) - 1-ch face detection or 4-ch false alarm filter (classify human&vehicle), Face picture detection, face picture search, Support 4-ch line crossing detection and intrusion detection - H.265 Pro+ video compression, 8MP@15fps, 1ch 4K UHD output, CVBS output - 1 SATA interface,up to 10TB, 1RJ45,2 USB Ports, Support Wi-Fi dongle, 12VDC, power supply included	RM634.00	2 Years	
iDS-7208HTHI- M2/S(C)	8-ch SMP(4K) 1U AcuSense DVR • TVI/ CVI/AHD/CVBS input adaptively, 8-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 8-ch IP video input (up to 16-ch) • 1-ch face detection or 8-ch false alarm filter(classify human&vehicle), Face picture detection, face picture search, Support 8-ch line crossing detection and intrusion detection • H.265 Pro+ video compression, 8MP@15fps, 1ch 4K UHD output, CVBS output • 2 SATA interface,up to 10TB/each, 1RJ45,2 USB Ports, Support Wi-Fi dongle, 12VDC, power supply included	RM1,235.00	2 Years	



### 1250 For an incompression (CRITICAL CORNICATION CONTROL CO	LECHNOLOGA 2010 BHD				
1. TOP CVENTION CONSTRUCTION and inclinated information of inclination of the control stocks on a substantial control of the c	iDS-E04HQHI-D	TVI/ CVI/AHD/CVBS input adaptively, 4-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 1-ch IP video input (up to 5-ch) Support 4-ch line crossing detection and intrusion detection, 2-ch false alarm filter(classify human&vehicle) H.265 Pro+ video compression, CH01-04:1080P/4MP Lite@15fps/ch Built-in 1024GB eSSD (960GB available),1RJ45,2 USB Ports, 12VDC 1A, power supply included	RM426.00	3 Years	
1. S. FARMENDE II. 1. S. FARMENDE III. 1. S. F	iDS-E08HQHI-B	TVI/ CVI/AHD/CVBS input adaptively, 8-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 2-ch IP video input (up to 10-ch) Support 4-ch line crossing detection and intrusion detection, 4-ch false alarm filter(classify human&vehicle) H.265 Pro+ video compression, CH01-08:1080P/4MP Lite@15fps/ch	RM565.00	3 Years	
Act Adapter for DYR-Pattern, Dorn scene, sec.	iDS-E04HUHI-B	TVI/ CVI/AHD/CVBS input adaptively, 4-ch HDTVI coaxial video & audio input, 1-ch RCA audio input, 1-ch IP video input (up to 5-ch) Support 4-ch line crossing detection and intrusion detection, 4-ch false alarm filter(classify human&vehicle) H.265 Pro+ video compression, CH01-04:5MP/4MP @15fps/ch	RM537.00	3 Years	
AC Adapter for DVR (Prin.) Imput:100-240V-2600Rt 1.7A max. Output:120V-233A. Different versions recorder requires different adapters, please confirm with your sales promot in a supplicable	VIS-AS-12V2A UKAC Power Adpater		RM9.00	6 Months	
CRI. 400E-VI	KPL-040F-VI		RM61.00	6 Months	
1.5. 1.5.	KPL-060F-VI	Output:+12.0V5.00A,Different versions recorder require different adapters, please confirm with your sales	RM72.00	6 Months	
1.4.5 Min H World NYR, advise for 2MP IPC -1.4.5 10 to APP resolution -1.5.7 10 NN 10 NN -1.5.7 10 NN		Descriptions	Srp(rm)	Warranty	
*4-th Up to 6MP resolution Incoming/Outgoing handwidth:49Mhps/80Mhps, H.265+ Decoding capability -4-th AMP@00ps or 1-th 8MP@00ps 1 SATA interfaceaut pt of FB, IR445; USB Ports, 48VDC 1.35A, power supply included *4-th U 4PoE 4K NVR, advise for 2MPPMMP & above IPC -4-th Up to 8MP resolution Incoming/Outgoing handwidth:49Mhps/80Mhps, H.265+ -1-th video analysis for human and vehicle recognition to reduce false alarm,4-th face picture comparison alarm Decoding capability -4-th 4MP@00ps or 1-th 8MP@00ps 1 SATA interfaceaut pt or 8TB, IR445; USB Ports, 48VDC 1.35A, power supply included **Seth Up to 8MP resolution Seth Up to 8MP resolution Incoming/Outgoing handwidth:56Mhps/80Mhps, H.265+ Decoding capability -4-th 48MP@00ps or 2-th 48MP@00ps 1 SATA interfaceaut pt or 8TB, IR445; USB Ports, 48VDC 1.85A, power supply included **Seth Up to 8MP resolution Incoming/Outgoing handwidth:56Mhps/80Mhps, H.265+ Decoding capability -4-th 48MP@00ps or 1-th 8MP@00ps 1 SATA interfaceaut pt or 8TB, IR445; USB Ports, 48VDC 1.88A, power supply included **Seth Up to 6MP resolution Incoming/Outgoing handwidth:56Mhps/80Mhps, H.265+ Decoding capability -4-th 4MP@00ps or 1-th 8MP@00ps 1 SATA interfaceaut pt or 8TB, IR445; USB Ports, 48VDC 1.88A, power supply included **Seth Up to 8MP resolution The outgoing behavior of the supplemental process of	DS-7104NI-Q1/4P/M	 4-ch Up to 4MP resolution Incoming/Outgoing bandwidth:40Mbps/60Mbps, H.265+ Decoding capability: 4-ch 1080P@30fps or 2-ch 4MP@30fps 	RM326.00	2 Years	
**-4-ch Up to 8MP resolution **Incoming/Outgoing bandwidth-40Mbps/80Mbps, H.265+ **-1-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm **Decoding capability*-4-ch 4MP@30fps or 1-ch 8MP@30fps **-1 8ATA interface,up to 8TB, IR145,2 USB Ports, 48VDC 1.35A, power supply included **S-ch Mini IU 8PoE NVR, advise for 2MP IPC **-8-ch Up to 4MP resolution **Incoming/Outgoing bandwidth-60Mbps/60Mbps, H.265+ **Decoding capability*-4-ch 1080P@30fps or 2-ch 4MP@30fps **1 SATA interface,up to 6TB, IR145,2 USB Ports, 48VDC 1.8A, power supply included **S-ch IU 8PoE 4K NVR, advise for 24MP IPC **-8-ch Up to 6MP resolution **Incoming/Outgoing bandwidth-80Mbps/60Mbps, H.265+ **Decoding capability*-4-ch 4MP@30fps or 1-ch 8MP@30fps **1 SATA interface,up to 8TB, IR145,2 USB Ports, 48VDC 1.88A, power supply included **S-ch IU 8PoE 4K NVR, advise for 22MP4MP & above IPC **-S-ch Up to 8MP resolution **Incoming/Outgoing bandwidth-80Mbps/80Mbps, H.265+ **-1-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm **Decoding capability*-4-ch 4MP@30fps or 1-ch 8MP@30fps **-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	DS-7604NI-Q1/4P	 4-ch Up to 6MP resolution Incoming/Outgoing bandwidth:40Mbps/80Mbps, H.265+ Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps 	RM427.00	2 Years	
- 8-ch Up to 4MP resolution - Incoming/Outgoing bandwidth:60Mps/60Mbps, H.265+ - Decoding capability: 4-ch 1080P@30fps or 2-ch 4MP@30fps - 1.8ATA interface.up to 6TB, IRJ45, 2USB Ports, 48VDC 1.8A, power supply included 8-ch IU 8PoE 4K NVR, advise for 2/4MP IPC - 8-ch Up to 6MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps - 1.8ATA interface.up to 8TB, IRJ45, 2USB Ports, 48VDC 1.88A, power supply included 8-ch IU 8PoE 4K NVR, advise for 2/MP/4MP & above IPC - 8-ch Up to 8MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - 1-ch video analysis for human and vehicle recognition to reduce false alarm, 4-ch face picture comparison alarm - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps - 1.8ATA interface.up to 10TB, IRJ45, 2USB Ports, 48VDC 1.88A, power supply included 8-ch IU 8PoE 4K NVR, advise for 2MP/4MP & above IPC - 8-ch Up to 8MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - 2-ch video analysis for human and vehicle recognition to reduce false alarm, 4-ch face picture comparison alarm - Decoding capability: 4-ch 4MP@30fps - 2 SATA interface.up to 10TB, IRJ45, 3 USB Ports, 48VDC 1.88A, power supply included 8-ch IU 8PoE 4K NVR, advise for 2MP/4MP & above IPC - 8-ch Up to 8MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - 2-ch video analysis for human and vehicle recognition to reduce false alarm, 4-ch face picture comparison alarm - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps - 2 SATA interface.up to 10TB, IRJ45, 3 USB Ports, 48VDC 2.5A, power supply included 8-ch Up to 6MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps	DS-7604NXI-K1/4P	4-ch Up to 8MP resolution Incoming/Outgoing bandwidth:40Mbps/80Mbps, H.265+ 1-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps	RM456.00	2 Years	
- 8-ch Up to 6MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps - 1 SATA interface,up to 8TB, 1RJ45;2 USB Ports, 48VDC 1.88A, power supply included S-ch 1U 8PoE 4K NVR, advise for 2MP/4MP & above IPC - 8-ch Up to 8MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - 1-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps - 1 SATA interface,up to 10TB, 1RJ45,2 USB Ports, 48VDC 1.88A, power supply included S-ch U 8PoE 4K NVR, advise for 2MP/4MP & above IPC - 8-ch Up to 8MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps - 2 SATA interface,up to 10TB, 1RJ45,3 USB Ports, 48VDC 2.5A, power supply included S-ch U 4K NVR without PoE, advise for 2/4MP IPC - 8-ch Up to 6MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps - 2 SATA interface,up to 10TB, 1RJ45,3 USB Ports, 48VDC 2.5A, power supply included S-ch U 4K NVR without PoE, advise for 2/4MP IPC - 8-ch Up to 6MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps - 2 SATA interface,up to 10TB, 1RJ45,3 USB Ports, 48VDC 2.5A, power supply included S-ch U 1 4K NVR without PoE, advise for 2/4MP IPC - 8-ch Up to 6MP resolution - Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ - Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps - RM385.00 - 2 Years	DS-7108NI-Q1/8P/M	 8-ch Up to 4MP resolution Incoming/Outgoing bandwidth:60Mbps/60Mbps, H.265+ Decoding capability: 4-ch 1080P@30fps or 2-ch 4MP@30fps 	RM456.00	2 Years	
**S-ch Up to 8MP resolution **Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ **1-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm **Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps **1 SATA interface,up to 10TB, 1RJ45,2 USB Ports, 48VDC 1.88A, power supply included **S-ch Up to 8MP resolution **Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ **2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm **Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps **2 SATA interface,up to 10TB, 1RJ45,3 USB Ports, 48VDC 2.5A, power supply included **S-ch Up to 6MP resolution **Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ **2 SATA interface,up to 10TB, 1RJ45,3 USB Ports, 48VDC 2.5A, power supply included **S-ch Up to 6MP resolution **Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ **Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps **Poeding capability: 4-ch 4MP@30fps **P	DS-7608NI-Q1/8P	 8-ch Up to 6MP resolution Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps 	RM570.00	2 Years	
* 8-ch Up to 8MP resolution * Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ * 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm * Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps * 2 SATA interface,up to 10TB, 1RJ45,3 USB Ports, 48VDC 2.5A, power supply included S-ch 1U 4K NVR without PoE, advise for 2/4MP IPC * 8-ch Up to 6MP resolution * Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ * Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps RM385.00 2 Years	DS-7608NXI-K1/8P	8-ch Up to 8MP resolution Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ 1-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps	RM623.00	2 Years	
• 8-ch Up to 6MP resolution • Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps RM385.00 2 Years	DS-7608NXI-K2/8P	8-ch Up to 8MP resolution Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps	RM818.00	2 Years	
	DS-7608NI-Q2	 8-ch Up to 6MP resolution Incoming/Outgoing bandwidth:80Mbps/80Mbps, H.265+ Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps 	RM385.00	2 Years	



LECHNOLOGY SON BHD				
DS-7608NI-M2	8-ch 1U 4K NVR without PoE, advise for 4/8MP IPC • 8-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:128Mbps/256Mbps, H.265+ • Decoding capability: 8-ch 8MP@30fps or 2-ch 32MP@30fps • 2 SATA interface,up to 16TB/each, 2RJ45,2 USB Ports, 12VDC 3.33A, power supply included	RM862.00	2 Years	
DS-7616NI-Q2/16P	16-ch IU 16P0E 4K NVR, advise for 2/4MP IPC • 16-ch Up to 6MP resolution • Incoming/Outgoing bandwidth:160Mbps/80Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 2 SATA interface,up to 8TB/each, 1RJ45,2 USB Ports, 100-240V,3.4A, power supply included	RM866.00	2 Years	
DS-7616NXI-K2/16P	16-ch IU 16PoE 4K NVR, advise for 2MP/4MP & above IPC • 16-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:160Mbps/160Mbps, H.265+ • 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • Decoding capability: 4-ch 4MP@30fps or 2-ch 8MP@30fps • 2 SATA interface,up to 10TB/each, 1RJ45,3 USB Ports, 100-240V,3.4A, power supply included	RM1,116.00	2 Years	
DS-7616NI-Q2	16-ch IU 4K NVR without PoE, advise for 2/4MP IPC • 16-ch Up to 6MP resolution • Incoming/Outgoing bandwidth:160Mbps/80Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 1-ch 8MP@30fps • 2 SATA interface,up to 8TB/each, 1RJ45,2 USB Ports, 12VDC, 2.1 A, power supply included	RM434.00	2 Years	
DS-7716NXI-K4/16P	16-ch 1.5U 16PoE 4K NVR without PoE, advise for 2MP/4MP & above IPC • 16-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:160Mbps/160Mbps, H.265+ • 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • Decoding capability: 6-ch 4MP@30fps or 3-ch 8MP@30fps • 4 SATA interface,up to 10TB/each, 1RJ45,3 USB Ports, 100-240V, power supply included	RM1,575.00	2 Years	
DS-7716NXI-K4	16-ch 1.5U 16PoE 4K NVR without PoE, advise for 2MP/4MP & above IPC • 16-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:160Mbps/160Mbps, H.265+ • 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • Decoding capability: 6-ch 4MP@30fps or 3-ch 8MP@30fps • 4 SATA interface,up to 10TB/each, 1RJ45,3 USB Ports, 100-240V,3.4A, power supply included	RM1,041.00	2 Years	
DS-7716NI-M4	16-ch 1.5U 8K NVR without PoE, advise for 4/8MP IPC - 16-ch Up to 8MP resolution - Incoming/Outgoing bandwidth:256Mbps/256Mbps, H.265+ - Decoding capability: 10-ch 8MP@30fps or 16-ch 4MP@30fps - 4 SATA interface,1 eSATA interfaceup to 16TB/each, 2RJ45,3 USB Ports, 100-240V, power supply includedsupply included	RM1,618.00	2 Years	
DS-7732NXI-K4	32-ch 1.5U 4K NVR without PoE, advise for 2/4MP & above IPC • 32-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:256Mbps/160Mbps, H.265+ • Decoding capability: 4-ch 4MP@30fps or 2-ch 8MP@30fps, • 2-ch video analysis for human and vehicle recognition to reduce false alarm,4-ch face picture comparison alarm • 4 SATA interface,up to 10TB/each, 2RJ45,3 USB Ports, 100-240V,power supply included	RM1,187.00	2 Years	
DS-9632NI-M8	32-ch 2U 4K NVR without PoE, advise for 2/4MP & above IPC 32-ch Up to 8MP resolution Incoming/Outgoing bandwidth:320Mbps/400Mbps, H.265+ Decoding capability: 8-ch 4MP@30fps or 4-ch 8MP@25fps,Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare 8 SATA interface,up to 16TB/each,1 eSATA, 2RJ45,3 USB Ports, 100-240V,power supply included	RM3,872.00	2 Years	
DS-9664NI-M8	64-ch 2U 4K NVR without PoE, advise for 2/4MP & above IPC • 64-ch Up to 8MP resolution • Incoming/Outgoing bandwidth:400Mbps/400Mbps, H.265+ • Decoding capability: 8-ch 4MP@30fps or 4-ch 8MP@25fps,Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare • 8 SATA interface,up to 16TB/each,1 eSATA, 2RJ45,4 USB Ports, 100-240V,power supply included	RM5,439.00	2 Years	
Model HIKVISION Switch	Descriptions	Srp(rm)	Warranty	
DS-3E1106P-EI/M	4 Port 100Mbps Smart Managed PoE Switch 4 x 10/100Mbps PoE ports, and 2 × 10/100Mbps RJ45 ports PoE power budget 45W,Network topology management, alarm push, network health monitor Max. 300m long distance transmission, 6KV surge protection	RM135.00	2 Years	
DS-3E1309P-EI/M	8 Port 100Mbps Smart Managed PoE Switch • 8 × 10/100Mbps PoE ports, and and 1 × Gigabit RJ45 port • PoE power budget 60W,Network topology management, alarm push, network health monitor • Max. 300m long distance transmission, 6KV surge protection	RM223.00	2 Years	
DS-3E1318P-EI/M	16 Port 100Mbps Smart Managed PoE Switch • 16 × 10/100 Mbps PoE ports, 1x gigabit RJ45 port, and 1x Gigabit combo • PoE power budget 130WM,Network topology management, alarm push, network health monitor • Max. 300m long distance transmission, 6KV surge protection	RM603.00	2 Years	



LECHNOLOGY SON BHD				
DS-3E1326P-EI/M	24 Port 100Mbps Smart Managed PoE Switch • 24 × 10/100 Mbps PoE ports, 1x gigabit R145 port, and 1x Gigabit combo • PoE power budget 230W,Network topology management, alarm push, network health monitor • Max. 300m long distance transmission, 6KV surge protection	RM736.00	2 Years	
DS-3E1506P-EI/M	4 Port Gigabit Smart Managed PoE Switch • L2, Smart Managed,4 × Gigabit PoE ports, and 2 × Gigabit RJ45 port • PoE power budget 45W,HPP Cloud managed, VLAN, STP/RSTP loop prefention, PoE watchdog, Max. 300 meter PoE transmission • 6KV surge protection	RM150.00	2 Years	
DS-3E1510P-EI/M	8 Port Gigabit Smart Managed PoE Switch • L2, Smart Managed,8 × Gigabit PoE ports, and 2 × Gigabit RJ45 port • PoE power budget 60W,HPP Cloud managed, VLAN, STP/RSTP loop prefention, PoE watchdog, Max. 300 meter PoE transmission • 6KV surge protection	RM278.00	2 Years	
DS-3E0518P-E/M	16 Port Gigabit Unmanaged PoE Switch • L2, Unmanaged, 16 × Gigabit PoE ports, 2× Gigabit SFP fiber optical ports • PoE power budget 125W • 6KV surge protection	RM782.00	2 Years	
DS-3E0526P-E/M	24 Port Gigabit Unmanaged PoE Switch • L2, Unmanaged,24 × Gigabit PoE ports, 2× Gigabit SFP fiber optical ports • PoE power budget 225W • 6KV surge protection	RM1,065.00	2 Years	
DS-3E1518P-SI	L2 16 Port Gigabit Smart Managed PoE Switch • L2, Smart Managed, 16 × Gigabit PoE ports, 2× Gigabit SFP fiber optical ports • PoE power budget 250W • Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push & Video Control & Preview, PoE watchdog to auto detect and restart the cameras that do not respond. • Max. 300m long distance transmission, 6KV surge protection	RM1,121.00	2 Years	
DS-3E1526P-SI	L2 24 Port Gigabit Smart Managed PoE Switch • L2, Smart Managed, 24 × Gigabit PoE ports, 2× Gigabit SFP fiber optical ports • PoE power budget 370W • Visualized Topology Management, Network Health Monitor, Real-Time Alarm Push & Video Control & Preview, PoE watchdog to auto detect and restart the cameras that do not respond. • Max. 300m long distance transmission, 6KV surge protection	RM1,482.00	2 Years	
HIKVISION Industrial Switch				
DS-3T1306P-SI/HS	Industrial 4 Port 100Mbps Smart Harsh PoE Switch • 4 × 100M PoE ports, 1 × gigabit RJ45 port and 1 × gigabit SFP Fiber Optical Port. • PoE power budget: 60W, Visualized topology management, Network Health Monitor • Max. 300m long distance transmission, 6KV surge protection, Wider temperature (- 30 to 65 °C) design.	RM322.00	2 Years	
DS-3T1310P-SI/HS	Industrial 8 Port 100Mbps Smart Harsh PoE Switch • 8x 100M PoE ports, 1x gigabit RJ45 port and 1x gigabit SFP Fiber Optical Port. • PoE power budget: 110W, Visualized topology management, Network Health Monitor • Max. 300m long distance transmission, 6KV surge protection, Wider temperature (- 30 to 65 °C) design.	RM537.00	2 Years	
DS-3T0506P	Industrial 4 Port Gigabit Unmanaged PoE Switch • 4 × Gigabit RJ45 port,2 × Gigabit fiber optical port • PoE power budget: 120W, Max. Port Power 30W • Adopt redundant dual power input design, 6KV surge protection, Wider temperature (-40 to 75 °C) design.	RM1,065.00	2 Years	
SFP Module				
HK-SFP-1.25G-20-1310	SFP Module,single mode and single fiber TX1310nm/1.25G, RX1550nm/1.25G, LC Connector, single mode and single fiber, 20km Distance Hot pluggable capability, Operating temperature 0-70°C To pair use with HK-SFP-1.25G-20-1550	RM99.00	2 Years	
HK-SFP-1.25G-20- 1550	SFP Module,single mode and single fiber • TX1550nm/1.25G, RX1310nm/1.25G, LC Connector, single mode and single fiber, 20km Distance • Hot pluggable capability, Operating temperature 0-70°C • To pair use with HK-SFP-1.25G-20-1310	RM112.00	2 Years	
HK-SFP-1.25G-20-1310-DF	SFP Module,Single mode and duplex fiber TX1310nm/1.25G, RX1310nm/1.25G, LC Connector, Single mode and duplex fiber, 20km Distance Hot pluggable capability, Operating temperature 0-70°C To pair use with HK-SFP-1.25G-20-1310-DF	RM95.00	2 Years	
Model	Descriptions	Srp(rm)	Warranty	
HIKVISION Wireless Bridge	Descriptions	STP(FIII)	warranty	
DS-3WF0AC-2NT	2.4Ghz 300Mbps 100m Elevator Wireless CPE(a pair 2pcs) • Up to 100 m wireless transmission distance • 300 Mbps 802.11n wireless,Built-in 8 dBi 2 × 2 MIMO Antenna • 12 V/1 A passive PoE or 12 V/1 A DC,Package Content: CPE(a pair),Power Adapter,Pole Mounting Straps	RM195.00	2 Years	
DS-3WF0FA-2N/O(2Pcs)	2.4Ghz 300Mbps 1KM 70° Wireless AP Bridge(a pair 2pcs) • Up to 1km wireless transmission distance • 300 Mbps 802.11n wireless,Built-in 7 dBi 2 × 2 MIMO Antenna,Visualized topology management • 12 VDC/1 A Passive PoE, Package Content: CPE x2,Power Adapter x2,10/100 Mbps PoE injector × 2, binding tape × 4	RM287.00	2 Years	
		l	l	I



DS-3WF02C-5AC/O(2Pcs)	SGhz 867Mbps 5km Outdoor Wireless CPE(a pair 2pcs) Up to 5km wireless transmission distance, Point, Point, Point-to-Multipoint 867 Mbps 802.11/a/n/ac wireless, Built-in 12 dBi 2 × 2 MIMO Antenna, Visualized topology management 12 VDC/I A Passive PoE, Package Content: CPE x2, Power Adapter x2, 10/100 Mbps PoE injector × 2, binding tape × 4	RM433.00	2 Years	
Model	Descriptions	Srp(rm)	Warranty	
HIKVISION Door Access				
DS-K1T8003EF	Fingerprint Access Control Terminal 2.4-inch LCD Display,Built-in EM card reading module, Support Fingerprint 1000 fingerprints, 1000 card and Max. 100,000 event records Communication: TCP/IP, ISUP5.0 Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm	RM207.00	2 Years	
DS-K1T8003MF	Fingerprint Access Control Terminal • 2.4-inch LCD Display,Built-in Mifare card reading module, Support Fingerprint • 1000 fingerprints, 1000 card and Max. 100,000 event records • Communication: TCP/IP, ISUP5.0 • Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm	RM207.00	2 Years	
DS-K1T804AEF	Fingerprint Access Control Terminal • 2.4-inch LCD Display,Built-in EM card reading module, Support Fingerprint • 3,000 fingerprints, 3,000 cards and 100,000 events storage • Communication via TCP/TP and Wi-Fi,RS-485, wiegand interface • Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM261.00	2 Years	
DS-K1T804AMF	Fingerprint Access Control Terminal • 2.4-inch LCD Display,Built-in Mifare card reading module, Support Fingerprint • 3,000 fingerprints, 3,000 cards and 100,000 events storage • Communication via TCP/TP and Wi-Fi, RS-485, wiegand interface • Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM261.00	2 Years	
DS-K1T321EX	Face Recognition Access Control Terminal • 2.4-inch LCD screen, 2 MP lens,Multiple authentication methods, including face,card (EM card), and PIN, etc. • 500 faces, 3000 cards, and 150,000 events • Communication via TCP/TPi,RS-485 interface • Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM307.00	2 Years	
DS-K1T321MX	Face Recognition Access Control Terminal • 2.4-inch LCD screen, 2 MP lens, Multiple authentication methods, including face, card (Mifare card), and PIN, etc. • 500 faces, 3000 cards, and 150,000 events • Communication via TCP/TP,RS-485 interface • Support Access Control and Time Attendance Function, Remotely opens door via Hik-Connect mobile client, Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM307.00	2 Years	
DS-K1T321EFX	Face Recognition Access Control Terminal • 2.4-inch LCD screen, 2 MP lens,Multiple authentication methods, including face, fingerprint, card (EM card), and PIN, etc. • 500 faces, 3000 cards, 3000 fingerprints and 150,000 events • Communication via TCP/TPi,RS-485 interface • Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM364.00	2 Years	
DS-K1T321MFX	Face Recognition Access Control Terminal • 2.4-inch LCD screen, 2 MP lens,Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. • 500 faces, 3000 cards, 3000 fingerprints and 150,000 events • Communication via TCP/TP,RS-485 interface • Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM364.00	2 Years	
DS-K1T321MFWX	Face Recognition Access Control Terminal • 2.4-inch LCD screen, 2 MP lens,Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. • 500 faces, 3000 cards, 3000 fingerprints and 150,000 events • Communication via TCP/TP and Wi-Fi,RS-485,wiegand interface • Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM393.00	2 Years	
DS-K1T342MFX	Face Recognition Access Control Terminal • 4.3-inch LCD touch screen, 2 MP lens, Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. Two-way audio • 1500 faces, 3000 cards, 3000 fingerprints • Communication via TCP/TP,RS-485 interface,12 VDC/1 A(power adapter included) • Support Access Control and Time Attendance Function, Remotely opens door via Hik-Connect mobile client, Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM553.00	2 Years	



Face Recognition Access Control Terminal (PoE) 4.3-inch LCD touch screen, 2 MP lens, Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. Two-way audio 1500 faces, 3000 cards, 3000 fingerprints Communication via TCP/TP,RS-485 interface, Power input: Power interface (power adapter included, 12 VDC/IA) or PoE (37 to 57 VDC/0.6 A) Power output: Power supply for xI door lock, 12 VDC/I A Support Access Control and Time Attendance Function, Remotely opens door via Hik-Connect mobile client, Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM572.00	2 Years	
Face Recognition Access Control Terminal - 7-inch LCD touch screen, 2 MP lens,Multiple authentication methods, including face, fingerprint, card (Mifare card), and PIN, etc. Two-way audio - 6000 faces, 6000 cards, 5000 fingerprints - Communication via TCP/TP and Wi-Fi,RS-485 interface. IP65 - Support Access Control and Time Attendance Function,Remotely opens door via Hik-Connect mobile client,Tamper alarm, Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out	RM1,388.00	2 Years	
Description	Srp(rm)	Warranty	
Single-door Access Controller Storage with 10,000 cards and 50,000 access control events, Uplink Communication: TCP/IP Accessible Card Reader: 2 Wiegand readers or RS485 reader; Input interface: Door Sensor×1, Door Switch×1, Case Input×1; Output interface: Door Switch Relay×1, Alarm Relay×4. Supports multi-door interlocking function, anti-passback function supports the Backup Battery Connection, Data can be saved when the access controller is powered off	RM419.00	2 Years	
Double-door Access Controller Storage with 10,000 cards and 50,000 access control events, Uplink Communication: TCP/IP Accessible Card Reader: 4 Wiegand readers or RS485 reader; Input interface: Door Sensor×2, Door Switch×2, Case Input×2; Output interface: Door Switch Relay×2, Alarm Relay×4. Supports multi-door interlocking function, anti-passback function supports the Backup Battery Connection, Data can be saved when the access controller is powered off	RM480.00	2 Years	
Four-door Access Controller Storage with 10,000 cards and 50,000 access control events, Uplink Communication: TCP/IP Accessible Card Reader: 4 Wiegand readers or RS485 reader; Input interface: Door Sensor×4, Door Switch×4, Case Input×3; Output interface: Door Switch Relay×4, Alarm Relay×4. Supports multi-door interlocking function, anti-passback function supports the Backup Battery Connection, Data can be saved when the access controller is powered off	RM542.00	2 Years	
1102 Series Card Reader • Mifare card reader • Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm • IP 64, Applied for 86 &120 Gang Box	RM93.00	2 Years	
1102 Series Card Reader • Mifare card reader, with keypad • Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm • IP 64, Applied for 86 &120 Gang Box	RM118.00	2 Years	
1102 Series Card Reader • EM card reader • Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm • IP 64, Applied for 86 &120 Gang Box	RM93.00	2 Years	
1102 Series Card Reader • EM card reader • Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm • IP 64, Applied for 86 & 120 Gang Box	RM118.00	2 Years	
Double Class Door Lock, include v1 remote controller			
Multiple authentication methods, including fingerprint, card (Mifare card), and PIN,APP, Max.100 fingerprints capacity, Max.1,000 ID card capacity Applicable glass door thickness:10-12mm Power supply mode 4 AAA batteries/Micro-USB emergency power supply interface	RM331.00	6 Months	
Remote control for door access/barrier/autogate(50m) * x1 Receiver,x2 controller, 50m distance * Rated Current: 12VDC * Frequency: 315 Mhz * Load Capacity: Single Circuit s 3.5A	RM74.00	6 Months	
Surface mounted magnetic lock (280kg/600lbs) 5 bolts Lock size: 250x47x25mm Holding force: 280KG Working voltage: 12/24V DC Working current: 400/200mA	RM64.00	6 Months	
Surface mounted magnetic lock (280kg/600lbs) 5 bolts,c/w buzzer for unlock alarm Lock size: 250x47x25mm Holding force: 280KG Working voltage: 12/24V DC Working current: 400/200mA	RM77.00	6 Months	
Bracket for Holding lock Plate Installation Size: 183x45x17mm Suitable for: 280KG/600LBS Lock magnetic loc	RM16.00	6 Months	
U Bracket Size : 182x45x28mm Suitable for: 280/350KG magnetic lock	RM15.00	6 Months	
	- 4.3-incl. CD touch screen, 2MP Ems. Multiple authentication methods, including face, fingerprint, card (Mifrice card), and 71 CVPT.PR.4-88 interface Power imput: Power interface (power adapter included, 12 VDC/IA) or PEC (37 to 57 VDC/0.6 A) - Power output: Dover supply for x1 does tools, 12 VDC/I Support Access Control and Time Attendance Panution, Remotely spens door via Illi-Connect mobile dent. Tamper almos, Supports distribution et alsts, including check in, check out, break in, break out, services, and the control and Time Attendance Panution, Remotely spens door via Illi-Connect mobile dent. Tamper almos, Supports distribution et al. 1, servicine in, evertime out - Face Recognition Access Control and Time Attendance Function. Remotely spens door via Hik-Connect mobile dient. Tamper almos, Support access to Support Access Control and Time Attendance Function. Remotely spens door via Hik-Connect mobile dient. Tamper alamo, Supports & attendance Function. Remotely spens door via Hik-Connect mobile dient. Tamper alamo, Supports & attendance status, including check in, check out, break in, break out, overtime in, overtime out - Doweription - Support Access Controller - Surgey with 10,000 cards and 50,000 access control events. Lipina Communication: TCPJP - Accessable Card Reader - Wisquant earlow on RSA85 reader, Input interface to Door Switch Lose Input-1; Output interface: Door Switch Relays1, Alamo Relays4 Supports multi-door intercheking function, anti-passback function supports the Backup Battery Connection, Data can be saved when the access controller is powered off - Bounded on Access Controller - Surgey with 10,000 cards and 50,000 access control events. Lipina; Communication: TCPJP - Supports multi-door intercheking function, anti-passback function supports the Backup Battery Connection, Data can be saved when the access controller is powered off - Bounded on Access Controller - Surgey with 10,000 cards and 50,000 access controller is powered off - Bounded on the Surgey of the Surgey	4-3-5-th. LCD touch serven. 2 Mr Jen. Multiple ambentication methods, including face, fingerprint, and Millare card, and Pick. C. Twoway and in Crimmination Mr. LCPT RISA-88 Interface. (**communication Mr. LCPT RISA-88 Interface.**) **Support Access Control and Time Attendance Functions. Remotely opens door via Hills-Connect mobile dient, Tamper alarms. Supports of attendance status, including check in, check out, break in, break out, wordrine in, worther out.** **Free Recognition Access Control and Time Attendance Functions. Remotely opens door via Hills-Connect mobile dient, Tamper alarms. Supports of attendance status, including check in, check out, break in, break out, wortline in, overtine out.** **Board Access Control and Time Attendance Functions. Remotely opens door via Hills-Connect mobile dient, Tamper alarms. Supports of attendance status, including check in, check out, break in, break out, wortline in, overtine out.** **Board Access Control and Time Attendance Functions. Remotely opens door via Hills-Connect mobile dient, Tamper alarms. Supports of attendance status, including check in, check out, break in, break out, wortline in, overtine out.** **Board-out Access Controller** **Sugad-out-Access Controller** **Sugad-out-Access Controller** **Sugad-out-Access Controller** **Possage with 10,000 cards and 50,000 access control events. Uplant Communication: TCPIP** **Possage with 10,000 cards and 50,000 access control events. Uplant Communication: TCPIP** **Possage with 10,000 cards and 50,000 access control events. Uplant Communication: TCPIP** **Possage with 10,000 cards and 50,000 access control events. Uplant Communication: TCPIP** **Possage with 10,000 cards and 50,000 access controller is powered off** **Possage with 10,000 cards and 50,000 access controller is powered off** **Possage wit	1-3. See LCD turch servers. 2 MP lean. Manipe authentication methods, including face, fingerptine, and Miller cardia, and Fixe. 7 Toward spatial of 1-100 faces, 2000 cards, 2000 language included, 12 NDCIA) or Pol. (97 to 57 VDCAs A) Pol. 100 faces, 2000 cards, 2000 car



L Bracket Size: 250x47x28mm Suitable for: 280kg magnetic lock	RM13.00	6 Months	
ZL Bracket Size: 250x47mm +180x53mm Suitable for: 280/350KG magnetic lock	RM26.00	6 Months	
Exit Button Plastic panel Exit Button 86*86mm	RM5.00	6 Months	
Touchless Exit Button	RM20.00	6 Months	
Emergency release button	RM16.00	6 Months	
Backup Power Supply Box 12V 3A	RM46.00	6 Months	
Backup Power Supply Box 12V 5A			
can put back up battery inside(Battery not include) Battery backup 12V 7AH			
125Khz EM Proximity white blank card	RM39.00	6 Months	
Read distance: 1 to 10cm Reading times: >100,000 Applications: access control and identification Thickness: 0.84 to 1.2mm Operating frequency: 125kHz	RM2.00	NA	
Mifare 1K Compatiable white blank card 13.56 MHz 1K Memory S50 reader and writer RFID Smart Card. Dimension:86×54×0.8(+/-0.04) mm. Working Frequency:13.56Mhz.	RM2.00	NA	
Description	Srp(rm)	Wrranty	
433MHz Wireless Control Panel Kits with keyfob • Supports Wi-Fi, TCP/IP, 4G communication methods, Support 64Zones • Supports Hik-Connect/Hik-Partner Pro/Web Portal/ IVMS4200/ Convergence Cloud • Kit Included: 1x Wireless Control Panel (DS-PWA64-L-WB) 1x Wireless Keyfob (DS-PKF1-WB) 1x Wireless PIR Detector (DSPDP15P-WG2-WB) 1x Wireless Magnetic Contact (DS-PDMC-EG2-WB)	RM623.00	2 Years (one to one exchange)	
433MHz AX Pro Wireless PIR Detector Two-way Tri-X wireless technology Communication,Range: 1200m (open area) PIR Detection Range: 15m / 85.9° Fully remote configurable through APP Installation Height: 1.8 to 2.4m Battery Type: 1 * CR123A batteries (included by default, easy replaceable) Battery Life: 5 years in working status(triggered 10 times every day)	RM122	2 Years (one to one exchange)	
433MHz AX Pro Wireless PIRCAM Detector Two-way Tri-X wireless technology Communication,Range: 800m (open area) PIR Detection Range: 12m / 85.9° Camera resolution:640°480 Lens Coverage: 88°(H), 68°(V) Fully remote configurable through APP Installation Height: 1.8 to 2.4m Battery Type: 1 * CR123A batteries (included by default, easy replaceable) Battery Life: 6 years in working status((triggered twice every week, 20 QVGA frames captured for every alarm)	RM321.00	2 Years (one to one exchange)	
AX Pro Wireless Magnetic Contact Two-way Tri-X wireless technology Communication,Range: 1200m (open area) -2-ch External Zones for wired sensors Fully remote configurable through APP Slim design for an unobtrusive (unnoticeable) installation Battery Type: 1 * CR123A batteries (included by default, easy replaceable) Battery Life: 5 years in working status(triggered 10 times every day)	RM91.00	2 Years (one to one exchange)	
AX Pro Wireless Magnetic Contact * Two-way Tri-X wireless technology Communication,Range: 1200m (open area) * Fully remote configurable through APP * Battery Type: 1 * CR2450 batteries (included by default, easy replaceable) * Battery Life: 3 years in working status(triggered 10 times every day)	RM68.00	2 Years (one to one exchange)	
433MHz AX Pro Wireless Magnet Shock Detector Two-way Tri-X wireless technology Communication,Range: 1200m (open area) 2-ch External Zones for wired sensors Fully remote configurable through APP Slim design for an unobtrusive (unnoticeable) installation Battery Type: 1 * CR123A batteries (included by default, easy replaceable) Battery Life: 3 years in working status(triggered 10 times every day)	RM114.00	2 Years (one to one exchange)	
433MHz AX Pro Wireless Glass Break Detector Two-way Tri-X wireless technology Communication,Range: 1200m (open area) Fully remote configurable through APP 2-ch External Zones for wired sensors Battery Type: 2 * CR123A batteries (included by default, easy replaceable) Battery Life: 5 years in working status(triggered 10 times every day)	RM122.00	2 Years (one to one exchange)	
433MHz AX Pro Wireless Water Leak Detector Two-way Tri-X wireless technology Communication,Range: 1000m (open area) Fully remote configurable through APP Battery Type: 1 * CR2450 batteries (included by default, easy replaceable) Battery Life: 3 years in working status (triggered 10 times every day)	RM134.00	2 Years (one to one exchange)	
	Size: 2504-728mm gangeric lock ZL Bracket ZL Bracket ZL Bracket ZL Bracket ZL Bracket Size: SUSA-72mm + 180x53mm Suitable for 2804-73mm + 180x53mm Suitable for 2804-73mm + 180x53mm Touchises Exit Button Flouring beat Exit Button Size: SGL-380x/92fm(mm) Emergancy release button Reacting Function Backup Power Supply Box 12V 3A can put back up battery inside(Battery not include) Backup Power Supply Box 12V 3A can put back up battery inside(Battery not include) Backup Power Supply Box 12V 3A can put back up battery inside(Battery not include) Backup Power Supply Box 12V 3A can put back up battery inside(Battery not include) Backup Power Supply Box 12V 3A can put back up battery inside(Battery not include) Battery backup 12V 7AH 125Khr EM Proximity white blank card Read distance: 1o 10cm Reading times: >100,000 Applications: excess control and sidentification Thickness: 0.84 to 1.2mm Operating frequency: 125MHz Mifare 1K Compatible white blank card 125MHz IK Memory 500 reader and writer RFID Smart Card. Dimension:86r-54v.0.8(v/-0.04) mm. Working Frequency: 15.56Mhz. Description Description Description Description Description Description Description Description Assimitation for the control Panel (DS-PWA64-L-WB) 1x Wireless (Control Panel (DS-PWA64-L-WB) 1x Wireless (Datation Height: 1.8 to 2.4m Battery Type: 1 re (TR22A) batteries (included by default, casy replaceable) Battery Type: 1 re (TR22A) batteries (included by default, casy replaceable) Battery Type: 1 re (TR22A) batteries (included by default, casy replaceable) Battery Type: 1 re (TR22A) batteries (included by default, casy replaceable) Battery Type: 1 re (TR22A) batteries (included by default, casy replaceable) Batt	Size 2: 250.47.28mm Sizubab for 2201-2508, magnetic lock AL Brecket Size 250.47mm + 180.53mm Sizubab for 2201-2508, Companies bock Ext. Button From the Size Button 85 Western RM5.00 RM5.00 RM5.00 RM5.00 RM5.00 RM5.00 RM5.00 RM6.00 RM6.	Size 2 25047 236mm 4 1000-230 magnetic lock Similar for 2000 gas gasgetic lock Similar for 2000 gasgetic lock Size 25045 mm 4 1000-230 mm 5 middle for 2000 550 KC magnetic lock Size 25045 mm 4 1000-230 mm 5 middle for 2000 550 KC magnetic lock Size 25045 mm 4 1000-250 mm 5 middle for 2000 550 KC magnetic lock Size 25045 mm 4 1000-250 mm 5 middle for 2000 550 KC magnetic lock Size 25045 mm 4 1000 mm 5 middle for 2000 550 KC magnetic lock Size 25045 mm 5 middle Size 25045 mm 5 mi



LECHNOLOGY SON BHD				
DS-PDSMK-S- WB	433MHz Wireless Photoelectric Smoke Detector * Two-way RF wireless technology Communication,Range: 800m (open area) * Fully remote configurable through APP * Battery Type: Non Replaceable 1x CR17450 * Battery Life: 10 years(standby time)	RM179.00	2 Years (one to one exchange)	
DS-PRI-WB	433MHz AX PRO Series Repeater * Two-way Tri-X and Cam-X wireless technology; Communication,Range: 800m (open area) * Fully remote configurable through APP * Multiple Enrolling Methods: Power up, Remote ID, QR Code * Finding and connecting up to 8 PIRCAM or smoke detectors automatically, smart auto-pairing * Power supply 100 VAC to 240 VAC, Up to 35 hrs battery backup after mains lost, no worry about communication	RM287.00	2 Years (one to one exchange)	
DS-PS1-I-WB(Blue Indicator)	AX Pro Wireless Indoor Sounder with Blue Strobe Light * Two-way Tri-X wireless technology Communication,Range: 900m (open area) * 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm * Fully remote configurable through APP * Buzzer Decibel: 90 to 110dB,Front & rear panel tamper-proof * Battery Type: 3 * CR123A batteries (included by default, easy replaceable) * Battery Life: 3 years(triggered once every two weeks and alerting 90s for each triggering)	RM156.00	2 Years (one to one exchange)	
DS-PS1-I-WB(Red Indicator)	AX Pro Wireless Indoor Sounder with Red Strobe Light Two-way Tri-X wireless technology Communication,Range: 900m (open area) 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm Fully remote configurable through APP Buzzer Decibel: 90 to 110dB,Front & rear panel tamper-proof Battery Type: 3 * CR123A batteries (included by default, easy replaceable) Battery Life: 3 years(triggered once every two weeks and alerting 90s for each triggering)	RM156.00	2 Years (one to one exchange)	
DS-PS1-E-WB(Red Indicator)	AX Pro Wireless Outdoor Sounder with Red Strobe Light * Two-way Tri-X wireless technology Communication,Range: 900m (open area) * 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm * Fully remote configurable through APP * Buzzer Decibel: 90 to 110dB, IP65 approved for outdoor installation * Battery Type: 4 * CR123A batteries (included by default, easy replaceable) * Battery Life: 3 years(triggered once every two weeks and alerting 90s for each triggering)	RM274.00	2 Years (one to one exchange)	
DS-PDEB1-EG2-WB(B)(Single button)	433MHz AX Pro Wall-mounted Wireless Emergency Button * Two-way RF wireless technology Communication,Range: 800m (open area) * Fully remote configurable through App * IP66 daily environment protection * Frequency hopping against jamming for reliable transmission * Battery Type: 1 * CR2450 batteries (included by default, easy replaceable) * Battery Life: 3 years(triggered 10 times every day)	RM64.00	2 Years (one to one exchange)	
DS-PDEBP1-EG2-WB(Single button)	433MHz AX Pro Wireless Portable Emergency Button Accidental press protection Fully remote configurable through App 1P66 daily environment protection Frequency hopping against jamming for reliable transmission Optional lanyard and wristband accessory available Battery Type: 1 * CR2032 batteries (included by default, easy replaceable) Battery Life: 3 years(triggered 10 times every day)	RM64.00	2 Years (one to one exchange)	
DS-PMI-OIL- WB	433MHz AX Pro Relay Module • Two-way Tri-X wireless technology Communication,Range: 800m (open area) • Fully remote configurable through App • One-way ouput and one-way tamper input • Frequency hopping against jamming for reliable transmission • Voltage protection • Trigger By Zone Alarm, By Arm/Disarm/Away/Clear Alarm, By Faults, By Manually, By Schedule	RM100.00	2 Years (one to one exchange)	
DS-PMI-OIH- WB	433MHz AX Pro Wall Switch * Two-way Tri-X wireless technology Communication,Range: 800m (open area) * Fully remote configurable through App * One-way output * Frequency hopping against jamming for reliable transmission * Voltage and current protection * Trigger By Zone Alarm, By Arm/Disarm/Away/Clear Alarm, By Faults, By Manually, By Schedule	RM114.00	2 Years (one to one exchange)	
Model	Description	Srp(rm)	Warranty	
HIKVISION Hybrid Alarm				
DS-PHA64-Kit- WB	433MHz AX Hybrid Pro Control Panle Kit + Hybrid system: 8 on-board zones and 56 wired/wireless zones expandable,4 on-board outputs, and 60 wired/wireless outputs expandable • Supports arming/disarming via keypad, keyfob, APP, iVMS-4200, SMS and tag • Multiple configuration tools: APP, Web server, iVMS-4200 •Kit Included: -64 zone controller DS-PHA64-LP *1 -Keypad DS-PK1-LRT-HWB *1 -Magnetic door contact DS-PDI-MC-WS *1 -PIR detector DS-PDI-B-EG2 *2 -Keyfob DS-PKF1-WB *1 -Tag DS-PT-M1 *2	RM667	2 Years (one to one exchange)	



TECHNOLOGY SDN BHD				
DS-PHA64-LP	AX Hybrid PRO Control Panel Hybrid system: 8 on-board zones and 56 wired/wireless zones expandable,4 on-board outputs, and 60 wired/wireless outputs expandable Dual-path communication of alarm events and other signals over LAN, PSTN, Wi-Fi, GPRS or 3G/4G utilizing a main and backup channel with configurable priority 8-ch HD wirded PIRCAM for image verification, GIF can have maximu 20 pics,4-ch on-board IP camera video verification, supports video recording (5s pre-alarm + 2s post-alarm, or 2s pre-alarm + 5s post-alarm) for verification to the alarm receiving email or mobile client Supports arming/disarming via keypad, keyfob, APP, iVMS-4200, SMS and tag Multiple configuration tools: APP, Web server, iVMS-4200 Pushes alarm notification via messages, email and Hik-Connect 1 installer, 1 administrator, and 62 users Supports ISAPI, Cloud P2P, ISUP, CSV-IP and DC-09 protocol Supports 1 Speed-X Bus	RM460.00	2 Years (one to one exchange)	
DS-PM2-S	3/4G Communication Module • FDD-LTE B1/B3/B7/B8/B20 • Dual-Band UMTS/HSDPA/HSPA+B1/B8 • GSM/GPRS/EDGE 900/1800MHz	RM323.00	2 Years	
DS-PK1-LRT- HWB	Wired LCD Keypad * 80 × 25 mm LCD screen display * Supports arming and disarming by swiping cards * Supports remote arming and disarming via keyfob One-push to arm(Arming without password) * Supports user friendly operation menu * Supports displaying zone name on the LCD screen * Supports Fire/Panic/Medical alarm key * Supports 2 on-board alarm inputs and 1 on-board alarm output * Supports displaying the real-time system status by LED indicator Detachable wiring terminal for easy wiring and installation * Temper proof: cover and wall	RM234.00	2 Years (one to one exchange)	
DS-PM1-1802-H	Wired Input Expander * 8 on-board wired zones * Support 3EOL connection(Alarm: 1ΚΩ; Tamper: 1ΚΩ; Fault: 2.2ΚΩ) * Support zone alarm, tamper, masking, fault, short detection 1 power output for wired detectors 2 Speed-X bus, supporting wired input expander cascade mode	RM128.00	2 Years (one to one exchange)	
DS-PM1-04L-H	Wired Output Expander • 4 on-board low current relays, supporting 6-30V and up to 5A current • 1 power output, maximum 500mA • Powered by Speed-X technology, supporting expander cascading with 1 uplink • Speed-X port and 1 downlink Speed-X port	RM163.00	2 Years (one to one exchange)	
DS-PM1-RT- HWB	Tri-X Wireless Receiver(433MHz) • Wireless transmission distance up to 1300m • Supports 32 wireless detectors, 4 wireless indoor sounders and 8 wireless outdoor sounders	RM180.00	2 Years (one to one exchange)	
DS-PD1-EB	Panic Button • Flame retardant ABS shell • Capacity: ≤ 250V/300mA • Connection mode: NO/NC	RM11.00	2 Years	
DS-PDP18-EG2	Wired internal 18m PIR detector Up to 18m volumetric detection coverage, the Ellipse is the ideal solution for any small to large indoor rooms and spaces. Digital temperature compensation Automatic sensitivity 3D optics - Improves the detection of moving targets Creep-zone protection - covers the blind spot area directly below it, where an intruder may have otherwise avoided detection Selectable EOL resistors, Anti-insect interference Wide voltage 9 to 16 V wide voltage adaptation with polarity reverse connection protection IFT technology - automatically adjust the upper and lower alarm trip thresholds when exposed to electromagnetic or electrical interference and shift the thresholds before the detector goes into false alarm	RM36.00	2 Years (one to one exchange)	
DS-PD1-MC-WS	Surface mounted magnetic contact of plastic casing • ABS shell • Connection type: NC • Designed for the surface mounting on wood door • Active gap: 40 mm	RM11.00	2 Years	
DS-PS1-B	Wired Outdoor Siren Sound and LED flash indication separately Sound Decibel: 105dB at 30cm 1P54 protective level Dimension(WxHxD): 140*134*33mm Wieght: 185g Power supply: 8 ~ 16 V DC	RM63	2 Years (one to one exchange)	

^{*}Prices are subject to change without prior notice.Please Call for stock available